





# JLG® MOBILE ELEVATING WORK PLATFORMS

Today, more people are demanding environmentally friendly equipment. More municipalities are demanding "green" building for new construction and renovations. The JLG\* line of electric powered mobile elevating work platforms are the green machines in the lift industry.

JLG\* electric powered mobile elevating work platforms feature longer runtime, greater uptime and higher productivity. The energy-efficient electric drive boosts your productivity with industry-leading duty cycles.

These machines are specifically designed so you have fewer scheduled services, a quieter work area, less dependency on hydraulic oils and zero emissions. From job start to completion, whether you need a scissor lift, boom lift or mast lift, JLG has an electric lift to meet your needs and keep your job green.

"With JLG" machines, I can get the job done faster and with less impact on the environment."





### **READY TO WORK OVERTIME**

Experience the benefits of reduced charging time and longer runtime with ES Series scissor lifts. You can stay on the job longer, getting more work done in one day. And the optional application-specific accessory packages enhance productivity.

With only two hoses and four fittings, you're working with a cleaner machine that decreases scheduled service requirements and reduces the chance for leaks.

Up to 1,000 lb capacity, proportional controls for ease of operation and optional accessory packages give you exactly what you need to get the job done.

## "I'm always impressed with how much runtime we get before recharging."

### THE RIGHT CAPACITY FOR THE JOB

The ES Series features various restricted and unrestricted capacities based on indoor or outdoor application. The 2632ES is rated to carry 800 lb up to 20 ft indoors, while its unrestricted capacity outdoors is up to 500 lb. The 2646ES features a 1,000-lb unrestricted capacity indoors and a 500-lb unrestricted capacity outdoors. And, the 3246ES is restricted to 26 ft at 1,000 lb indoors, while unrestricted up to 700 lb in both indoor and outdoor applications.

### NARROW OR WIDE PLATFORMS

The 2632ES features a 32-in. wide narrow platform for access through standard doorways. The 2646ES and 3246ES provide a 46-in. platform for more worker tools or supplies.

# VERSATILE ENOUGH FOR ANY WORKSITE

From commercial construction to hospitals, schools and facilities maintenance applications, the R Series can be used virtually anywhere there's work to be done. The ruggedness of thick rubber tires and all-steel component doors and platforms make them extremely reliable. R Series scissor lifts deliver the value you need without sacrificing performance and quality.

With platform capacities up to 770 lb, operators can reduce the number of trips to the ground for additional tools and materials. An optional MDI display and improved battery charger enhance uptime by assisting with trouble-shooting.

### LOW COST OF OWNERSHIP

With a simplified pothole protection system that minimizes the number of moving parts and the associated repair costs, the R Series is a valuable solution for everyday job site needs.

### **IMPROVED SERVICEABILITY**

With no stacked components, the R Series makes it easy for service personnel tackle the task at hand without having to remove other components.





### **Longer Runtime**

On a single charge, the electric drive delivers more than double the battery life of hydraulic drive machines.



### **One-Handed Operation**

Fully proportional drive and lift control is smoother and more efficient.

## RSERIES



# Active Pothole Protection

Active pothole protection provides increased ground clearance.



### **Greater Serviceability**

Improved battery charger and all-steel swing-out component tray and for greater serviceability.



# OUTSTANDING PERFORMANCE, ON SLAB AND OFF

Handle a wide variety of terrain indoors and out, without noise and futures thanks to the quiet operation and zero emissions of the 4069LE. With the standard oscillating axle, 35% gradeability, rugged all-terrain tires and available all-wheel drive, you'll be able to go off the slab and into the mud with the 4069LE scissor lift.

There are two models available with working heights up to 46 ft and a maximum platform capacity of 1,000 lb. All models will fit through standard double doorways to get you to and from the work site.

The efficient direct electric drive system gives you the muscle you'll need for demanding jobs; and, you'll get double the duty cycles of other electric scissors with the deep cycle batteries. Plus, the M model has the multipower feature, which has an on-board, diesel-powered generator with improved fuel efficiency for lower costs.



### COMPACT. POWERFUL. PRODUCTIVE.

The ultra-compact 1230ES mast lift is compact enough to fit in a freight elevator and lightweight enough to be used on weight-sensitive floors. Its 5-inch turning radius navigates tight workspaces while heavy-duty steel wheels with non-marking rubber provide a more cushioned ride.

Charged and ready to go, the super-efficient electric drive increases your uptime and gives your productivity a lift. With 500 lb capacity, the 1230ES has the muscle to carry you and your gear, even at full height.

No chains, cables or rollers to grease or adjust in the mast means you've got lower maintenance requirements and operating costs. Plus, the 1230ES helps to keep your work environment clean; with only

four hoses, you greatly reduce the chance for hydraulics leaks.



Saloon-style swing gate for ease of entry and exit.





### **98% CLEANER**

Fewer hoses and couplings mean fewer potential leak points.



### 200 00 00 00 00



### Off-Slab Mobility

Full-time automatic traction control and an oscillating axle boost off-slab productivity.



### **Platform Extension**

A standard feature, the platform extension has a 250 lb capacity.





### Tool Tray

The workstation includes tool and fastener tray, 110V AC outlet and one-hand controller operation.



### Serviceability

All-steel swing-out battery doors have heavy-duty hinges.

Rugged design and strong 12 ft mast provide durability.



# PUTS HARD TO REACH WITHIN REACH

With the JLG Toucan® vertical mast lift, you can meet your overhead challenges head on. Work up, over and around assembly lines, shelving, ductwork or partitions more easily and without interferences. Positioning is easier with a 345° rotating mast, up to 32 ft of lift height and 15 ft of jib reach. With its 500-lb capacity and a long-running, environmentally friendly electric powered drive, the Toucan will help you boost productivity hour by hour, year after year.

## BUILT TO TAKE ON YOUR FACILITY CHALLENGES

Plant maintenance, retooling and changeovers, warehousing, inspection and remodeling, general contracting—you can count on the Toucan Series to help keep production moving.

### **AS VERSATILE AS YOUR NEEDS**

With thick rubber non-marking tires, clean and efficient electric power and 25% gradeability, you're equipped better than ever to meet your access challenges.

Smooth proportional controls, a narrow chassis and greater horizontal outreach are just some of the features that come standard and help you get the job done with greater speed and efficiency.

# EXPERIENCE ROUND-THE-CLOCK PERFORMANCE

Stay on the job longer than the competition thanks to the industry-leading duty cycles of JLG® E Series boom lifts. These environmentally friendly machines deliver maximum performance, including automatic traction control, which allows both drive wheels to work independently for improved traction on uneven surfaces.

E Series booms are available in a range of platform heights and chassis widths—all with enhanced platform capacity—to help you find the perfect machine to suit your work environment. Plus, the exclusive JibPLUS® articulating boom option has a 180° range of side-to-side movement, providing you with even greater access to hard-to-reach places.





## FOUCAN<sup>®</sup> SERIES



**Work Cleaner** 

Thick rubber non-marking tires leave facility floors intact.



**Greater Access** 

Compact dimensions for getting into hard-to-reach areas.

## 



JibPLUS® Boom Option

Gain greater reach with 180-degree range of side-to-side movement.



Narrow Width

Accomplish more with greater maneuverability in tight spaces.



# DIESEL-LIKE PERFORMANCE. HYBRID VERSATILITY.

The H340AJ and H800AJ models are 4WD boom lifts that combine diesel-like performance with the benefits of hybrid efficiency, so you can tackle jobs inside and out. By reducing fuel consumption and lowering maintenance costs, these hybrids offer a lower total cost of ownership.

### **SAME POWER AND PERFORMANCE**

New hybrid models have similar components to their diesel counterparts, so you get uncompromising performance with

the benefits of hybrid technology.

### INDOOR AND OUTDOOR USE

Less noise and lower emissions give access to job sites where traditional diesel machines are not allowed to operate. For enclosed facilities, that means a less disruptive, more productive working environment.

### **ENHANCED FUEL EFFICIENCY**

Using up to 40% less fuel\*, these versatile boom lifts combine electrical and mechanical power to tackle rough terrain and navigate inclines.

### **CLEAN AND GREEN, 60-FT MACHINE**

The EC600 Series gives you the most height in an electric powered boom lift and over 44 ft of horizontal outreach. With four configurations, you can choose from electric or multi-power, standard jib or horizontally pivoting jib with JibPLUS.\*

A 17,210 (7,807 kg) low gross vehicle weight and non-marking all-terrain tires let you work on slab or off without hesitation. With the Automatic Traction Control, optional all-wheel drive and standard oscillating axle, you won't need to be shy about traveling over rough terrain.





Whether your jobs include industrial applications, maintenance, construction or anything in between, the EC600 Series delivers with zero emissions and reduced noise levels.



# H340AJ & H800AJ



### **Reduced Maintenance**

With maintenance-free AGM batteries and a smaller Tier 4 Final engine, maintenance and service requirements are reduced.



### Low Emissions

Experience reduced fuel use\*, emissions, noise and maintenance.

# E06000 SERIES



**Optional All-Wheel Drive**Power through difficult terrain on the job site.



**Environmentally-Friendly**Electric power system
makes it possible to deliver

makes it possible to deliver zero emissions.



### TOW-PRO GOES WHEREVER YOU GO

The Tow-Pro® Series lets you tackle the same jobs as the other JLG° electric boom lifts, but with an easier option for transportation. You also have the choice of a 24V DC electric or gas-powered engine. And with the standard combination hitch, industry-leading 65 mph towing speed and hydraulic auto-leveling outriggers, you can have the Tow-Pro to the job site and working in no time.

Standard air and water lines to the platform let you tackle a variety of jobs, including residential maintenance, construction, pressure washing, tree trimming, exterior painting and maintenance tasks, with greater ease. Two models offer platform heights of 35 ft or 50 ft, and both have a 500 lb capacity for you and your tools.











The articulating jib on the T500J gets you into those hard-to-reach places.



### **OPTIONAL GENERATOR**

An accessory mounting tray accommodates a generator, air compressor or pressure washer.



### **Enhanced Control Panel**

Operator-friendly controls have one-touch outrigger leveling and interactive display in platform.



### Ease of Transport

Fits on a trailer or tilt-back truck (low weight, good gradeability, compact).

## 



### **Innovative Controls**

Detachable platform controls provide faster and more efficient boom positioning with one-hand operation of all boom functions.



### **Ease of Transport**

A standard combination hitch and adjustable height coupler make it easy to attach the Tow-Pro to most vehicles.



### **PUTTING YOUR WORK ABOVE EVERYTHING**

When it comes to JLG° Support, it's all about you. Your productivity. Your profitability. Your uptime. From the purchase of your first piece of equipment straight through to the training, parts and maintenance that follows.

### Customer Service Contact Center

You can be assured we'll be giving an all-out effort to support you. Just think of us as your personal on-call, full-service support team. We make it happen. Period.

### Financial Solutions

Maximizing your profits. Preserving your cash flow. Let our financing specialists help choose the program designed specifically for your needs.

### Aftermarket Parts

Keep your equipment running at peak performance with genuine replacement parts, accessories, attachments, rebuilt and competitive parts all from one source—JLG.

### Training


Knowing your equipment inside and out results in higher productivity on the job. Our instructor-led courses give you the hands-on time you need to successfully operate equipment.

### Service Centers

Your needs. Your uptime. JLG is on the job to fulfill your every need, from repair, reconditioning, same-day parts and much more. We're here to support you.

### Pre-Owned Equipment

As a high-value alternative to purchasing new equipment, you can search our used equipment inventory of pre-owned JLG and competitor products.



Optional Workstation in the Sky® accessory packages are designed for the specific needs of electricians, plumbers, contractors and plant maintenance professionals.

13

Note: Some options and accessories available exclusively through JLG  $^{\circ}$  Parts, Service and Support.

12

### **ACCESSORIES THAT EXTEND YOUR SCISSOR LIFT'S VERSATILITY**

Workstation in the Sky® accessory packages are designed to keep your tools and components within arm's reach. Choose from packages that feature a removable workstation that optimizes platform space with compartments for tools such as a reciprocating saw, drill, circular saw, battery charger and 6 in. x 6 in. component boxes. Plus, a pull-out tray is included to provide a flat working surface near the top of the rails.

### **PLUMBER'S PACKAGE**

Manufacturer-approved pipe racks provide positive retention of materials for plumbing contractors, while storage outside the platform helps prevent rail damage and optimizes space.

### **ELECTRICIAN'S PACKAGE**

For electrical contractor applications that require battery-powered tools, the JLG® workstation keeps your tools within reach and off the floor of the platform. A stowable workbench and molded pockets provide ample storage while leaving the workspace open to get the job done. Electrician's Tree carries six 500 ft wire spools to speed up wire pulling and reduce friction associated with ground-based wire trees.

### PLANT MAINTENANCE PACKAGE

The Plant Maintenance Package combines popular elements of the Electrician and Plumber packages to help plant maintenance professionals perform tasks, ranging from general repair to electrical and mechanical installation. In addition, a small welder powered by the machine batteries is included for light repairs.

Note: Some options and accessories available exclusively through JLG® Parts, Service and Support.

ES SERIES ACCESSORIES					
	1930ES*	2032ES*	2632ES	2646ES	3246ES
Electrician's Package	N/A	N/A	N/A	•	
Plumber's Package	N/A	N/A	N/A	•	
Plant Package	N/A	N/A	N/A	•	•
Workstation w/o 12V Plug					
Workstation w/12V Plug					
Panel Carrier	N/A			•	
Quik Welder* by Miller*					
Pipe Racks	N/A				
Vise	N/A	N/A	N/A		
Electrician's Tree		•		•	

\*Non-current models









### **Main Features**

- Best on-the-job performance-Double duty cycles for longer operating times, tight turning radius for maneuvering and positioning and a rugged design.
- Narrow aisle models-Efficiently access hard-to-reach areas for more productive maintenance projects
- Revolutionary new Workstation in the Skv\* options and accessories.

	2632ES	2646ES	3246ES
ES Series Electric Scissor Lifts			
Platform Height	25 ft 6 in. (7.77 m)	26 ft (7.92 m)	31 ft 9 in. (9.68 m)
Platform Capacity	800/500 lb (363/227 kg) <sup>1</sup>	1,000/500 lb (454/227 kg) <sup>2</sup>	1,000/700 lb (454/318 kg) <sup>3</sup>
No. Occupants (indoor/outdoor)	2/0	2/2	2/1
Platform Size	30x90.5 in. (0.76x2.3 m)	44x98.5 in. (1.12x2.5 m)	44x98.5 in. (1.12x2.5 m)
Overall Width	32 in. (81 cm)	46 in. (1.17 m)	46 in. (1.17 m)
Weight	4,635 lb (2,103 kg)	4,975 lb (2,257 kg)	4,975 lb (2,257 kg)
Tilt Rating—Side to Side (indoor/outdoor)	1.5°/NA	1.5°/2°	2°/2°
Tilt Rating—Fore and Aft	3°	3°	3°
Power Source	4 x 6V 220 amp-hr	4 x 6V 220 amp-hr	4 x 6V 220 amp-hr
Available Options			
1,000 Watt—AC Inverter/Charger			
Flashing Amber Beacon	•		•
Spring-Loaded Gate			
245 Amp-Hour Batteries	•		
AGM Batteries	•		
Lifting Lugs	•		
UL® EE Rating	•		•
Platform Padding	•		•
Platform Padding with Proximity Switches			
SkySense™	•	•	•


- 1. 2632ES 800 lb restricted to 20 ft (indoor); 500 lb unrestricted (indoor) 2. 2646ES 1,000 lb unrestricted (indoor); 500 lb unrestricted (outdoor) 3. 3246ES 1,000 lb restricted to 26 ft (indoor); 700 lb unrestricted (indoor/outdoor)

#### **Main Features**

- Up to 770 lb (350 kg) capacity for more tools and materials to get the job done
- Easy-to-use controls and 25 percent gradeability allow operators to work confidently on a variety of job sites
- Simple and reliable pothole protection system reduces calls and improves uptime

	R1932i	R1932	R2632	R3246	R4045
R Series Electric Scissor Lif	t				
Platform Height (indoor/outdoor)	19 ft/NA (5.8 m/NA)	19 ft/19 ft (5.8 m/5.8 m)	25 ft 6 in./19 ft (7.8 m/5.8 m)	32 ft/32 ft (9.8 m/9.8 m)	39 ft 3 in./29 ft (12 m/8.8 m)
Platform Capacity (indoor/outdoor)	507 lb/NA (230 kg/NA)	507 lb/507 lb (230 kg/230 kg)	507 lb/275 lb (230 kg/125 kg)	705 lb/507 lb (320 kg/230 kg)	770 lb/550 lb (350 kg/250 kg)
No. Occupants (indoor/outdoor)	1/0	2/1	2/1	2/1	3/1
Platform Size	62.7x25.4 in. (1.59x.64 m)	62.7x25.4 in. (1.59x.64 m)	84x41.6 in. (2.13x1.06 m)	84x41.6 in. (2.13x1.06 m)	96x41 in. (2.43x1.05 m)
Overall Width	32 in. (81 cm)	32 in. (81 cm)	32 in. (81 cm)	46 in. (1.17 m)	46 in. (1.17 m)
Weight	2,675 lb (1,213 kg)	3,353 lb (1,521 kg)	4,310 lb (1,955 kg)	5,410 lb (2,454 kg)	7,000 lb (3,175 kg)
Tilt Rating—Side to Side (indoor/outdoor)	2.75°/NA	1.75°/1.5°	1.5°/1.5°	2.5°/1.5°	1.5°/1.5°
Tilt Rating—Fore and Aft	2.75°	3.75°	3.5°	3.5°	3.5°
Power Source	4 x 6V 220 amp-hr	4 x 6V 220 amp-hr	4 x 6V 220 amp-hr	4 x 6V 220 amp-hr	4 x 12V 150 amp-hr
Available Options					
900W Inverter					
AGM Batteries					
Anti-Vandalism Package		•	•	•	
Coiled Platform Control Box Cable					
Eagle Performance Charger					
Flashing Amber Beacon					
Spring-loaded Gate					
White Noise Alarm					

For complete specifications, visit www.jlg.com 15



#### **Main Features**

- Double the duty cycles of competitive electric scissor lifts.
- Superior off-slab performance Full-time automatic traction control system, standard oscillating axle and all-terrain tires.
- Powerful options QuikCharge GenSet and all-wheel drive.
- Fold-down handrails.



### **Main Features**

- 35 ft (10.4 m) and 50 ft (15.2 m) models.
- Hydraulic auto-leveling outriggers for faster and easier set-up.
- 24V DC electric or gasoline powered engine.
- Platform controls with one-hand operation of boom functions.
- Accessory Mounting Tray accommodates customer-provided generator, air compressor or pressure washer.
- Standard air and water lines to the platform.
- Optional Drive and Set from the platform.

	4069LE	M4069LE
LE Series Large Electric Scissor Lifts		
Platform Height	40 ft (12.19 m)	40 ft (12.19 m)
Platform Capacity	800 lb (363 kg)	800 lb (363 kg)
No. Occupants (indoor/outdoor)	2/2	2/2
Platform Size	65 x 115 in. (1.65 x 2.92 m)	65 x 115 in. (1.65 x 2.92 m)
Overall Width	5 ft 9 in. (1.75 m)	5 ft 9 in. (1.75 m)
Weight	10,560 lb (4,790 kg)	10,860 lb (4,926 kg)
Tilt Rating—Side to Side	3°	3°
Tilt Rating—Fore and Aft	5°	5°
Power Source	8 x 6V 370 amp-hr	8 x 6V 370 amp-hr
Generator Set—M models		45 amp Diesel Kubota
Available Options		
110V-AC Power Pack Inverter		
Flashing Amber Beacon		•
Hydraulic Leveling Jacks	•	•
Self-Closing Entry Gate	•	•
Foam-Filled Sand/Turf Tires	·	•
Top Rail Padding	•	•
Rail and Deck Padding	•	•
Bio-Degradable Hydraulic Oil	•	•

	T350	T500J
Towable Boom Lifts		~0
Platform Height	34 ft 5 in. (10.5 m)	50 ft 9.5 in. (15.3 m)
Platform Capacity	500 lb (227 kg)	500 lb (227 kg)
Horizontal Outreach	20 ft 2 in. (6.14 m)	29 ft 5 in. (9.0 m)
Overall Width	4 ft 11.25 in. (1.5 m)	5 ft 7 in. (1.7 m)
Weight	3,400 lb (1,542 kg)*	4,800 lb (2,177 kg)*
Power Source—Electric	24V DC, 4 x 6V 220 amp-hr	24V DC, 4 x 6V 220 amp-hr
Gasoline Engine—Optional	Honda GX 270	Honda GX 270
*Machine Weights may increase with options.		
Available Options		
Platform Rotator		•
Material Hook—500 lb capacity		
Platform Mounted Glass/Panel Tray		
Spare Tire—Full Size		
Flashing Amber Beacon	•	
Lifting Lugs	•	·
2,500 Watt Generator	•	•

	E300AJP	
E300 Series Electric Boom Lifts		
Platform Height	29 ft 5 in. (8.96 m)	
Platform Capacity	500 lb (227 kg)	
Horizontal Outreach	20 ft 1 in. (6.14 m)	
Up and Over Height	13 ft 2 in. (4.01 m)	
Overall Width	48 in. (1.22 m)	
Weight	15,705 lb (7,123 kg)	
Power Source	48V DC 8 x 6V 305 amp-hr	
Available Options		
Platform Worklights		
1/2 in. Air Line to Platform		
1000 Watt Inverter		
UL* EE Rating		
375 amp-hr Batteries		
	·	


Main Fe
IVIAIII FE
 ■ 4 ft (1.
4 1 1 ( 1
LI DI LI
JibPLU
- ATC /A
■ ATC (A
(
perfor
perio.
Ultra c
_ 0.0.0
 _
■ Fast cy
<b>—</b> 1 ust cy



### **Main Features**

- 4 ft (1.22 m) articulating jib with optional JibPLUS°.
- ATC (Automatic Traction Control) improves performance on uneven surfaces.
- Ultra compact width of only 48 in. (1.22 m).
- Fast cycle times.


	H340AJ	H800AJ
1340AJ & H800AJ Articulating Boom Lifts		
Platform Height	33 ft 10 in. (10.33 m)	80 ft (24.38 m)
Platform Capacity	500 lb (227 kg)	500 lb (227 kg)
Horizontal Outreach	19 ft 11 in. (6.06 m)	51 ft 10 in. (15.8 m)
Jp and Over Height	17 ft (5.17 m)	32 ft 1 in. (9.78 m)
Overall Width	6 ft 4 in. (1.93 m)	8 ft (2.44 m)
Veight	9,860 lb (4,472 kg)	35,400 lb (16,057 kg)
Power Source–Electric	8 x 12V 100 amp-hr	8 x 12V 100 amp-hr
Diesel Engine	Kubota Z482 11.1 hp (8.3 kW)	Kubota Tier 4 Final 30 hp (22.3 kW)
Available Options		
30 x 48 in. (0.76 x 1.22 m) Platform		
/2 in. Air Line to Platform		
x 20 Non-Marking Foam-Filled Tires		
x 18 Solid Tires		
x 18 Non-Marking Foam-Filled Tires		
AC Generator		
ight Package		
Hostile Environment Kit		•
Flashing Amber Beacon	•	•
pecial Hydraulic Oils		
Self Closing Gate	•	
SkySense™		•



### **Main Features**

- Tier 4 Final, diesel-powered generator produces fewer emissions.
- 8 x 12v 100 amp-hour AGM batteries deliver longer runtime.
- Four direct electric drive motors provide optimal off-slab productivity with enough power for 45% gradeability.
- Four-wheel drive for exceptional terrainability.

16 For complete specifications, visit www.jlg.com
For complete specifications, visit www.jlg.com



### **Main Features**

- JibPLUS\* models provide access in and around confined work areas.
- ATC (Automatic Traction Control) improves performance on uneven surfaces.
- QuikCharge GenSet option provides automatic charging for continuous machine operation.

	E400AJP
E400 Series Electric Boom Lifts	
Platform Height	40 ft (12.19 m)
Platform Capacity	500 lb (227 kg)
Horizontal Outreach	22 ft 5 in. (6.83 m)
Up and Over Height	21 ft 6 in. (6.55 m)
Overall Width	5 ft 9 in. (1.75 m)
Weight—M Models, add 300 lb (136 kg)	13,700 lb (6,214 kg)
Power Source	48V DC 8 x 6V 370 amp-hr
Generator Set—M models	45 amp Kubota
Available Options	
Padding for Platform	
Light Package	·
UL® EE Rating	·
1200 Watt Inverter	•



### **Main Features**

- The fastest boom speeds in this class.
- ATC (Automatic Traction Control) improves performance on uneven surfaces.
- QuikCharge GenSet option provides automatic charging for continuous machine operation.
- Jib models provide access in and around confined work areas.

	E450AJ
E450 Series Articulating Boom Lifts	
Platform Height	45 ft (13.72 m)
Platform Capacity	500 lb (227 kg)
Horizontal Outreach	23 ft 9 in. (7.24 m)
Up and Over Height	25 ft 3 in. (7.7 m)
Overall Width	5 ft 9 in. (1.75 m)
Weight	14,400 lb (6,532 kg)
Power Source	48V DC 8 x 6V 370 amp-hr
Generator Set—H models	45 amp Kubota
Available Options	i de
Padding for Platform	
Solid Non-Marking Tires	0,
UL° EE Rating	10
1200 Watt Inverter	70
SkySense™	

	EC600SJ	H600SJ	EC600SJP	H600SJP
EC/H600 Electric Boom Lifts				
Platform Height	60 ft 3 in. (18.36 m)	60 ft 3 in. (18.36 m)	60 ft 4 in. (18.39 m)	60 ft 4 in. (18.39 m)
Platform Capacity	500 lb (227 kg)			
Horizontal Outreach	43 ft 3 in. (13.18 m)	43 ft 3 in. (13.18 m)	44 ft 5 in. (13.54 m)	44 ft 5 in. (13.54 m)
Overall Width	7 ft 11 in. (2.41 m)			
Weight	16,710 lb (7,580 kg)	16,710 lb (7,580 kg)	17,210 lb (7,807 kg)	17,210 lb (7,807 kg)
Power Source	48V DC, 8 x 6V 415 amp-hr			
Generator Set—M models	_	45 amp Diesel Kubota		45 amp Diesel Kubota
Available Options	<i>a</i> (1).			
30 x 48 in. (0.76 x 1.22 m) Platform	O			•
1/2 in. Air Line to Platform		•		•
Foam-Filled Tires		•		•
1200 Watt Inverter	•	•	•	•
Hostile Environment Kit <sup>1</sup>	•	•	•	•
UL <sup>®</sup> EE Rating				
Tow Package <sup>2</sup>				
Light Package³	•	•	•	•
Flashing Amber Beacon	•		•	
SkySense™		<u> </u>		•

- Includes console cover, boom wipers and cylinder bellows.
   2. 2WD only.
   Includes head and tail lights, as well as platform work lights and beacon.



#### **Main Features**

■ The world's first 60-foot electric boom — Indoor and outdoor versatility.

SPECIFICATIONS

- Indoor advantages Zero emissions, industry-leading noise reduction, non-marking tires and the lowest weight in its
- Outdoor advantages Rugged design with all-wheel drive, automatic traction control and oscillating axle.
- Available with 45 amp Kubota diesel-powered generator to maintain battery charge level during extended outdoor use.

**18** For complete specifications, visit **www.jlg.com** For complete specifications, visit www.jlg.com 19



#### **Main Features**

- Low weight and rubber tracks for enhanced maneuverability and accessibility.
- Compact design increases ease of transport.
- Electric and combustion combination power for efficient energy usage.

X430AJ	X500AJ	X600AJ	X770AJ	X1000AJ
es Boom Lifts				
43 ft 6 in. (13.30 m)	49 ft (14.95 m)	59 ft 3 in. (18.05 m)	77 ft 5 in. (23.60 m)	100 ft (30.48 m)
500 lb (227 kg)	500 lb (227 kg)	500 lb (227 kg)	500 lb (227 kg)	500 lb (227 kg)
21 ft 7 in. (6.60 m)	23 ft (7.0 m)	30 ft (9.1 m)	43 ft (13.1 m)	54 ft 2 in. (16.50 m)
29 in. (0.75 m)	31 in. (0.78 m)	31 in. (0.78 m)	39 in. (0.99 m)	47 in. (1.19 m)
4,392 lb (1,992 kg)	5,071 lb (2,300 kg)	6,571 lb (2,980 kg)	9,665 lb (4,384 kg)	16,790 lb (7,616 kg)
Honda iGX390 11.7 hp (8.7 kw)	Honda iGX390 11.7 hp (8.7 kw)	Honda iGX390 11.7 hp (8.7 kw)		
			Kubota D902 21.6 hp (16.1 kW)	Kubota D902 21.6 hp (16.1 kW)
100Ah 36V Lithium Ion	100Ah 48V Lithium-lon	100Ah 72V Lithium-lon	100Ah 83V Lithium-lon	150Ah 76V Lithium-lon
	25 Boom Lifts 43 ft 6 in. (13.30 m) 500 lb (227 kg) 21 ft 7 in. (6.60 m) 29 in. (0.75 m) 4,392 lb (1,992 kg)  Honda iGX390 11.7 hp (8.7 kw)	25 Boom Lifts  43 ft 6 in. (13.30 m) 49 ft (14.95 m)  500 lb (227 kg) 500 lb (227 kg)  21 ft 7 in. (6.60 m) 23 ft (7.0 m)  29 in. (0.75 m) 31 in. (0.78 m)  4,392 lb (1,992 kg) 5,071 lb (2,300 kg)  Honda iGX390 Honda iGX390 11.7 hp (8.7 kw)  100Ah 36V 100Ah 48V	25 <b>Boom Lifts</b> 43 ft 6 in. (13.30 m) 49 ft (14.95 m) 59 ft 3 in. (18.05 m) 500 lb (227 kg) 500 lb (227 kg) 500 lb (227 kg) 21 ft 7 in. (6.60 m) 23 ft (7.0 m) 30 ft (9.1 m) 29 in. (0.75 m) 31 in. (0.78 m) 31 in. (0.78 m) 4,392 lb (1,992 kg) 5,071 lb (2,300 kg) 6,571 lb (2,980 kg)  Honda iGX390 Honda iGX390 Honda iGX390 11.7 hp (8.7 kw) 11.7 hp (8.7 kw) 11.7 hp (8.7 kw)	25 Boom Lifts  43 ft 6 in. (13.30 m) 49 ft (14.95 m) 59 ft 3 in. (18.05 m) 77 ft 5 in. (23.60 m)  500 lb (227 kg) 500 lb (227 kg) 500 lb (227 kg) 500 lb (227 kg)  21 ft 7 in. (6.60 m) 23 ft (7.0 m) 30 ft (9.1 m) 43 ft (13.1 m)  29 in. (0.75 m) 31 in. (0.78 m) 31 in. (0.78 m) 39 in. (0.99 m)  4,392 lb (1,992 kg) 5,071 lb (2,300 kg) 6,571 lb (2,980 kg) 9,665 lb (4,384 kg)  Honda iGX390 Honda iGX390 11.7 hp (8.7 kw) 11.7 hp (8.7 kw)  Kubota D902 21.6 hp (16.1 kW)  100Ah 36V 100Ah 48V 100Ah 72V 100Ah 83V


	>>
8	


### **Main Features**

- Versatile articulating jib provides up to 14 ft 6 in. (4.42 m) up and over reach.
- 345° rotating mast for unmatched positioning capabilities.
- Capacity for two workers and supplies.
- Drive through doorways and narrow aisles.
- Navigate around multiple obstacles on the ground and in the air.

Toucan Series Mast-Style Boom Lifts			
Platform Height	20 ft 3 in. (6.2 m)	26 ft 6 in. (8.10 m)	32 ft 3 in. (9.83 m)
Platform Capacity—Unrestricted	500 lb (227 kg)	500 lb (227 kg)	500 lb (227 kg)
Horizontal Reach	6 ft 5 in. (1.97 m)	8 ft 8 in. (2.64 m)	14 ft 11 in. (4.55 m)
Overall Width	3 ft 3 in. (0.99 m)	3 ft 9 in. (1.14 m)	3 ft 9 in. (1.14 m)
	4,875 lb (2,210 kg)	6,900 lb (3,130 kg)	10,140 lb (4,600 kg)
Power Source	24V 225 amp-hr	24V 260 amp-hr	48V 260 amp-hr
Available Options			
1/2 in. Air Line to Platform	•		
Light Package			

20E





### **Main Features**

- Maintenance-free elevating mast design—No chains, cables or rollers to grease or adjust.
- Only four hydraulic hoses Less to maintain, minimizes leak potential.
- Compact dimensions and low GVW Fits on most elevators.

20 For complete specifications, visit www.jlg.com 21

To order go to Discount. Equipment. Com



