

MAXI-AIRTM

PORTABLE AIR COMPRESSOR





www.discount-equipment.com

Model	MA100	MA185	MA375DP	MA400	
Air Delivery			(0)		
Actual Free Air Delivery (cfm)	100 cfm	185 cfm	High Pressure: 330 Low Pressure: 375	400	
Normal Operating Pressure (PSI)	100 PSI		High Pressure: 150 Low Pressure: 100	100	
MAX Working Pressure (PSI)	115	PSI	175	125	
Receiver Tank Capacity (gal)	5.3 gal		20.3		
Lubrication System Capacity (gal)	2.6 gal	4.0 gal	10.6		
Air Valves	3/4" - qty 2	3/4" - qty 2	2" - qty 1 3/4" - qty 2		
Control Detail					
Control Display Outputs (Hourmeter, etc.)	Fuel Level Engine RPM Engine Coolant Temperature Glow Plugs Charging System ECO Mode Alarm & Error Codes		Fuel Level Engine RPM Engine Coolant Temperature Glow Plugs Charging System ECO Mode Alarm & Error Codes High / Low Pressure Mode Switch	Fuel Level Engine RPM Engine Coolant Temperature Glow Plugs Charging System ECO Mode Alarm & Error Codes	
Engine Detail					
Engine Make	Kubota	Yanmar	Kubota		
Engine Model	D1005	4TNV88C	V3800-T		
Engine Induction	Naturally Aspirated	Naturally Aspirated	Turbocharged with Charge Air Cooler		
Engine Displacement (L)	1.0 L	2.2 L	3.8 L		
Number of Cylinders	3 Cylinders	4 Cylinders			
Type of After-Treatment	None	None	Diesel Oxidation Catalyst (DOC) Selective Catalytic Reduction (SCR) Diesel Particulate Filter (DPF)		
Mechanical Output at Rated Speed (HP (kW))	24.8 Hp (18.5 kWm) @ 3,200 RPM	47.6 Hp (35.5 kWm) @ 3,000 RPM	115.8 Hp (86.4 kWm) @ 2,600 RPM		
Engine Speed @ MAX Load (RPM)	3,200 RPM	3,000 RPM	High Pressure: 2,700 Low Pressure: 2,400	2,600 RPM	
Engine Speed @ No Load (RPM)	1,800 RPM	1,350 RPM	1,300 RPM	1,300 RPM	
Engine Control Panel	Ignition Switch w/ Digital Display		LCD Screen		
Acceptable Fuel Types (Engine Only)	Ultra Low Sulfur Diesel (ULSD)				
Fuel Consumption @ Full Load (gal/hr)	1.6 gal/hr	2.4 gal/hr	High Pressure: 5.1 gal/hr Low Pressure: 5.0 gal/hr	5.5 gal/hr	
Fuel Run Time @ Full Load	6.5 hrs	10 hrs	9 hrs	8.5 hrs	
Diesel Exhaust Fluid (DEF) Tank Size (gal)	Not Applicable		5.3 gal		
DEF Consumption @ Full Load (gal/hr)	Not Applicable		0.12 gal/hr		
DEF Run Time @ Full Load	Not Applicable		44 hrs		
Engine Oil Capacity With Filter (gal)	1.2 gal	2.0 gal	3.4 gal		

TECHNICAL SPECS

Model	MA100	MA185	MA375DP	MA400	
Engine Detail (continued)				min too	
Oil Change Interval (hours)	500 hrs	500 hrs	500	hrs	
Engine Cooling System Capacity (gal)	1.1 gal	1.9 gal		gal	
Engine Fuel Filter Change Interval (hours)	500 hrs	500 hrs		hrs	
Electrical System Voltage			olt DC		
Battery Size	85D26R	95D31R	130	F51	
Battery (CCA)	615	620	843		
Air Compressor Detail					
Type of Compressor	Single-Stage Oil Cooled, Screw Type Compressor		Dual Pressure, Single- Stage Oil Cooled, Screw Type Compressor Single-Stage Oil Coole Screw Type Compressor		
Control Type	Unloader Valve Valve				
Lubricating System	Forced lubrication by compressed pressure				
Compressor Oil Change Interval (hours)	500 hrs				
Drive System	Direct driving wi	th gear coupling	Direct driving with	h rubber coupling	
Air Filtration		Two-Stage with tar	o-Stage with tangential pre-cleaner		
NVH - Noise, Vibration, Harshness					
Sound Level @ 23 ft (NO LOAD) - dBA	55 dBA	63 dBA	60 dBA		
Sound Level @ 23 ft (FULL LOAD) - dBA	68 dBA	76 dBA	76 dBA		
Weights and Dimensions - With Trailer					
Net Dry Weight (lbs)	1,393 lbs	2,070 lbs	4,197 lbs	4,227 lbs	
Operating Wet Weight NO fuel & DEF (lbs)	1,465 lbs	2,165 lbs	4,470 lbs	4,500 lbs	
Operating Wet Weight FULL fuel & DEF (lbs)	1,525 lbs	2,320 lbs	4,800 lbs	4,810 lbs	
Gross Vehicle Weight Ratings - GVWR (lbs)	2,200 lbs	2,975 lbs	5,080 lbs		
Length (in)	120.0 in	132.0 in	176.0 in		
Width (in)	55.3 in	68.0 in	78.0 in		
Track Width (in)	47.25	57.5 in	69.0 in		
Height (in)	53.5 in	60.0 in	71.0 in		
Truck Load Shipping Quantities - 48' flatbed		6			
Weights and Dimensions - Skid Mount	7				
Net Dry Weight (Ibs)	1,179 lbs	1, 797 lbs	3,836 lbs		
Operating Wet Weight NO fuel & DEF (lbs)	1,251 lbs	1,892 lbs	4,109 lbs		
Operating Wet Weight FULL fuel & DEF (lbs)	1,289 lbs	2,024 lbs	4,365 lbs		
Length (in)	64.0 in	78.0 in	107.0 in		
Width (in)	42.0 in	50.0 in	58.0 in		
Height (in)	38.0 in	47.0 in	56.0 in		
Number of Units on 48' Flatbed	8	6	3	3	
Number of Units on 53' Flatbed	9	6	3	3	

Model	MA100	MA185	MA375DP	MA400		
Trailer Detail						
Standard Trailer Coupler	Adjustable Heigl	Adjustable Height 2" Ball Coupler		t 3" Lunette Ring		
Optional Trailer Couplers	Adjustable Height: 2-5/16" Ball Coupler 2" Bulldog 2-5/16" Bulldog 3" Lunette Ring		Adjustable Height: 2" Ball Coupler 2-5/16" Ball Coupler 2" Bulldog 2-5/16" Bulldog			
Electrical Connector	4-Way Flat	Connector	7-Way Flat Pin Connector			
Tongue jack load capacity		5,00	0 lbs			
Tire Size	ST175/80D13 Load Range 'C'	ST205/75R15 Load Range 'C'	ST225/75R15 Load Range 'D'			
Axle Type	Single Axle w/ Leaf Spring					
Axle Quantity		1 <i>A</i>	xle			
Trailer Brake Type	Not required by the Federal Motor Vehicle Safety Standards (FVMSS) Electric with Breakaway Brakes (STD)			away Brakes (STD)		
Body Detail						
Fluid Containment		No Av	ailable			
Fuel Tank Size (gal)	10.6 gal	24 gal	47 gal			
Fuel Tank Material & Construction	Welded Steel	Rotationally Molded Polyethylene	Welded Steel			
Fuel fill port size	2.65 in dia	2.00 in dia	2.65 in dia			
Enclosure (Material & Gauge)		Steel - 14 Ga covers and doors				
Door Hinge Material	Steel hinge and hinge pins					
Lifting Eye		Lifting eye at top of machine				
Compliance & Certifications						
Fluid Containment (%)	Not Available					
USA DOT Compliant	Yes					
CSA Listed	Not CSA Listed					
Transport Canada Compliant	Yes					
EPA Tier Level - Engine Warranty Coverage	/,0	Tier 2	Final			
Body, Trailer, Air End & Controls	,		s and labor			
Engine	2 years parts only 1 year parts and labor 2 years parts only					
Available Options		_ , ,				
Fluid Containment	Not Available					
Skid Mount	✓	✓	✓	✓		
50 Foot Hose Reel	✓	✓	✓	✓		
Block Heater	✓	✓	✓	✓		
Battery Charger	✓	✓	✓	✓		
Battery Disconnect		✓				
2" Ball Coupler	✓	✓	✓	✓		
2" Bulldog Coupler	✓	✓	✓	✓		
2 5/16" Ball Coupler	✓	✓	✓	✓		
2 5/16" Bulldog Coupler	✓	✓	✓	✓		
3" Lunette Ring	✓	✓	✓	✓		
Telematics	√					

TO PURCHASE THIS PRODUCT PLEASE CONTACT US



Equipment Financing and Extended Warranties Available



Discount-Equipment.com is your online resource for commercial and industrial quality parts and equipment sales. 561-964-4949
visit us on line @ www.discount-equipment.com

Select an option below to find your Equipment

Search by Manufacturer

Search by Product Type

Request a Quote

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment, Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep, Small Line, Wanco, Yanmar