



Product Specifications:

	RZ60
Weight	17.6 lbs (8.0 kg)
Bar Length	up to 12-inches (30 cm)
Engine Speed	11500 +/- 500 rpm, electronically governed 2800-3200 rpm idle
Horsepower	4.2 hp (3.1 kW) @ 9500 rpm
Engine Type	2-stroke, single-cylinder, air-cooled
Displacement	3.9 cu-in (64 cc)

Unmatched Economy, Speed and Utility

- Narrow-kerf Diamond Chain cuts faster
- Plunge cuts up to 12-inches for deep, fast cutting
- Rear-port multi-chambered air filtration designed for wet-cutting
- Double-pad fixed WallWalker® for stable cutting and less vibration
- Decompression valve eases starting effort by 50%
- Ergonomic handle for balanced vertical and horizontal cutting
- Externally mounted clutch for increased cooling and longer life
- Chain mounted inside clutch provides better saw balance by placing bar closer to center of saw
- Compensating carburetor for reliability and performance even at altitude
- Starter designed for durability and performance in wet-cut environment
- All metal water valve construction provides longer life and smooth adjustment





DO YOU HAVE THE RIGHT TOOL?

DIAMOND CHAINS



Fastest Cutting, Most Economical Diamond Chain Available

- Three types for various materials and applications
 - ◆ Economy for the budget-minded occasional user
 - ◆ GP-Concrete, for general purpose cutting including light rebar
 - ◆ Premium-Abrasive, for cutting block and other abrasive material
- Laser-welded segments designed for durability in tough conditions
- MBS™ grade diamonds for high quality and long life
- Narrow .210" width for faster cutting
- Safe to use - does not have rotational kickback
- Proprietary steel alloy specified and used in chain components for increased durability
- Available in single units and also with guide bar combinations and volume buckets* for better value



* Bucket includes three chains and one guide bar

	Segment Height	Segment Length	Suitable For Abrasive Material	Over all Chain Life	Cutting Speed
Economy	.170"	.500"	◆	◆◆	=====●
GP-Concrete	.200"	.550"	◆◆◆	◆◆◆◆	=====●
Premium-Abrasive	.170"	.550"	◆◆◆◆	◆◆◆◆◆	=====●



ICS, Blount Inc. • 4909 SE International Way Portland, OR 97222 USA • Ph 800.321.1240 • Fax 503.653.4393 • www.Redzaw.com
 © ICS, Blount Inc. Redzaw® is a trademark and product division of ICS, Blount Inc. Specifications and pricing subject to change without notice. 1106