

Terex Construction Americas is a part of Terex Corporation, a manufacturer of over 700 products worldwide including aerial work platforms, construction, mining, utilities and roadbuilding. Other Terex products not included in this publication:

AERIAL WORK PLATFORMS

Articulating booms
Material lifts
Trailer-mounted booms
Portable aerial work platforms
Scissor lifts
Telescopic booms

UTILITIES & ROADBUILDING

Aerial devices – utilities
Asphalt mixing plants
Cable placers
Concrete mixers
Concrete pavers
Concrete production plants
Digger derricks
Pavement profilers
Reclaimers/stabilizers

CRANES

All terrain cranes
Boom truck cranes
Container/Reach stackers
Lattice boom cranes
Lift and carry cranes
Rough terrain cranes
Telescopic truck cranes
Tower cranes
Truck mounted cranes

MATERIALS PROCESSING & MINING

All wheel drive rear dump trucks
Crushers
Crushing and recycling systems
Drills
Screens
Surface mining equipment
Surface mining trucks
Trommels
Washing systems



Terex Construction Americas

8800 Rostin Road
Southaven, MS 38671
USA

TEL 662-393-1800
SALES 866-837-3923
PARTS & TECH SUPPORT 888-201-6008
FAX 662-393-1700
EMAIL sales@terexca.com
WEB terexca.com

Effective date: August 15, 2006. For further information, please contact your local distributor or the Terex sales office listed. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. Terex makes no other warranty, expressed or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries and all rights are reserved. "Terex" is a Registered Trademark of Terex Corporation in the USA and many other countries. Copyright ©2006 Terex Corporation



Product Guide | Americas Edition 2007

CONSTRUCTION



The Terex Value Proposition

Terex Corporation is a diversified global manufacturer of a broad range of equipment for the construction, quarrying, recycling, surface mining, shipping, transportation, refining, utility, and maintenance industries. Terex is dedicated to the manufacturing and marketing of high-quality capital equipment designed to improve our customers' productivity and return on invested capital. In addition to offering quality products at an affordable price, Terex offers many value-added benefits through its sales/marketing, finance, parts and service organizations. Terex, the third largest construction and mining equipment manufacturer in the world, has over 15,000 team members worldwide and manufacturing in over 47 facilities in North America, South America, Europe, Asia, and Australia. The Terex name is backed by hundreds of years of experience from over 50 respected brands that make up the Terex family.

Terex Construction Americas offers a broad range of hauling, digging, loading, compaction and material handling equipment for construction, infrastructure and recycling. Our construction products include:

- Articulated and rigid-frame off-highway trucks
- Compact and heavy excavators
- Wheel loaders
- Material handlers for scrap, recycling, logging and portside industries
- Scrapers
- Site dumpers
- Tandem asphalt rollers
- Telehandlers
- Tractor loader backhoes
- Wheeled and crawler excavators

Our products deliver the right combination of capabilities and value that can help assure desired return on invested capital. And the Terex commitment to provide the best product value possible includes readily-available and responsive distributor and factory product support resources that keep Terex products operating productively and profitably.

FINANCING

Terex has been successful at delivering the right equipment at the right price. Through Terex Financial Services (TFS) we assist our customers with managing their financial goals while meeting their equipment needs. TFS offers a variety of financing solutions customizable to match our customer's needs.

SUPPORT

Terex Construction Americas is dedicated to offering superior product support through our parts, service and sales teams to support our dealer network and customers. Our team members work together to ensure up-time for customers while always looking for new and innovative ways to get the job done.

TABLE OF CONTENTS

Off-Highway Trucks & Scraper.....	4-5
Heavy Hydraulic Excavators	6-7
Compact Crawler & Wheeled Excavators.....	8-9
Wheel Loaders	10-11
Tractor Loader Backhoes & Tandem Asphalt Rollers	12-13
Site Dumpers	14-15
Material Handlers	16-17
Telehandlers	18-19
Product Support.....	18-19



ARTICULATED TRUCKS						
	Maximum payload	Heaped capacity 2:1 SAE	Gross engine power	Net engine power	Net vehicle weight	Gross vehicle weight
TA27	27.5 ton (25 mt)	20.3 yd ³ (15.5 m ³)	365 hp (272 kW)	335 hp (250 kW)	48,280 lbs (21,900 kg)	103,395 lbs (46,900 kg)
TA30	30.9 ton (28 mt)	22.9 yd ³ (17.5 m ³)	385 hp (287 kW)	333 hp (248 kW)	49,430 lbs (22,420 kg)	111,308 lbs (50,485 kg)
TA35	35 ton (32 mt)	27.5 yd ³ (21.0 m ³)	400 hp (298 kW)	388 hp (289 kW)	64,547 lbs (29,279 kg)	139,506 lbs (63,279 kg)
TA40	40 ton (36.5 mt)	30.3 yd ³ (23.3 m ³)	450 hp (336 kW)	437 hp (326 kW)	67,804 lbs (30,820 kg)	151,579 lbs (68,820 kg)



RIGID TRUCKS						
	Maximum payload	Heaped capacity 2:1 SAE	Gross engine power	Net engine power	Net vehicle weight	Gross vehicle weight
TR35	35 ton (31.8 mt)	25 yd ³ (19.4 m ³)	400 hp (298 kW)	369 hp (276 kW)	52,300 lbs (23,725 kg)	122,300 lbs (55,475 kg)
TR40	40 ton (36.3 mt)	31.5 yd ³ (24 m ³)	525 hp (392 kW)	495 hp (370 kW)	77,200 lbs (35,025 kg)	157,200 lbs (71,325 kg)
TR45	45 ton (41 mt)	34 yd ³ (25.6 m ³)	525 hp (392 kW)	495 hp (370 kW)	81,870 lbs (37,135 kg)	171,870 lbs (77,960 kg)
TR60	60 tons (55 mt)	46 yd ³ (35 m ³)	650 hp (485 kW)	613 hp (457 kW)	90,940 lbs (41,250 kg)	210,490 lbs (95,680 kg)
TR70	72 ton (65 mt)	54.3 yd ³ (41.5 m ³)	760 hp (567 kW)	700 hp (522 kW)	105,140 lbs (47,690 kg)	248,440 lbs (112,690 kg)
TR100	100 ton (91 mt)	74.5 yd ³ (57 m ³)	1,050 hp (783 kW)	943 hp (703 kW)	147,710 lbs (67,000 kg)	347,715 lbs (157,720 kg)



SCRAPER						
	Heaped capacity 1:1 SAE	Struck capacity	Width of cut	Gross engine power	Net vehicle weight	Gross vehicle weight
TS14G	20 yd ³ (15.3 m ³)	14 yd ³ (10.7 m ³)	9 ft 10 in (3,000 mm)	48,000 lbs (21,770 kg)	352 hp (263 kW)	62,922 lbs (28,541 kg)


HEAVY HYDRAULIC EXCAVATORS

	Operating weight	Maximum digging depth	Maximum reach	Maximum capacity	Net engine power
TXC 140LC-1	30,600 lbs (13,900 kg)	18 ft 6 in (5,630 mm)	27 ft 1 in (8,260 mm)	0.68 yd ³ (0.52 m ³)	95 hp (71 kW) @ 1,850 rpm
TXC 175LC-1	38,360 lbs (17,400 kg)	20 ft 5 in (6,220 mm)	29 ft 9 in (9,070 mm)	0.92 yd ³ (0.7 m ³)	118 hp (88 kW) @ 1,950 rpm
TXC 180LC-2	38,933 lbs (17,400 kg)	20 ft 5 in (6,220 mm)	30 ft (9,070 mm)	1.22 yd ³ (0.93 m ³)	118 hp (88 kW) @ 1,950 rpm
TXC 225LC-1	47,400 lbs (21,500 kg)	21 ft 9 in (6,630 mm)	32 ft 6 in (9,910 mm)	1.22 yd ³ (0.93 m ³)	148 hp (110 kW) @ 1,950 rpm
TXC 225LC-2	47,400 lbs (21,500 kg)	21 ft 9 in (6,620 mm)	31 ft 11 in (9,910 mm)	1.28 yd ³ (1.67 m ³)	148 hp (110 kW) @ 1,900 rpm
TXC 255LC-1	54,200 lbs (24,600 kg)	22 ft 3 in (6,790 mm)	35 ft 7 in (10,240 mm)	1.44 yd ³ (1.1 m ³)	162 hp (121 kW) @ 2,000 rpm
TXC 255LC-2	54,200 lbs (24,600 kg)	22 ft 3 in (6,790 mm)	32 ft 10 in (10,010 mm)	1.44 yd ³ (1.1 m ³)	162 hp (121 kW) @ 2,000 rpm
TXC 300LC-2	65,904 lbs (29,890 kg)	26 ft 3 in (8,010 mm)	36 ft 11 in (11,270 mm)	2.29 yd ³ (1.75 m ³)	197 hp (147 kW) @ 1,900 rpm
TXC 340LC-2	77,603 lbs (35,200 kg)	27 ft 2 in (8,287 mm)	39 ft 7 in (11,748 mm)	2.39 yd ³ (1.83 m ³)	247 hp (184 kW) @ 1,750 rpm
TXC 420LC-2	93,480 lbs (42,400 kg)	27 ft 8 in (8,287 mm)	39 ft 4 in (11,748 mm)	2.83 yd ³ (2.16 m ³)	293 hp (218 kW) @ 1,800 rpm
TXC 480LC-2	104,700 lbs (47,500 kg)	25 ft 7 in (7,810 mm)	39 ft 9 in (12,120 mm)	3.73 yd ³ (2.86 m ³)	228 hp (245 kW) @ 1,800 rpm


COMPACT CRAWLER EXCAVATORS

	Operating weight	Max. dig depth	Maximum reach	Bucket capacity	Net engine power
TC16	3,792 lbs (1,720 kg)	7 ft 3 in (2.2 m)	12 ft 8 in (3.9 m)	1.38 - 6.18 ft ³ (40 - 147 L)	18 hp (13.3 kW)
TC20	4,455 lbs (2,020 kg)	8 ft 2 in (2.5 m)	14 ft 4 in (4.4 m)	1.38 - 6.18 ft ³ (40 - 147 L)	18 hp (13.3 kW)
TC29	6,480 lbs (2,940 kg)	9 ft 7 in (2.96 m)	16 ft 4 in (4.99 m)	1.4 - 4.6 ft ³ (40 - 181 L)	28 hp (20.5 kW)
TC35/TC35E	7,980 lbs (3,620 kg)	11 ft 8 in (3.6 m)	18 ft 9 in (5.7 m)	1.4 - 4.6 ft ³ (40 - 181 L)	32.5 hp (23.8 kW)
TC37	8,047 lbs (3,650 kg)	11 ft 1 in (3.38 m)	18 ft 6 in (5.68 m)	1.4 - 4.6 ft ³ (40 - 181 L)	32.5 hp (23.8 kW)
TC48	10,920 lbs (4,950 kg)	12 ft 10 in (3.9 m)	20 ft 4 in (6.2 m)	2.5 - 13.2 ft ³ (70 - 374 L)	47 hp (34.6 kW)
TC50	11,067 lbs (5,020 kg)	12 ft 2 in (3.7 m)	20 ft 4 in (6.2 m)	2.5 - 13.2 ft ³ (70 - 374 L)	39.4 hp (29 kW)
TC60	12,458 lbs (5,650 kg)	12 ft 3 in (3.8 m)	21 ft 0 in (6.4 m)	2.5 - 13.2 ft ³ (70 - 374 L)	51.5 hp (37.9 kW)
TC75	17,420 lbs (7,900 kg)	14 ft 7 in (4.44 m)	24 ft 5 in (7.4 m)	3.2 - 13.2 ft ³ (93 - 374 L)	72 hp (53 kW)
TC125	27,563 lbs (12,500 kg)	15 ft 4 in (4.67 m)	27 ft 2 in (8.28 m)	9.18 - 31.86 ft ³ (260 - 902 L)	94 hp (64 kW)


WHEELED EXCAVATORS

	Operating weight	Max. dig depth	Maximum reach	Bucket capacity*	Net engine power
TW110	24,230 lbs (10,990 kg)	14 ft 2 in (4.3 m)	27 ft 4 in (8.3 m)	0.34 - 1.18 yd ³ (0.26 - 0.90 m ³)	91 hp (67 kW)
1705 M	34,613 lbs (15,700 kg)	18 ft 8 in (5.7 m)	30 ft 2 in (9.2 m)	1.0 yd ³ (0.75 m ³)	148 hp (110 kW)
1905 M	39,683 lbs (18,000 kg)	20 ft 4 in (6.2 m)	31 ft 8 in (9.65 m)	1.1 yd ³ (0.84 m ³)	182 hp (134 kW)
2205 M	46,297 lbs (21,000 kg)	22 ft 2 in (6.75 m)	34 ft 3 in (10.5 m)	1.49 - 1.75 yd ³ (1.14 - 1.34 m ³)	182 hp (134 kW)

*Not permitted for every type

of boom. Please contact your Terex representative for more information.



LARGE WHEEL LOADERS						
	Operating weight	Std bucket capacity	Breakout force	Tipping load straight	Tipping load fully articulated	Gross engine power
TXL 160-1	18,960 lbs (8,600 kg)	2.1 yd ³ (1.6 m ³)	17,200 lbs (7,800 kg)	13,440 lbs (6,100 kg)	11,460 lbs (5,300 kg)	99 hp (74 kW) @ 2,200 rpm
TXL 200-1	24,250 lbs (11,000 kg)	2.35 yd ³ (1.8 m ³)	23,150 lbs (10,500 kg)	18,740 lbs (8,500 kg)	16,315 lbs (7,400 kg)	158 hp (118 kW) @ 2,000 rpm
TXL 200-2	25,673 lbs (11,645 kg)	2.5 yd ³ (1.9 m ³)	23,149 lbs (10,500 kg)	19,555 lbs (8,870 kg)	16,667 lbs (7,560 kg)	143 hp (107 kW) @ 2,000 rpm
TXL 250-1	30,420 lbs (13,800 kg)	3.1 yd ³ (2.4 m ³)	29,100 lbs (13,200 kg)	26,455 lbs (12,000 kg)	21,605 lbs (9,800 kg)	170 hp (127 kW) @ 2,000 rpm
TXL 250-2	30,865 lbs (14,000 kg)	3.25 yd ³ (2.5 m ³)	20,101 lbs (89 kN)	26,896 lbs (12,200 kg)	22,482 lbs (10,200 kg)	170 hp (127 kW) @ 1,800 rpm
TXL 300-2	38,140 lbs (17,300 kg)	3.9 yd ³ (2.98 m ³)	36,419 lbs (162 kN)	31,967 lbs (14,500 kg)	26,676 lbs (12,100 kg)	227 hp (169 kW) @ 1,700 rpm
TXL 400-2	49,604 lbs (22,500 kg)	5.1 yd ³ (3.9 m ³)	49,458 lbs (220 kN)	41,667 lbs (18,900 kg)	36,376 lbs (16,500 kg)	310 hp (231 kW) @ 1,700 rpm
TXL 500-2	67,681 lbs (30,700 kg)	6.3 yd ³ (4.8 m ³)	61,373 lbs (273 kN)	50,706 lbs (23,000 kg)	40,092 lbs (20,000 kg)	360 hp (268 kW) @ 1,600 rpm



COMPACT AND MEDIUM WHEEL LOADERS						
	Operating weight	Std bucket capacity	Breakout force	Tipping load straight	Tipping load fully articulated	Gross engine power
TL60	8,598 lbs (3,900 kg)	0.65 - 1.3 yd ³ (0.50 - 1.0 m ³)	8,325 lbs (37,031 N)	6,063 lbs (2,750 kg)	5,456 lbs (2,475 kg)	50 hp (37 kW)
TL65	9,040 lbs (4,100 kg)	0.65 - 1.3 yd ³ (0.50 - 1.0 m ³)	8,325 lbs (37,031 N)	6,560 lbs (2,975 kg)	5,788 lbs (2,625 kg)	50 hp (37 kW)
TL80	11,240 lbs (5,100 kg)	1.0 - 1.6 yd ³ (0.8 - 1.2 m ³)	10,128 lbs (45,000 N)	8,577 lbs (3,890 kg)	7,563 lbs (3,430 kg)	60 hp (44 kW)
TL100	13,230 lbs (6,001 kg)	1.1 - 2.0 yd ³ (0.85 - 1.55 m ³)	12,375 lbs (55,036 N)	10,540 lbs (4,780 kg)	9,305 lbs (4,221 kg)	73.5 hp (54.8 kW)
TL120	15,656 lbs (7,101 kg)	1.1 - 2.4 yd ³ (0.85 - 1.8 m ³)	13,275 lbs (59,050 N)	11,642 lbs (5,280 kg)	10,275 lbs (4,660 kg)	84 hp (62.6 kW)
TL160	20,283 lbs (9,200 kg)	2.0 - 4.0 yd ³ (1.5 - 3.0 m ³)	19,334 lbs (86,000 N)	15,986 lbs (7,251 kg)	14,002 lbs (6,351 kg)	102 hp (74.5 kW)
SKL873SP	30,870 lbs (14,000 kg)	2.6 - 4.6 yd ³ (1.7 - 3.5 m ³)	24,425 lbs (113,000 N)	19,613 lbs (8,895 kg)	17,397 lbs (7,890 kg)	144 hp (130 kW)
TL260	32,855 lbs (14,903 kg)	3.3 - 6.0 yd ³ (2.5 - 4.5 m ³)	26,995 lbs (119,900 N)	24,255 lbs (11,000 kg)	21,168 lbs (9,600 kg)	175 hp (130 kW)



TRACTOR LOADER BACKHOES							
	Maximum dig depth std. stick	Maximum reach	Loader bucket capacity	Loader lift capacity	Loader bucket breakout force	Engine net power	Standard operating weight
TX760B	14 ft 8 in (4.5 m)	23 ft 5 in (7.14 m)	1.32 yd ³ (1.0 m ³)	7,604 lbf (3,449 kgf)	10,485 lbf (4,756 kgf)	86 hp (64.3 kW)	15,151 lbs (6,887 kg)
TX860B	14 ft 8 in (4.5 m)	23 ft 5 in (7.14 m)	1.32 yd ³ (1.0 m ³)	8,783 lbf (3,984 kgf)	12,291 lbf (5,575 kgf)	94 hp (70.3 kW)	15,964 lbs (7,241 kg)
TX870B	15 ft 11 in (4.9 m)	24 ft (7.32 m)	1.32 yd ³ (1.0 m ³)	8,783 lbf (3,984 kgf)	12,291 lbf (5,575 kgf)	94 hp (70.3 kW)	16,986 lbs (7,721 kg)*
TX970B (all wheel steer)	15 ft 11 in (4.9 m)	24 ft (7.32 m)	1.32 yd ³ (1.0 m ³)	8,783 lbf (3,984 kgf)	12,291 lbf (5,575 kgf)	94 hp (70.3 kW)	17,663 lbs (8,029 kg)

*Includes front counterweight



TANDEM ASPHALT ROLLERS						
	Drum width	Operating weight	Centrifugal force	Static linear load	Frequency	Amplitude
TV800-1	31.5 in (800 mm)	3,466 lbs (1,572 kg)	2,809 lbs (12.5 kN)	54.2 lbs/in (8.7 kg/cm)	2,760/3,120 VPM (46/52 Hz)	0.020 in (0.5 mm)
TV900-1	35.4 in (900 mm)	3,572 lbs (1,620 kg)	2,944 lbs (13.1 kN)	56.4 lbs/in (10.1 kg/cm)	2,760/3,120 VPM (46/52 Hz)	0.021 in (0.5 mm)
TV900-H*	35.4 in (900 mm)	3,572 lbs (1,620 kg)	2,944 lbs (13.1 kN)	56.4 lbs/in (10.1 kg/cm)	2,760/3,120 VPM (46/52 Hz)	0.021 in (0.5 mm)
TV1000-1	39.4 in (1000 mm)	5,644 lbs (2,560 kg)	5,397 lbs (24.0 kN)	71.7 lbs/in (12.0 kg/cm)	3,120 VPM (51 Hz)	0.022 in (0.6 mm)
TV1200-1	47.2 in (1200 mm)	6,382 lbs (2,895 kg)	6,776 lbs (30.4 kN)	67.5 lbs/in (13.9 kg/cm)	3,120 VPM (51 Hz)	0.022 in (0.6 mm)
TV1300-1	51.2 in (1300 mm)	7,859 lbs (3,565 kg)	7,175 lbs (32.2 kN)	76.6 lbs/in (13.7 kg/cm)	3,120 VPM (51 Hz)	0.022 in (0.5 mm)
TV1400-1	55.2 in (1400 mm)	9,953 lbs (4,515 kg)	8,090/11,685 lbs (36/52 kN)	90 lbs/in (16.1 kg/cm)	2,580/3,120 VPM (43/51 Hz)	0.020/0.039 in (0.5/1.0 mm)

*Auxiliary hydraulic attachment



SITE DUMPERS							
	Heaped	Maximum payload	Engine HP (kW) @ RPM	Steering type	Transmission type	Water level	Struck level
Straight Tip 2-Wheel Drive							
PT200	1.8 yd ³ (1,384 L)	4,409 lbs (2,000 kg)	Kubota D905E 22 hp (16.4 kW) @ 3,000	rear wheel	3/1 Manual	1.1 yd ³ (860 L)	1.4 yd ³ (1,052 L)
Power Tip 4-Wheel Drive Articulating							
PT2000	2.3 yd ³ (1,720 L)	4,409 lbs (2,000 kg)	Kubota D1705M 33 hp (24.5 kW) @ 2,600	articulated	3/1 Manual	1.2 yd ³ (900 L)	1.7 yd ³ (1,320 L)
PT3000	2.6 yd ³ (1,850 L)	6,615 lbs (3,000 kg)	Kubota V2203-M 43.2 hp (32.4 kW) @ 2,600	articulated	3/1 Manual	1.25 yd ³ (960 L)	1.5 yd ³ (1,150 L)
PT4000H	3.22 yd ³ (2,640 L)	8,820 lbs (4,000 kg)	Kubota V2203 43.2 hp (32.4 kW) @ 2,400	articulated	2/2 Hydrostatic	1.9 yd ³ (1,420 L)	2.4 yd ³ (2,000 L)
PT6-AWS	4.8 yd ³ (3,650 L)	13,228 lbs (6,000 kg)	Perkins 1004C-44 80 hp (60.0 kW) @ 2,200	all wheel	4/4 Powershift	2.5 yd ³ (1,910 L)	3.7 yd ³ (2,800 L)
Power Swivel 4-Wheel Drive Articulating							
PS2000	2.3 yd ³ (1,720 L)	4,409 lbs (2,000 kg)	Kubota D1705M 33 hp (24.5 kW) @ 2,600	articulated	3/1 Manual	1.2 yd ³ (900 L)	1.7 yd ³ (1,320 L)
PS3000	2.6 yd ³ (1,850 L)	6,615 lbs (3,000 kg)	Kubota V2203-M 43.2 hp (32.4 kW) @ 2,600	articulated	3/1 Manual	1.25 yd ³ (960 L)	1.5 yd ³ (1,150 L)
PS4000H	3.22 yd ³ (2,640 L)	8,820 lbs (4,000 kg)	Kubota V2203 43.2 hp (32.4 kW) @ 2,400	articulated	2/2 Hydrostatic	1.9 yd ³ (1,420 L)	2.4 yd ³ (2,000 L)
PS6-AWS	4.34 yd ³ (3,320 L)	13,228 lbs (6,000 kg)	Perkins 1004C-44 82 hp (61.5 kW) @ 2,200	all wheel	4/4 Powershift	2.7 yd ³ (2,030 L)	3.5 yd ³ (2,800 L)


SCRAP MATERIAL HANDLERS

	Engine	Operating weight	Reach to stick tip	Max. lifting capacity	Grab size	Generator
MHL 320	112 hp (84 kW)	41,900 lbs (19,000 kg)	31' 7" (9.5 m)	18,740 lbs (8,500 kg)	0.8 yd ³ (0.6 m ³)	11 kW
MHL 331	129 hp (76 kW)	49,600 lbs (22,500 kg)	36' 1" (11 m)	27,500 lbs (12,500 kg)	0.8 yd ³ (0.6 m ³)	13 kW
MHL 340	153 hp (114 kW)	55,115 lbs (25,000 kg)	41' (12.5 m)	29,000 lbs (13,154 kg)	0.8 yd ³ (0.6 m ³)	13 kW
1704 MI	213 hp (157 kW)	58,200 - 67,800 lbs (25,400 - 26,200 kg)	43' 6" (13.3 m)	27,808 - 27,979 lbs (12,613 - 12,691 kg)	0.72 yd ³ (0.55 m ³)	10 kW
MHL 350	198 hp (148 kW)	70,548 - 78,264 lbs (32,080 - 35,500 kg)	52' 6" (16 m)	36,010 - 38,750 lbs (16,300 - 17,600 kg)	0.8 yd ³ (0.6-0.8 m ³)	20 kW
1804 MI	228 hp (170 kW)	77,200 - 90,500 lbs (41,000 - 43,100 kg)	54' 4" (16.5 m)	19,810 - 35,115 lbs (8,986 - 15,928 kg)	0.98 yd ³ (0.75 m ³)	20 kW
MHL 360	249 hp (186 kW)	97,000 - 101,413 lbs (44,000 - 46,000 kg)	54' - 59' (16.6 - 18 m)	44,092 - 52,911 lbs (20,000 - 24,000 kg)	1.0-1.3 yd ³ (0.8-1.0 m ³)	20/30 kW
5205 MI	256 hp (191 kW)	108,045 - 115,763 lbs (49,008 - 52,509 kg)	64' 1" - 71' 9" (19.5 - 21.9 m)	22,481 - 50,737 lbs (10,197 - 23,014 lbs)	1.31 yd ³ (1.0 m ³)	30 kW
MHL 380	337 hp (248 kW)	143,300 - 145,505 lbs (65,000 - 66,000 kg)	60' 7" - 68' 9" (18.5 - 21 m)	54,010 - 68,560 lbs (24,499 - 31,100 kg)	1.1-2.1 yd ³ (1.3-1.6 m ³)	20/30 kW
RHL 350	190 hp (142 kW)	87,082 - 88,185 lbs (39,500 - 40,000 kg)	44' 4" - 49' 2" (13.5 - 15 m)	33,950 lbs (15,400 kg)	0.8 yd ³ (0.6 m ³)	20 kW
1804 LCI	228 hp (170 kW)	77,200 - 90,500 lbs (41,000 - 43,100 kg)	54' 4" (16.5 m)	26,319 - 28,204 lbs (11,938 - 12,793 kg)	0.98 yd ³ (0.75 m ³)	20 kW


LOGGING MATERIAL HANDLERS

	Engine	Operating weight	Reach to stick tip	Max. lifting capacity	Grapple
MHL 331L	133 hp (99 kW)	49,600 lbs (22,498 kg)	40' (12.2 m)	34,500 lbs (15,649 kg)	0.8 cord pulpwood or 52" bypass
MHL 340L	153 hp (114 kW)	55,115 lbs (25,000 kg)	41' (12.3 m)	27,200 - 30,100 lbs (12,338 - 13,653 kg)	1.0 cord pulpwood or 60" bypass
MHL 460	221 hp (165 kW)	74,449 - 75,287 lbs (33,770 - 34,150 kg)	41' - 49' 2" (12.5 - 15 m)	32,630 - 41,910 lbs (19,010 - 14,800 kg)	1.25 yd ³ or 62" bypass
MHL 434	150 hp (112 kW)	48,722 - 50,926 lbs (22,100 - 23,100 kg)	31' - 35' 1" (9.5 - 10.7 m)	22,487 - 26,235 lbs (10,200 - 11,900 kg)	2 yd ³ or 0.8 cord pulpwood
MHL 464	221 hp (165 kW)	84,878 lbs (38,500 kg)	36' (11.0m)	40,100 lbs (18,189 kg)	3.8 yd ³ or 2.6 cord pulpwood



TELEHANDLERS						
	Operating weight	Maximum lift capacity	Max lift height	Max reach	Engine power	Max speed
GTH-5519	10,000 lbs (4,536 kg)	5,500 lbs (2,500 kg)	18 ft 10 in (5.74 m)	11 ft 3 in (3.43 m)	63 hp (47 kW)	15.0 mph (24 km/hr)
GTH-6622	13,000 lbs (5,897 kg)	6,600 lbs (3,000 kg)	22 ft 5 in (6.83 m)	12 ft 9 in (3.89 m)	81 hp (60 kW)	21.0 mph (33 km/hr)
GTH-636	21,000 lbs (9,525 kg)	6,000 lbs (2,722 kg)	36 ft (10.97 m)	21 ft (6.4 m)	99 hp (73.8 kW)	18.0 mph (29 km/hr)
GTH-644	21,500 lbs (9,752 kg)	6,000 lbs (2,722 kg)	44 ft (13.4 m)	27 ft (8.2 m)	99 hp (73.8 kW)	17.0 mph (27.4 km/hr)
GTH-842	21,500 lbs (9,752 kg)	8,000 lbs (3,629 kg)	42 ft (12.8 m)	25 ft (7.6 m)	99 hp (73.8 kW)	18.0 mph (29 km/hr)
GTH-844	22,500 lbs (10,206 kg)	8,000 lbs (3,629 kg)	44 ft (13.4 m)	27 ft (8.2 m)	99 hp (73.8 kW)	17.0 mph (27.4 km/hr)
GTH-1048	27,500 lbs (12,474 kg)	10,000 lbs (4,536 kg)	48 ft (14.6 m)	31 ft (9.45 m)	115 hp (85.8 kW)	18.0 mph (29 km/hr)
GTH-1056	29,500 lbs (13,381 kg)	10,000 lbs (4,536 kg)	56 ft (17.1 m)	40 ft (12.1 m)	125 hp (93.3 kW)	18.0 mph (29 km/hr)

TEREX TECH is a comprehensive resource designed to assist those servicing Terex Construction Americas Heavy and Compact Equipment in becoming better qualified and more competent.

With a combination of classroom and hands-on sessions, expert instructors use a wide array of effective training aids assuring TEREX TECH graduates will receive quality, in-depth hands-on training that will greatly increase return on investment.



Course schedule opportunities are updated and distributed on a regular basis and are also available for review on the Terex Construction Americas website www.terexca.com/training/ where on-line registration is available.



Terex Construction Americas' products are available and supported by an extensive network of independent distributors throughout North America.

TEREX PRODUCT SUPPORT - SOUTHAVEN, MS

TEL 662-393-1800
SALES 866-837-3923
FAX 662-393-1700
EMAIL sales@terexca.com
WEB terexca.com

TEREX PARTS - SOUTHAVEN, MS

- On-line parts ordering available 24/7
- Orders for available parts received by 8:00 pm CST ship same day

TEL 662-393-1800
PARTS & TECH SUPPORT
888-201-6008
FAX 662-393-1751
EMAIL sales@terexca.com
WEB terexparts.com