## **MTX-Series Rammers**





Once again, Multiquip raises the bar with new Cyclone filtration, on-board hourmeter and much more.

## **MTX-Series Rammers**

New for 2007, our MTX-Series resets the bar for tamping rammers.

Improved clutch design — features a new self-cleaning design that prevents build-up for material and provides a longer service life.

**Hourmeter** — New on-board hourmeter/tachometer.



New Cyclone Filter System

**Throttle** — Mikasa's original design that functions as a throttle, start/stop and fuel shut-off.

Air Cleaner — New Cyclone Filter System delivers triple the amount of clean air to lengthen component life with less maintenance than ever before.



Throttle Hourmeter

## **Specifications**

Model	MTX70	MTX80	MTX90
Operating Weight lb. (kg)	168 (76)	183 (83)	196 (89)
Overall length in. (mm)	29.9 (760)	29.9 (760)	29.9 (760)
Overall width in. (mm)	13.8 (350)	14.4 (365)	14.4 (365)
Operating height in. (mm)	39.3 (1000)	1000	1000
Shoe Size WxL in. (mm)	11.2 x 13.4 (285 x 340)	11.2 x 13.4 (285 x 340)	11.2 x 13.4 (285 x 340)
Jump Height in. (mm)	3.1 (80)	3.1 (80)	3.1 (80)
Impact Force lb. (kg)	2900 (1300)	3100 (1400)	3550 (1600)
Blows Per Minute	Up to 690*	Up to 678*	Up to 696*
Fuel Tank Capacity qt. (lit)	3.2 (3)	3.2 (3)	3.2 (3)
Engine Make/Model	Honda GX100UKRBF	Robin EX12-2D46530	Robin EX12-2D46530
Engine Power HP (kw)	3 (2.2)	3.5 (2.6)	3.5 (2.6)
Fuel	Gasoline	Gasoline	Gasoline
Engine Displacement in <sup>3</sup> (cc)	6 (98)	7.4 (121)	7.4 (121)
Engine RPM	4,100	3,600	3,700
Start Method	Recoil	Recoil	Recoil
Travel Speed ft./min (m/min)	39.3 (12)	39.3 (12)	36.1 (11)
Max. Area Capacity ft.²/hr (m²/hr)	3,165 (294)	3,165 (294)	2,002 (186)

<sup>\*</sup>Variable speed impact — up to maximum impact force.

Specifications are in accordance with LEMB Standard No. 1.

Your Multiquip dealer is:	



MULTIQUIP INC. POST OFFICE BOX 6254 **CARSON, CA 90749** 310-537-3700 • 800-421-1244 FAX: 310-537-3927 E-MAIL: mg@multiquip.com

© COPYRIGHT 2007, MULTIQUIP INC