





www.discount-equipment.com

atte

**MAXI-**

**POWER**<sup>™</sup>

| 15XR MOBILE GENERATOR                                |  |
|--|--|
| Model  | CAT C1.5T  |
| Control Detail                                       |  |
| Engine-Generator Control Interface                   | Deep Sea 4520  |
| Control Display Outputs (Hour meter, etc.)           | Hourmeter<br>Fuel Level<br>RPM<br>Genset Frequency<br>Genset Voltage |
| Engine Detail  |  |
| Engine Make  | Caterpillar  |
| Engine Model   | C1.5T  |
| Engine Induction                                     | Turbocharged   |
| Engine Displacement                                  | 1.5 L  |
| Number of Cylinders                                  | 3  |
| Type of After-Treatment                              | None   |
| Mechanical Output (Prime) at Rated Speed*            | 22.3 hp (16.6 kWm) @ 1,800 RPM                                       |
| Engine Speed @ MAX Load                              | 1,800  |
| Engine Speed @ No Load                               | 1,800  |
| Acceptable Fuel Types (Engine Only)                  | ULSD-US/Canada   |
| Fuel Consumption @ Full Load                         | 1.22 GPH   |
| Fuel Run Time @ Full Load                            | 82.0 hr  |
| Engine Oil Capacity                                  | 1.75 gal   |
| Oil Change Interval                                  | 500 hr   |
| Engine Cooling System Capacity                       | 1.61 gal   |
| Maximum ambient operating temperature at full output | 118 °F (48 °C)   |
| Electrical System Voltage                            | 12 VDC   |
| Battery Size   | Group 24   |
| Battery  | Lead Acid  |
| Alternator Detail                                    |  |
| Output Phase and Voltage                             | Dedicated 1-Phase 120/240 VAC  |
| Power Output Rating (Prime Power)                    | 15 kW (15 kVA)   |
| Armature Connection                                  | 4 Lead, Series Connected, Frame Grounded Neutral                     |
| Number of Poles                                      | 4 Pole   |
| Insulation   | NEMA MG1 Class "H"   |
| Excitation   | AVR  |
| Voltage Regulation %                                 | 0.01   |
| NVH - Noise, Vibration, Harshness                    |  |
| Sound Level @ 23 ft (NO LOAD)                        | 61.9 dBA   |
| Sound Level @ 23 ft (75% FULL LOAD)                  | 64.8 dBA   |
| Sound Level @ 23 ft (FULL LOAD)                      | 66.0 dBA   |
|  | · · · · · · · · · · · · · · · · · · ·                                |

Maxi-Power® 15XR

| Model  | CAT C1.5T  |
|--|--|
| Weights and Dimensions                       |  |
| Net Dry Weight                               | 2417 lb  |
| Operating Wet Weight NO fuel                 | 2444 lb  |
| Operating Wet Weight fuel FULL               | 3160 lb  |
| Gross Vehicle Weight Ratings - GVWR          | 5,000 lb   |
| Length - Transport Position                  | 126 in   |
| Width  | 77 in  |
| Track Width                                  | 67.5 in  |
| Height                                       | 73.3 in  |
| Truck Load Shipping Quantities - 48' flatbed | 7 units  |
| Truck Load Shipping Quantities - 53' flatbed | 7 units  |
| Container Load Shipping Quantities - 40'     | 6 units  |
| Trailer Detail                               |  |
| Standard Trailer Coupler                     | Adjustable height combination 2" ball coupler, 3" lunette ring for pintle hitch  |
| Optional Trailer Couplers                    | Adjustable height combination 2"" Bulldog coupler with 3"" lunette ring for pintle hitch<br>Adjustable height combination 2 5/16"" Bulldog coupler with 3"" lunette ring for pintle hitch            |
| Electrical Connector                         | 7 Pin Connector  |
| Leveling Jack Load Capacity                  | Tongue Jack-2,000 lbs  |
| Tire Size                                    | ST225/75R15 Load Range 'D'   |
| Ахіе Туре                                    | Tubular  |
| Axle Quantity                                | 1 Axle   |
| Trailer Brake Type                           | Electric with Breakaway Brakes (STD)   |
| Body Detail                                  |  |
| Fluid Containment                            | Standard-Intergral with chassis  |
| Fuel Tank Size                               | 100 gal  |
| Fuel Tank Material & Construction            | Rotationally Molded Polyethylene   |
| Fuel fill port size                          | 2.72 in diameter   |
| Enclosure (Material & Gauge)                 | Steel - 12 ga doors and stringer, 14 ga quarter panels and front panels, 7 ga rear panel   |
| Door Hinge Material                          | Steel hinge and hinge pin  |
| Fork Pockets / Lifting Eyes                  | 2 lateral fork pockets<br>Lifting eye at top of stringer   |
| Compliance & Certifications                  |  |
| Fluid Containment                            | 110%   |
| USA DOT Compliant                            | Conforms to the Code of Federal Regulations 49 CFR Transportation Subtitle B. Chapter V. National Highway Traffic Safety Administration, Department of Transportation - Parts 565, 566, 567 and 571. |
| CSA Listed                                   | Certificate Of Compliance No. 1088975 available with certain options   |
| Transport Canada Compliant                   | Conforms to Canadian Motor Vehicle Safety Standards  |
| EPA Tier Level - Engine                      | Tier 4 Final   |
| Limited Warranty Coverage                    |  |
| Engine                                       | 2 years or 2,000 hrs whichever comes first   |
| Alternator                                   | "18 months from Invoice to Allmand,or<br>12 months or 1,000 hrs whichever comes first from date of end user installation"  |



## www.discount-equipment.com

BRIGGS&STRATTON, LLC Copyright ©2020. All rights reserved.

## **TO PURCHASE THIS PRODUCT PLEASE CONTACT US**



Equipment Financing and Extended Warranties Available



## Discount-Equipment.com is your online resource for commercial and industrial quality parts and equipment sales. 561-964-4949

visit us on line @ www.discount-equipment.com

Select an option below to find your Equipment

Search by Manufacturer

Search by Product Type

## **Request a Quote**

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment ,Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep,Small Line, Wanco, Yanmar