

MAXI-POWER™ 65

MOBILE GENERATOR

Maximize the power of your job site with the Maxi-Power™ Mobile Generator. This generator comes equipped with a heavy-duty, oversized alternator equipped for starting any motor size needed. This generator will last and deliver the power you need to get the job done.



www.discount-equipment.com

Electrical Power Output	
Frequency - Hz	60
Standby Power - kVA (kW)	3Φ: 69 (55) 1Φ: 40 (40)
Prime Power - kVA (kW)	3Φ: 63 (50) 1Φ: 37 (37)
Voltage Single Phase (V)	120 / 127 / 139 / 240 / 254 / 277
Voltage Three Phase (V)	208 / 220 / 240 / 416 / 440 / 480
Main Circuit Breaker Size (A)	175
Amperage Single Phase 120V (A)	152 x 2
Amperage Single Phase 240V (A)	152
Amperage Three Phase 208V (A)	167
Amperage Three Phase 240V (A)	152
Amperage Three Phase 480V (A)	76
Control Panel	NEMA 5-20R (20A GFI Duplex Receptacle) - qty 2 CS6369 (50A 3 Prong Locking Receptacle) - qty 3 Output Terminals (L1, L2, L3, N, & G)
Control Detail	
Engine-Generator Control Interface	Not Applicable
Control Display Outputs (Hour meter, etc.)	Deep Sea 7310MK II

Engine Detail	
Engine Make	Isuzu
Engine Model	4JJ1X
Engine Induction	Turbocharged with Charge Air Cooler
Engine Displacement (L)	3.0 L
Number of Cylinders	4
Type of After-Treatment	Diesel Oxidation Catalyst (DOC) Selective Catalytic Reduction (SCR)
Mechanical Output (Prime) at Rated Speed (HP (kW))	86.5 Hp (64.5 kWm) @ 1,800 RPM
Engine Speed @ MAX Load (RPM)	1,800 RPM
Engine Speed @ No Load (RPM)	
Engine Control Panel	Deep Sea 7310MK II
Acceptable Fuel Types (Engine Only)	Ultra Low Sulfur Diesel (ULSD)
Fuel Consumption @ Full Load (gal/hr)	3.9 gal/hr
Fuel Run Time @ Full Load	28 hrs
DEF Tank Size (gal)	7.4 gal
DEF Consumption @ Full Load (gal/hr)	No Data
DEF Run Time @ Full Load	No Data
Engine Oil Capacity With Filter (gal)	4.0 gal
Oil Change Interval (hours)	500 hrs
Engine Cooling System Capacity (gal)	3.0 gal
Engine Fuel Filter Change Interval (hours)	500 hrs
Electrical System Voltage	12 Volt DC
Battery Size	95D31R
Battery (CCA)	620

Alternator Detail	
Armature Connection	Star with Neutral / Zig Zag
Number of Poles	4-pole
Insulation	Class F
Excitation	Brushless with AVR
Voltage Regulation %	0.5
3 Phase Power Factor (Single Phase)	80% (100%)
Harmonic Distortion (%)	No Load: 1.10-0.80 Full Load (PF = 0.8): 0.80-0.90 Full Load (PF = 1.0): 1.00-1.00
NVH - Noise, Vibration, Harshness	
Sound Level @ 23 ft (NO LOAD) - dBA	64 dBA
Sound Level @ 23 ft (FULL LOAD) - dBA	64 dBA
Weights and Dimensions - With Trailer	
Net Dry Weight (lbs)	4,389 lbs
Operating Wet Weight NO fuel (lbs)	4,445 lbs
Operating Wet Weight fuel FULL (lbs)	5,170 lbs
Gross Vehicle Weight Ratings - GVWR (lbs)	6,000 lbs
Length (in)	157.0 in
Width (in)	67.6 in
Track Width (in)	59.4 in
Height (in)	82 in
Truck Load Shipping Quantities - 48' flatbed	4
Truck Load Shipping Quantities - 53' flatbed	4
Weights and Dimensions - Skid Mount	
Net Dry Weight (lbs)	3,307 lbs
Operating Wet Weight NO Fuel or DEF (lbs)	3,363 lbs
Operating Wet Weight FULL Fuel & DEF (lbs)	4,189 lbs
Length (in)	98 in
Width (in)	40 in
Height (in)	67 in
Truck Load Shipping Quantities - 48' flatbed	11
Truck Load Shipping Quantities - 53' flatbed	11
Trailer Detail	
Standard Trailer Coupler	Adjustable Height 3" Lunette Ring
Optional Trailer Couplers	Adjustable Height: 2" Ball Coupler 2-5/16" Ball Coupler 2" Bulldog 2-5/16" Bulldog
Electrical Connector	4-Way Flat Connetor
Tongue jack load capacity	5,000 Lbs
Tire Size	ST205/75R15 Load Range 'C'
Axle Type	Single Torsion Axle
Axle Quantity	1 Axle
Trailer Brake Type	Hydraulic Surge With Breakaway Brakes

Body Detail	
Fluid Containment	Standard - Steel containment tray with rear drain
Fuel Tank Size (gal)	111 gal
Fuel Tank Material & Construction	Welded Steel
Fuel fill port size	2.65 in dia
Enclosure (Material & Gauge)	Steel - 13 Ga covers and doors
Door Hinge Material	Steel hinge and hinge pins
Lifting Eyes	Lifting eye at top
Compliance & Certifications	
Fluid Containment (%)	112%
USA DOT Compliant	Yes
CSA Listed	Not CSA Listed
Transport Canada Compliant	Yes
EPA Tier Level - Engine	Tier 4 Final
Warranty Coverage	
Body, Trailer, Air End & Controls	1 year parts and labor 2 years parts only
Engine	1 year parts and labor 2 years parts only
Available Options	
Arctic Package	✓
Cam Locks	✓
Skid mount	✓
Battery Disconnect	
Battery charger	✓
2" Ball Coupler	✓
2" Bulldog Coupler	✓
2 5/16" Ball Coupler	✓
2 5/16" Bulldog Coupler	✓
Telematics	



www.discount-equipment.com



ALLMAND BROS., INC.
A subsidiary of Briggs & Stratton Corporation
Copyright ©2020. All rights reserved.

TO PURCHASE THIS PRODUCT PLEASE CONTACT US



**Equipment Financing and
Extended Warranties Available**



**Discount-Equipment.com is your online resource for
commercial and industrial quality parts and equipment sales.**

561-964-4949

visit us on line @ www.discount-equipment.com

Select an option below to find your Equipment

Search by Manufacturer

Search by Product Type

Request a Quote

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment, Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep, Small Line, Wanco, Yanmar