

Standard Configurations

- Overload Sensor and Alarm
- Tilt/Slope Sensors and Alarm
- Self-closing/Self-catching Gate
- Higher Platform Rails (Foldable)
- Solid Non-marking Tires
- Swing-out Component Trays
- Descent Protection and Alarm
- Flashing Beacons (Both Sides)
- Pothole Protectors
- Universal Control Box
- Quick Disconnect for Control Box
- Foot Pedal Extended Platform
- Proportional Control
- Lanyard Points
- Manual Brake Release
- Emergency Descent
- Horn and Hour Meter
- Full Height Drive
- Intelligent Diagnostic System
- AC Platform Power (GFCI)
- Charging Protection System
- Wind Rating Stickers
- LED Battery Charging Indicator

ANSI A92.20 Slab Scissor Lifts

**Discount
Equipment**

www.Discount-Equipment.com

LGMG North America Inc.

ELECTRIC MOTOR DRIVE


AS2632E Scissor Lift (Indoor)

- Optimized to deliver longer-lasting performance for jobs that are inside
- Battery-powered with zero emissions means it is environmentally friendly and great for indoor use
- A superior electronic control system that allows for better braking abilities on long downhill
- Improved steering mechanism reduces tire wear during turning



Product Specifications AS2632E

Platform Capacity	510 lbs
Platform Occupants (Indoor/Outdoor)	2/0
Platform Height	26'
Machine Length	7' 11"
Machine Width	2' 8"
Machine Height (Rails Up)	7' 7"
Machine Height (Rails Down)	6' 5"
Platform Extension	3'
Deck Extension Capacity	265 lbs
Drive Speed (Lowered)	2.2 Mph
Drive Speed (Elevated)	0.5 Mph
Lift Time	31 Secs
Lower Time	40 Secs
Gradeability	25%
Max Slope/Tilt	1.5°/3°
Amp Hours	(4) 6V x 225Ah
Maximum Ground Bearing Pressure	123 PSI
Tire Size	15" x 5"
Ground Clearance - Center	3.75"
Machine Weight	4,718 lbs



ANSI A92.20 Compliant



LGMG North America Inc.



www.Discount-Equipment.com