

CARRY 150

DIESEL POWERED 180° SWIVEL TRACKED DUMPER

TOGETHER **WE BUILD**



**CAPACITY
28 CU FT**

CARRY 150 - 180° SWIVELLING BUCKET | Model # 5240304101 | 20HP Kubota Diesel

POWER, SPEED AND 180° SWIVEL DUMP

The Carry 150 has an independent dual circuit hydrostatic transmission with a variable displacement axial piston pump and a dual displacement axial piston hydraulic engine for each track. The standard Carry 150 model offers a 180° trilateral hydraulic lift and swivel bucket to handle a multitude of loading/unloading options.



28 cubic foot bucket capacity

180° trilateral load/unloading with hydraulic lift and swivel

Spacious ground clearance and rubber tracks provide greater mobility and higher speeds

Foldable ROPS for operator protection

Adjustable operator seat in central rear position with access from both sides

Abundantly oversized Kubota 20 HP engine

Battery housing under engine bonnet

Technical specifications



	Kubota D902, 20 hp
Engine* - Diesel	Kubota D902, 20 hp
Machine weight	1,896 lbs
Operating load	3,307 lbs
Payload capacity	28 cu ft
Speed	5 mph
Max allowed slope when empty	32° - 62%
Max allowed slope when loaded**	32° - 62%***
Ground clearance	9-½ in
Start	Electric
Length	107 in
Height	93-¾ in
Width	42-½ in

INTUITIVE CONTROLS

The control panel is easy to access and operate. Drive and operate the Carry 150 from the protected operator's seat located behind the swivelling bucket.



HI-TIP SELF-LOADING SHOVEL AND BUCKET KIT OPTION

Model # 5250315101

The Carry 150 offers a "Hi-Tip" Tipping Bucket & Self-loading Shovel kit. The variable height scissor lifting bucket can lift and dump materials up to 75".

(*) Warning: Cancer and Reproductive Harm - <https://www.p65warnings.ca.gov>
(**) Guide with operator on the ground, where applicable (***) Variable based on the configuration
File: 5240304101 - Carry 150 Diesel Dumper - Spec Sheet