

## APPLICATIONS

For pumping gypsum or cement based self-levelling screeds, non-shrink grouts and repair mortars.

60 Hz  
**STEP-UP 120a**  
 220V/60Hz 3 phase  
 Model # 1106094



✓ 10 HP, 220V high torque 3 phase motor

✓ High flow rate (9.5 CY/h)





✓ High capacity hopper fitted with vibrating grate

✓ High flow 60.12 rotor and statot

## CONTROL PANEL



- 1 On/Off switch
- 2 Current supply light
- 3 Emergency stop button
- 4 Rotor/stator forward/reverse
- 5 Vibrating grate switch
- 6 Safety default light

Part number	Accessories
1107533	 33' rubber hose Ø 50 (2") with cam couplings
1107534	 66' rubber hose Ø 50 (2") with cam couplings
1107081	 Stator 60.12 for self-levelling floor screeds
1107083	 Rotor 60.12 for self-levelling floor screeds

## Standard Equipment

- ✓ Three-phase 220V/60Hz motor – 10 HP
- ✓ Electric control panel
- ✓ Built-in low voltage electric remote control with 120' of cable
- ✓ 66' power supply cord
- ✓ 60.12 rotor-stator
- ✓ Vibrating grid
- ✓ 100' of hose (66+33) Ø 50 mm (2")
- ✓ Accessory box

Supply	-	220V/60Hz, 3 phase
Motor power rate	HP	10
Max grain size	In.	3/8
Flow rate	CY/h	9.5
Max pumping distance	Ft.	200
Max pumping height	Ft.	100
Hopper capacity	CF	4.25
Dimensions length/width/height	In.	91/32/38
Weight	Lbs.	616
Sound pressure level	dB (A)	< 79

\* The pumping distance may vary depending on: the type of material used, pumping height, material consistency, type of pump installed.