

24000 lb Heavy Duty Trailer with Internal Fuel Tank

SKU 190008

- New
- 1 Year / 1,000 Hour Limited Warranty (Whichever comes first)
- Installation Additional cost to fully install generator set
- Weight Capacity (Pounds): 20000
- Trailer Options:

STANDARD FEATURES:

Tandem DEXTER type 12,000 lb. axles
Integral single walled fuel tank (up to 500 gal. capacity)
3" Adjustable pintle ring
10000 lb. drop leg jack - two
DOT wiring package - enclosed in ½" steel conduit
6 way round trailer plug
ST245/75R16 load range E trailer rated tires on OEM wheels
8-lug wheels
2 - 5/16" x 30 safety chains with 3/8" hooks
Electric brakes with safety break-away
Direct reading manual fuel gauge
Fuel fill and vent
Fuel pick-up and return ports
Mounting rails for your specified genset
Primed & painted semi-gloss black

STANDARD SPECIFICATIONS:

GVWR 24000 lbs.
Load capacity (less fuel) approximately 20000 lbs.
Deck size 96" x 288"
Deck height 36" (approx.)
Hitch height 28" (+/- 6")
Empty weight 4000 lbs. (approx.)

CONSTRUCTION FEATURES

Frame Rail Material - 4" x 12" x 3/16" rectangular tubing
Cross Members - 12" Junior I-beam
Top Deck - 1/8" Diamond Floor Plate
Mounting Rails for Genset - 3" standard channel

Tongue Material - 3" x 8" x 3/16" rectangular tubing
Fenders - Heavy Duty Steel Floor Plate Fenders
Stabilizer Jacks - Adjustable - 2 1/2" x 3/16" Square Tubing
Bottom Tank Sheet - 10 gauge smooth plate





Download More Information
[24000 LB TRAILER 288.pdf](#)
File Size: 225.908 kb

