

GOOD VIBRATIONS

Stone WolfPac™ 4100 Triples Vibration Versatility



The WolfPac 4100 Asphalt Roller with a working width of 40" and a static weight of 4,000 lbs., is ideal for professional finishes on driveways, parking lots, bicycle paths, and other confined areas where maneuverability and impact force counts.

Versatile for Maximum Impact

The WolfPac 4100 features a Stone-exclusive eccentric system, which directs the impact force where needed. The electro-hydraulic circuit, combined with a custom-designed manifold, allows the operator to initiate the vibration either in the front drum, the rear drum or both drums. The 3-position selection switch activates lighter or heavier compaction, or static mode - depending on the requirements of the job. Its versatility makes it the ideal roller for all phases of asphalt rolling - subbase, binder and finish coats.

Productive

The 24.8 hp liquid-cooled Kubota engine combined with the dual-drum drive and 4,000 lbs. of force per drum delivers maximum power and optimal torque. Centerpoint articulation, balanced weight distribution, power steering, a short wheelbase and high curb and minimum wall clearance make this roller incredibly effective in confined areas.

The WolfPac 4100 features an overall design that's properly balanced to prevent scuffing or gouging with infinitely variable forward and reverse hydrostatic drive, providing smooth acceleration and stopping.

The corrosion resistant, pressurized water system allows maximum water to the drums, to prevent asphalt from sticking. Spring loaded, urethane scrapers evenly



A 3-position switch directs the impact force to the front, rear or both drums, providing compaction where needed. The 4-in-1 control puts vibe on/off, direction, speed and braking at your fingertips.

spread water over drum surfaces, reducing asphalt buildup.

Reliable

An isolated, dedicated hydraulic circuit for steering and eccentrics optimizes both operations simultaneously. A Parker® seal lock hydraulic connector system provides leak-free pressure, torque and vibration.

Large capacity hydraulic tank delivers cooler hydraulic oil, reduces heat and contamination for longer component life. Large, oversized fuel tank and 40 gallon reinforced polyethylene water tank with level indicators minimize refilling stops and provides quick visual fluid level checks.

Operator Friendly

The roomy operator compartment with an adjustable safety seat is ergonomically-designed to provide maximum space, comfort and visibility. The seat also houses the spring applied hydraulic released automatic parking brake system (SAHR) which activates when the operator leaves the seat.

The contoured styling of the poly hood maximizes operator's line



The corrosion-resistant pressurized water system directs a smooth even flow over the drums to prevent asphalt from sticking. It features a gravity backup to keep the roller operating.

of sight to the roller front, rear and sides. A 4-in-1 control lever, which includes forward, reverse and neutral along with a vibration button, puts total control at your fingertips.

Serviceable

The WP4100 is easy to service. A swing-away hood provides full access to the engine compartment. A conveniently located oil drain makes oil changes fast and easy. "Dirty" indicators alert when filters require changing. Sprinkler bars are easily removed for quick cleaning.

Get the right vibes for versatile, fast working, highly productive power and performance with the WolfPac™ 4100.



The hood swings away for maximum accessibility to the engine and all components.

WOLFPAC 4100	
Dimensions	
Dry Wt. (kg)	3465 lbs. (1575)
Operating Wt. (kg)	4000 lbs. (1818)
L x W x H (cm)	82" x 45" x 96" (208 x 114,3 x 243,8)
Drum Width (cm)	40" (101,6)
Drum Diameter (cm)	23" (58,5)
Wall Clearance (cm)	2.3" (5,8)
Curb Clearance (cm)	17.5" (44,5)
Wheelbase (cm)	55" (139,7)
Operating System	
Engine (kW)	24.8 hp Kubota Diesel (18,5)
Drive	Hydrostatic Double Drum
Steering	Hydrostatic Power Steering
Frame	Center-Point Articulating
Travel Speed (km/hr)	0-5.5 mph (8,9)
Fuel Capacity (liters)	8 gallons (30)
Water System	Pressurized, gravity backup
Water Tank Capacity (liters)	40 gallons (151)
Performance	
Vibrating Drum	Front, Rear, Dual
Centrifugal Force (kN)	4000 lbs. (18)
Frequency (Hz)	4000 vpm (67)
Oscillation	±15°
Gradeability	30%
Inside/Outside Turning Radius (m)	7.1' / 11.3' (2,2 / 3,4)
Max. Area Cap. (m²/hr)	96,800 ft²/hr (8993)
Static Linear Force (N/mm)	F 40.6 lb./in. (7,09) R 60.6 lb./in. (10,5)
Dynamic Linear Force (N/mm)	100 lb./in. (17,5) per drum
Options	Working Lights, Beacon, Foldable ROPS



STONE CONSTRUCTION EQUIPMENT, INC., 8662 Main St, Honeoye, NY 14471-0150
1-800-888-9926 • 1-585-229-5141 • (fax) 1-585-229-2363
www.stone-equip.com
e-mail: sceny@stone-equip.com

©2005 Stone Construction Equipment, Inc.