

KM International

Infrared Asphalt Recyclers • Sealcoat Systems • Asphalt Reclaimer Boxes

Crack Maintenance Equipment

The 50,000 BTU propane burner is thermostatically controlled optimizing fuel efficiency and temperature accuracy.

The self-contained insulated KM 55 allows for continuous accurate heating of material and does not require constant monitoring. Direct fire units typically consume twice as much propane as the KM 55.



A two (2) inch flow valve extends out for easy filling of application equipment.



The KM 55 is equipped with a utility torch for heating the valve, tools, pour pots, etc.

KM 55 Specifications

Dimensions:	24"W x 68"L x 32"H
Capacity:	55 gallon
Thermostat:	100-500° controller
Heating Element:	50,000 BTU propane heating Element
Pilot:	Electronic fuel ignitions with 100% safety shut down capability
Insulation:	High efficiency insulation and reflective metal for maximizing fuel economy
Construction:	All welded steel; 16 gauge skin, 14 gauge funnel, 20 gauge opening lid
Weight:	340 lbs.
Agitation:	360° hand agitation paddle

Specifications Subject to Change

Available from KM International is an affordable line of crack maintenance equipment. The KM 55 Melter, when mounted on a heavy duty utility trailer and teamed with the Crack Jet II and MA-10 applicator provide everything you need to prepare and fill cracks. Leaving room for storage & transport of material & tools.

*** check local codes for transporting melter while burner is on.**