



KM8000T



- Extend working seasons with KM repair equipment.
- The KM 8000T allows work when plants are closed
- No longer do you need to discard old asphalt.
- Cold patch works well if asphalt is not available.
- Just stockpile and recycle with the KM Asphalt Hotbox Reclaimer.

- Optional Features**
- Heated 30 gallon liquid tack tank, thermostatically controlled with 100% safety shut down
 - Liquid utility solvent tank
 - 60 or 100 pound cylinders
 - 1000 lbs. loading winch and davit
 - Hand torch
 - Type 2 fuel oil heating system
 - Hydraulic brakes
 - Self-contained hydraulic dump unit





KM 8000T Specifications

Dimensions:	174"L x 96"W x 78"H
Capacity (Asphalt):	8,000 lbs. of material
Heating Element:	60,000 BTU propane 105,000 BTU #2 fuel oil (option)
Fuel Supply:	Two (2) 30 lb. cylinders 25 gallon fuel tank with #2 fuel (option)
Pilot:	Electronic fuel ignition with 100% safety shut down capability
Filling Door:	Two insulated lids with cantilevered shock assist door that takes 15 pounds of pressure to open
Shovel Port:	Two insulated sliding track design, 10"W x 16"H. Slanted walls funnel contents toward the shovel ports
Construction:	All welded steel, triple welded construction 16 gauge skin, 12 gauge asphalt compartment
Capacity (Trailer):	14,000 lbs. GVWR
Axles:	Dual 7,000 lb. axle leaf spring, electric brakes on all wheels and emergency breakaway feature



Optional Features

- Heated 30 gallon liquid tack tank, thermostatically controlled with 100% safety shut down
- Liquid utility solvent tank
- 60 pound cylinders
- 1000 lb. loading winch and davit
- Hand torch
- Type 2 fuel oil heating system
- Hydraulic brakes
- Self-contained hydraulic dump unit
- Low temperature thermostat (for cold patching materials)
- Electric back-up heat (for overnight, indoor heat maintenance)

