

TORO® DINGO® TXL 2000

COMPACT UTILITY LOADERS



OUTSTANDING REACH & LIFT HEIGHT

Thanks to the telescoping loader arm technology, operators are able to backfill behind a retaining wall, dump material into the center of a full-size dump truck or dumpster and offload both rows of a trailer from one side with ease.

HINGE PIN HEIGHT OF JUST OVER



auxiliary, and traction torque for

greater operation efficiency -

info center.

a selectable option through the

 Selectable traction speed allows operators to customize machine speed based on operator preference

attachments at their desired speed.

and project application.Proportional auxiliary control allows the operator to run

360°

OUTSTANDING VISIBILITY

With a stand-on operator platform instead of a cab, the TXL 2000 provides 360° visibility. No need for a back-up camera — just turn and look.



EASE OF USE

TXL 2000 control interface is easy to use and master — no special equipment licensing required.



OUTSTANDING ACCESS

Easy for operators of different sizes to jump on and off the machine instead of getting into and out of a cab.



OUTSTANDING MANEUVERABILITY

Maneuver in and out of small spaces where other machines just can't go.



www.discount-equipment.com

		DINGO TXL 2000 WITH TELESCOPING ARMS (MODEL 22530)	DINGO TXL 2000 WITHOUT TELESCOPING ARMS (MODEL 22531)	
ENGINE	Engine	49.6 hp (37 kW) Kubota D180	3 Diesel	
	Air Filter	Two-stage, heavy-duty, remote		
Cooling System		Liquid Cooled		
	Fuel Tank	18.3 gallons (69.3 liter	s)	
	Oil Capacity	7.4 quarts (7 liters)		
HYDRAULIC SYSTEM	Hydraulic Pressure	Auxiliary: 3,000 PSI Traction: 4,350 PSI	10	
	Hydraulic Flow	Auxiliary: 21.4 gpm Traction: 21.5 gpm (81.4 lpm) each pump		
	Reservior Capacity	15.25 gallons (57.7 lite	rs)	
TRACKS Standard		Sprocket-drive, 6 road wheels	Sprocket-drive, 6 road wheels per side	
	Traction	Dual hydrostatic pum	p	
DIMENSIONS	Track Dimensions	162.2 " x 11.8" (413 cm x 30 cm	n)	
	Wheelbase	53.7" (136.4 cm)		
	Ground Clearance	6.3" (16 cm)		
Overall Dimensions (WxLxH) With Bucket		54" x 136.9" x 67.8" (137 x 348 x 172 cm)		
Overall Dimensions (WxLxH) Without Bucket		54" x 98.8" x 67.8 (137 x 251 x 172 c		
Maximum Operating Height		Telescoping 67.8" (172cm)	Non-Telescoping 63.9" (162 cm)	
Hinge Pin Height		123.4" (313 cm)	98.6" (250 cm)	
Dump Height		88.9" (226 cm)	64.1" (163 cm)	
Dump Angle		46.3 degrees		
Reach - Fully Raised		45.2" (114.8 cm)	26.1" (66.3 cm)	
Ground Speed		5.4 mph (8.6 km/h)		
Weight		6,655 lbs (3,019 kg)	6,235 lbs (2,828 kg)	
Tip Capacity		5,715 lbs (2,592 kg) retr, 2,620 lbs (1,188 kg) ext.	5,715 lbs (2,592 kg)	
Rated Operating Capacity (35% of Tip Capacity)*		2,000 lbs (907 kg) retr, 920 lbs (417 kg) ext.	2,000 lbs (907 kg)	
Ground Pressure		5.3 PSI		

*Per ISO 14397-1





TO PURCHASE THIS PRODUCT PLEASE CONTACT US



Equipment Financing and Extended Warranties Available



Discount-Equipment.com is your online resource for commercial and industrial quality parts and equipment sales. 561-964-4949
visit us on line @ www.discount-equipment.com

Select an option below to find your Equipment

Search by Manufacturer

Search by Product Type

Request a Quote

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment, Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep, Small Line, Wanco, Yanmar