



# Chicago Pneumatic



**CPG 20 - 25**

**People. Passion. Performance.**



## Over 100 years of experience

Since 1901 the Chicago Pneumatic name has represented high-performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools, air compressors and generators are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, generators, accessories and workshop equipment, please visit [www.cp.com](http://www.cp.com).

Since 1901 the Chicago Pneumatic name has represented high performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools, air compressors and generators are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, accessories and workshop equipment, please visit [www.cp.com](http://www.cp.com).

## Standard Features

- Reliable Kubota engine and Leroy Somer alternator
- 29 hour run time at 75% load with integrated 30 gallon in-frame fuel tank
- Environmentally friendly 110% fluid containment frame
- Solid-state digital controller with easy-to-read analog gauges
- Very quiet 65 dB(A)
- Electronic governor for increased voltage stability (0.25%)
- 3 position voltage selector switch (CPG 25 only)
- Remote start connections

## Options

- Skid-mounted
- Battery charger
- Coolant heater
- Spare tire
- Tool box
- Rear stabilizer jacks
- External fuel connections

## Technical Data

Model	CPG 20	CPG 25
Rated Standby Power	19.2 kW / 19.2 kVA	22 kW / 22 kVA
Rated Prime Power	17.3 Kw / 17.3 kVA	20 Kw / 25 kVA
Voltage Selections - 1Ø	120 / 240	-
Voltage Selections - 3Ø	-	208/240/480
Amperage Capacity @ 120 volts 1Ø	2 x 66	-
Amperage Capacity @ 208 volts 3Ø	-	69
Amperage Capacity @ 240 volts 1Ø	70	-
Amperage Capacity @ 240 volts 3Ø	-	60
Amperage Capacity @ 480 volts 3Ø	-	30
Sound Pressure Level @ 23 feet @ 75% load	65 dB(A)	
Fuel Tank Capacity	30 gal.	
Fuel Consumption At 75% Load	1.04 gal/hr	
Fuel Autonomy At 75% Load	29 hr	

Engine	Kubota
Model number	V2403
Rated Speed	1800 rpm
Emission Compliance	EPA IT4
Rated Output	29.6 HP @ 1800 rpm
Coolant	Water / Glycol
Cylinders	4
Displacement	2.4 L
Engine Control	Electronic

Alternator	Leroy Somer
Model	LSA40M5
Degree Of Protection / Insulation Class	IP23 / H

Convenience Receptacles	
20 amp - 125 volt GFCI duplex	2
50 amp - 125 / 250 volt twist lock	2

Dimensions (LxWxH) & Weight	
Dimensions, mounted on skid	82.5 x 37.4 x 51 in
Weight, wet, mounted on Skid	1,868 lbs
Dimensions, mounted on trailer	110 x 59 x 57 in
Weight, wet, mounted on Trailer	2,121 lbs

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.