



TORO® DINGO® TX 1000

COMPACT UTILITY LOADERS

Toro invented the category, now meet **THE ALL-NEW TORO DINGO TX 1000** that's redefining the compact utility loader. Designed with Toro exclusive vertical lift loader arms, its 1,000-lb rated operating capacity delivers category crushing performance. The TX 1000 also offers outstanding hinge pin height of 81" (206 cm) to clear the side of 30-yard dumpsters and one-ton trucks for maximum jobsite productivity. Patent-pending, traction controls are easy to operate and an innovative foot-operated auxiliary control results in greater efficiency. The TX 1000 is a lightweight, maneuverable machine that packs unmatched strength and reach in a compact package for the ultimate working advantage.

FEATURES

VERTICAL LIFT LOADER ARMS

- Rated operating capacity over 1,000-lbs allows the TX 1000 to lift more than any compact utility loader on the market
- Increased load capacity and greater reach at full height deliver even stronger performance
- 81" (206 cm) hinge pin height allows attachments to easily clear the side of 30-yard dumpsters or one-ton trucks
- Vertical path of lift arms allows for more efficient vertical applications, such as augering or concrete breaking

HIGH DRIVE TRACK SYSTEM

- Endless Kevlar® reinforced tracks ensure maximum strength and durability
- Ideal for the demands of any jobsite to outperform on any surface, even sand or loose gravel
- Maximum maneuverability on uneven surfaces

EASY OPERATION

- Our patent-pending traction control design is intuitive, easy to operate, and effortless
- Auxiliary foot control maintains hydraulic flow to the attachment, freeing the operators hands to focus on ground speed and attachment positioning

- Dedicated operating platform with thigh and hip padding for increased operator comfort
- Suspended platform has clear line of sight to the attachment plate, machine, and jobsite for maximum visibility

POWERFUL AND EFFICIENT

- Kubota® D1305 diesel, Tier-4 compliant engine features high torque and increased displacement for the strongest Dingo yet
- Fast ground speeds at 4.7 mph (7.6 km/h) in forward and reverse
- Dual fuel tanks offer all day productivity
- Easy engine access and belt-free design minimize maintenance



DINGO TX 1000



UNMATCHED STRENGTH
Over 1,000-lb rated operating capacity to lift and transport heavy loads.


SPECIFICATIONS

	DINGO TX 1000 (MODEL 22327)	DINGO TX 1000 WIDE TRACK (MODEL 22328)	
ENGINE	Engine	Kubota® D1305 Diesel	
	Air Filter	Two-stage, heavy-duty, remote	
	Cooling System	Liquid Cooled	
	Fuel Tank	11.5 gallons (44 liters)	
	Oil Capacity	6.0 quarts (5.7 liters)	
HYDRAULIC SYSTEM	Hydraulic Pressure	3,000 PSI	
	Hydraulic Flow	Traction: 13.3 gpm (each pump) Auxiliary: 15.2 gpm	
	Reservoir Capacity	15.2 gallons (57.5 liters)	
TRACKS	Standard	Sprocket-drive, 6 road wheels per side	
	Traction	Dual hydrostatic pump	
DIMENSIONS	Track Width	127.6" x 5.9" (324 cm x 15 cm)	127.6" x 9.5" (324 cm x 24 cm)
	Wheelbase	41" (10 cm)	
	Ground Clearance	6.0" (15 cm)	
	Overall Dimensions (WxLxH) With Bucket	33.7" x 100.7" x 53.2" (86 x 256 x 135 cm)	41" x 100.7" x 53.2" (104 x 256 x 135 cm)
	Overall Dimensions (WxLxH) Without Bucket	33.7" x 81.7" x 53.2" (86 x 208 x 135 cm)	41" x 81.7" x 53.2" (104 x 208 x 135 cm)
	Maximum Operating Height	105" (267 cm)	
	Hinge Pin Height	81" (206 cm)	
	Dump Height	61" (155 cm)	
	Dump Angle	40-degrees	
	Reach - Fully Raised	24.5" (62 cm)	
	Ground Speed	4.7 mph (7.6 km/h)	
	Weight	2610 lbs (1184 kg)	2790 lbs (1266 kg)
	Tip Capacity	2,857 lbs (1,296 kg)	3,071 lbs (1,393 kg)
	Rated Operating Capacity (35% of Tip Capacity)*	1,000 lbs (454 kg)	1,075 lbs (488 kg)
	Ground Pressure	5.5 PSI	3.6 PSI

*SAE J818 Rating of 35%



MAXIMUM HEIGHT & REACH
81" hinge pin height allows operator to dump into 30-yard dumpster or side of one-ton truck.



TORO EXCLUSIVE CONTROLS
Effortless traction controls are easy to use for all-day productivity.

©2014 The Toro Company Part No. 490-9120

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties. toro.com/dingo

