

Trime X-SMART (EL1250H) Specifications

Mast, Dimensions & Weight		
Mast Height	26'	
Wind Rating	50 mph	
Fully Retractable Stabilizers	Y	
Axle	Torsion	
Drawbar	Tubular Steel	
Unit Dimensions - Stowed	63" x 56" x 95"	
Operating Dimensions	98" x 100" x 315"	
Dry Weight	2107	
Operating Weight	2429	
Engine		
Make	Kubota*	Kohler*
Model	Z482-E4B	KDW702
Emission Regulation	Tier 4	
Туре	Vertical 4 Cycle Liquid	
	Cooling Diesel	
Cylinder	2	
Displacement / L (cu. In.)	0.479 (29.23)	
Combustion System	IDI	
Intake System	Naturally Aspirated	
Maximum Speed	1800 rpm	
Sound Level @ 23'	65 dBA	
Alternator		
Make	Linz	
Output	4.2 kVA	
Hz	60	
Fuel		
Туре	Diesel	
Fuel Capacity	46 gal.	
Run Time	288 Hrs	

*Specs subject to change. Ask about engine.

Applications








Anti-Glare Light Heads

Anti-glare light heads are available as an option in place of the standard 320W light head. There is a 10% less square footage difference with the antiglare heads, but more economical then other options out there.



Receiver Hitch

The receiver hitch gives user the ability to tow two towers together safely, one hooked to the back of the other. It bolts into the existing frame and axle.





www.discount-equipment.com