Model ST-312 • 3GPM • 2000PSI





hydraulic shoring pressure pump, the ST-312; it's a SHORE-Thing! Designed for use with bio-degradable anti-freeze the ST-312 offers a 20 gallon tank reservoir, a pressure adjusting valve up to 2000 PSI with bypass relief, and NO flat polyurethane tires. Constructed in a vertical ergonomic design the ST-312 has increased mobility, with reduced operator stress and user fatigue. A heavy gauge welded steel eye-hook allows for quick and easy jobsite relocation. Developed under the guidance of a local rental yard and two major construction companies, the ST-312 carries a 1 year FULL product warranty from manufacturer's defect.

- Heavy duty welded steel eye-hook for job site relocation
- Stainless-steel liquid filled gauge for accurate readings
- Available in gas or pneumatic driven
- Enclosed in a rugged roll cage for pump protection

SPECIFICATIONS

• INLET: 4" fill, with twist lock cap

• OUTLET: 50 foot high pressure outlet hose

Pressure regulating valve to 2000 PSI

• PUMP: Triplex Ceramic Plunger pump, with inner oil bath

OUTPUT FLOW: 3 GPMOUTPUT PRESSURE: 2000 PSI

• ENGINE: 5.5 HP 163 CC, Honda engine with oil alert

SHIPPING DIMENSIONS: 26 x 28 x 48
SHIPPING WEIGHT: 200 pounds
UNIT WEIGHT: 175 pounds



Shoring Pressure Pumps



ST 312

Gas powered hydraulic shoring pressure pump, it's a SHORE-Thing!

Designed for use with bio-degradable anti-freeze the ST-312 offers a 20 gallon tank reservoir, a pressure adjusting valve up to 2000 PSI with bypass relief, and NO flat polyurethane tires.

Manual Test Pumps

Manually operated test pumps, designed for testing small diameter lines in areas such as: landscaping, plumbing, and residential. A unique dual checkvalve system eliminates water bleed-back during test, greatly reducing operators labor and fatigue.

The series offers three pressure ranges of 500, 1000, or 1500 PSI; also available with an optional pressure regulator assembly.



