

185
cfm
@ 100 psi



www.discount-equipment.com



PERFORMANCE //

- 1 - Key Start & Digital Monitor
- 2 - Quick Access Air Connections
- 3 - Emergency Shut-off Button
- 4 - E2 Airflow Technology
- 5 - QuietTech™ Sound Attenuation
- 6 - Direct Coupled Engine to Air

MAINTENANCE //

- 7 - Large Panel Doors
- 8 - Curbside Service Drains
- 9 - Air Filter Access Door
- 10 - 23.2 Gallon Fuel Tank
- 11 - Heavy-Duty 12V Battery
- 12 - Fuel & Pre-Filters


CONSTRUCTION //

- 13 - Stainless Steel Hardware
- 14 - Lockable Access Doors
- 15 - Integral Lifting Bail
- 16 - Powder-coated Steel Enclosure
- 17 - Automotive Door Seals
- 18 - Skid Utility Mount



Yanmar®
4TNV88C
Tier 4 / CARB
Diesel Engine

Model PDS185LS shown
with side panel removed.



1 | Keyed Start and Digital Monitor
with fuel-saving Auto Idle Mode



2 | Air Connections
3/4" Male Ball Valve x 2



8 | Exterior Service Drains
Quick drain valves for Fuel, Oil Cooler,
Radiator and Engine Oil fluids



9 | Air Filter Access Door
Easy access for fast filter replacement

BEST-IN-CLASS POWER TRANSFER // FUEL EFFICIENCY // dBA RATING
THE INDUSTRY'S HIGHEST-QUALITY MOBILE AIR COMPRESSORS

AIR COMPRESSOR MODEL PDS185LS-5E1



AIR COMPRESSOR SPECIFICATIONS		ENGINE MAKE & MODEL (Continued)		WEIGHTS & DIMENSIONS	
COMPRESSOR TYPE		EPA TIER 4F CARB EMISSION CERTIFIED		LENGTH x WIDTH x HEIGHT	
PRESSURE 185 CFM @ 100 PSI		EMISSIONS TIER		DRY WEIGHT	
ACTUAL FREE AIR DELIVERY				OPERATING WEIGHT	
WORKING PRESSURE				LENGTH	
WORKING PRESSURE (MAXIMUM)				WIDTH	
WORKING PRESSURE (MINIMUM)				HEIGHT	
COMPRESSOR LUBRICATING OIL CAP.		EMISSIONS TYPE		COMPLIANCE & CERTIFICATIONS	
COMPRESSOR LUBRICATING SYSTEM		FUEL TANK CAPACITY		FLUID CONTAINMENT	
DRIVING SYSTEM		FUEL FILTER QUANTITY/TYPE		USA DOT COMPLIANT	
RECEIVER TANK CAPACITY		FUEL PUMP		CSA LISTED	
AIR SERVICE VALVES		DIESEL EXHAUST FLUID (DEF) CAPACITY		TRANSPORT CANADA COMPLIANT	
SEPERATION FILTERS		DEF CONSUMPTION		DIESEL ENGINE EPA TIER LEVEL	
OIL COOLER TYPE		ENGINE OIL CAPACITY			
COMPRESSOR OIL FILTER		COOLANT CAPACITY			
SOUND dBA RATING		ELECTRICAL SYSTEM - VOLTAGE			
ENGINE MAKE & MODEL		BATTERY RATING			
		BATTERY GROUP			
		AMBIENT TEMPERATURE (MIN./MAX.)			
		OPERATING ALTITUDE (MAXIMUM)			
		RUNTIME (FULL LOAD / 70% LOAD)			
		CONTAINMENT			
		FUEL CONSUMPTION			
		FULL LOAD			
		70% LOAD			
		NO LOAD			

All specifications are subject to change without prior notice. Visit anacorp.com for the most current information.

OPTIONAL ACCESSORIES



Double Hose Reel Kit



Single Hose Reel Kit



Battery Charger



Engine Block Heater



Battery Blanket



ANA, Inc.
Executive Office
1770 Raid Road

www.discount-equipment.com



ANA

We make your world easier.

© 2023 Alliance North America, Inc. All rights reserved.

Airman® is a registered trademark of Hokuetsu Industries Co. Ltd. All other trademarks are property of their respective owners.
Form AMAC185LSREV0523