ARR 1575-2

TRENCH ROLLER

EU STAGE V / U.S. EPA TIER 4 FINAL

APPLICATIONS

- · Pipeline construction
- Electric and cable installation
- Commercial, residential, and industrial development
- Structure backfill work
- · Confined work spaces
- Subbase of roads



PRODUCTIVITY

Powerful compaction

Reach compaction goals in the shortest possible time.

Exceptional manoeuvrability

Brings responsiveness and precision to the jobsite.

ERGONOMICS

Infrared remote control

The safest solution; the operator must have direct visibility for the machine to run.

Advanced protection

systems enhance jobsite safety and prevent injuries.

SERVICEABILITY

Minimized downtime Heavy duty components

and robust construction.

Reduced maintenance

Reduced maintenance Easy-to-reach maintenance points.

SUSTAINABILITY

ECOdrop

Improved efficiency, reduced use of fluids.

Advanced technologies

Machine usage controlled to bring efficiency, productivity – and enable precise documentation.

OPTIONAL EQUIPMENT

- Additional documentation printed
- AmmannCare Gold
- AmmannCare Silver
- Battery charger external
- Certificate of origin
- Color scheme customer
- Compaction Measuring
 System ACE
- Drums 600mm (23,6 in) incl. Extensions 860mm (33.9 in)

- Drums 860mm (33.9 in)
- Hydraulic oil biodegradable
- Maintenance kit 1000h
- Maintenance kit 500h
- Maintenance kit 200h
- Maintenance kit 50h
- Remote control batteryTelematics ServiceLink
- Light
- Telematics Trackunit
- Toolset

STANDARD EQUIPMENT

- Ammann color design and decals
- Articulated frame with Oscillation
- Automatic intelligent LED beacon
- CE conformity
- Central lifting point
- ECOdrop

- Infra-red remote control
- Maintenance-free articulation joint
- On-board diagnostics
- PD Drums with steel scrapers 600mm (23,6 in)
- Standard hydraulic oil




www.discount-equipment.com



ARR 1575-2

StV / T4f



WEIGHT & OPERATING CHARACTERISTICS

600 mm (23.6 in) 860 mm (33.9 in
OPERATING WEIGHT CECE 1480 kg (3,263 lb) 1595 kg (3,516 lb
OPERATING WEIGHT MAX. 1605 kg (3,538 lb) 1605 kg (3,538 lb)
MAX. WORKING SPEED 1.7 km/h (1.1 MPH) 1.7 km/h (1.1 MPH)
MAX. TRANSPORT SPEED 3.3 km/h (2.1 MPH) 3.3 km/h (2.1 MPH)
GRADEABILITY WITHOUT VIBRATION 35% 35%
GRADEABILITY WITH VIBRATION 30% 30%

ENGINE

MANUFACTURER	Kubota
ENGINE TYPE	D1105
ENGINE SPEED	2400 rpm
POWER OUTPUT SAE J1995	15,6 kW / 21HP
EMISSION STAGE	EU Stage V / U.S. EPA Tier 4 Final

COMPACTION FORCES

FREQUENCY	40 Hz (2,400 vpm)
CENTRIFUGAL FORCE I	72 kN (16,186 lbf)
CENTRIFUGAL FORCE II	34 kN (7,644 lbf)
AMPLITUDE I	1,2 mm (0.047 in)
AMPLITUDE II	0,6 mm (0.024 in)

MISCELL ANEOUS

BRAKES OPERATING	Hydrostatic
BRAKES PARKING	Hydromechanical
BRAKES EMERGENCY	Hydromechanical
FUEL TANK CAPACITY	25 l (6.6 gal)
HYDRAULIC TANK CAPACITY	27 l (7.1 gal)
STEERING ANGLE	±25°
OSCILLATION ANGLE	±4°
BATTERY VOLTAGE	12V
BATTERY CAPACITY	50 Ah

MAXIMUM RECOMMENDED COMPACTED LIFT THICKNESS AT OPTIMAL WORKING CONDITIONS

ROCKFILL	-
SAND / GRAVEL	200 mm (8 in)
MIXED SOILS	150 mm (6 in)
SILT	100 mm (4 in)
CLAY	80 mm (3 in)
ASPHALT	-



www.discount-equipment.com



TO PURCHASE THIS PRODUCT PLEASE CONTACT US



Equipment Financing and Extended Warranties Available



Discount-Equipment.com is your online resource for commercial and industrial quality parts and equipment sales. 561-964-4949
visit us on line @ www.discount-equipment.com

Select an option below to find your Equipment

Search by Manufacturer

Search by Product Type

Request a Quote

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment, Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep, Small Line, Wanco, Yanmar