

ARX 10.1

LIGHT TANDEM VIBRATORY ROLLER

U.S. EPA PHASE III / EU STAGE V

APPLICATIONS

- Small and medium construction sites
- Road maintenance
- City street repairs
- Confined work spaces
- Pathways
- Playgrounds, golf courses



PRODUCTIVITY

Smart design that provides diverse benefits to enhance machine performance and overall productivity.

A single-stage vibratory system makes the machine an invaluable tool on the jobsite, delivering optimal **compaction performance**.

ERGONOMICS

The **operator platform** is designed for comfort, ensuring a pleasant experience no matter the duration of the shift.

The **operator station** offers 360° visibility to maximize safety on the jobsite.

SERVICEABILITY

Low downtime

Robust design that protects components

Reduced maintenance

Easy-to-reach maintenance points

SUSTAINABILITY

ECOdrop

Improved efficiency, reduced use of fluids

Advanced technologies

Machine usage controlled to bring efficiency, productivity – and enable precise documentation

OPTIONAL EQUIPMENT

- Additional Documentation Printed
- Additional Lights for Hard Canopy
- Additional Lights for ROPS
- Additional Mirror
- Back-up Alarm
- Back-up Alarm Adaptive
- CE Conformity
- Certificate of Origin
- Color Scheme Customer
- Frame Rigid ROPS
- Frame ROPS
- Hard Canopy ROPS mounted
- Hydraulic Oil Biodegradable
- Maintenance Kit 100h
- Maintenance Kit 200h
- Overseas Shipping Preparation
- Seat Activation Warning Switch
- Seat Belt 3"
- Telematics ServiceLink Light
- Toolset
- Warning Beacon for Hard Canopy
- Warning Beacon for ROPS LED
- Water Tank Lock
- Working Lights

STANDARD EQUIPMENT

- Two steel drums with in-line configuration
- Front and rear drum hydrostatic drive
- 1 amplitude vibration system (front drum)
- Mechanical drive lever (RH)
- Comfortable seat, dashboard with multi-functional display and emergency stop
- Pressurized interval water sprinkling system
- Central lifting hook
- Ammann color scheme



www.discount-equipment.com

AMMANN

ARX 10.1

Phase III / StV



WEIGHT & OPERATING CHARACTERISTICS

| | |
|------------------------------|------------------------|
| OPERATING WEIGHT CECE | 2866 lb (1300 kg) |
| OPERATING WEIGHT MAX. | 3082 lb (1398 kg) |
| STAT. LIN. LOAD AVG. | 7.2 lb/in (40.3 kg/cm) |
| TURNING RADIUS INSIDE | 97.2 in (2470 mm) |
| STEERING / OSCILLATING ANGLE | 33/5 ±° |

ENGINE

| | |
|-----------------------------------|---------------------------------|
| ENGINE TYPE | Honda GX630 |
| EMISSION CLASS | U.S. EPA Phase III / EU Stage V |
| POWER OUTPUT ISO 3046 | 21 HP (15.5 kW) |
| 1 WORKING SPEED | @ 3300 rpm |
| TRAVEL SPEED | 4.9 MPH (7.9 km/h) |
| GRADEABILITY WITH / WITHOUT VIBR. | 30 % / 30 % |

COMPACTION FORCES

| | |
|-------------------|--------------------|
| AMPLITUDE | 0.02 in (0.5 mm) |
| FREQUENCY | 4560 VPM (76 Hz) |
| CENTRIFUGAL FORCE | 3687 lbf (16.4 kN) |

MISCELLANEOUS

| | |
|--------------------|------------------|
| BATTERY / CAPACITY | 12/50 V/Ah |
| WATER TANK | 29.1 gal (110 l) |
| FUEL TANK | 7.1 gal (27 l) |

For additional product information and services please visit: www.ammann.com
Materials and specification data are subject to change without notice.
MSS-3081-02-EN | © Ammann Group



MAXIMUM RECOMMENDED COMPACTED LIFT THICKNESS AT OPTIMAL WORKING CONDITIONS

| | |
|---------------|---------------|
| ROCKFILL | — |
| SAND / GRAVEL | 6 in (150 mm) |
| MIXED SOILS | 4 in (100 mm) |
| SILT | — |
| CLAY | — |
| STABILISATION | 3 in (80 mm) |
| ASPHALT | 2 in (60 mm) |



AMMANN

www.discount-equipment.com

TO PURCHASE THIS PRODUCT PLEASE CONTACT US



**Equipment Financing and
Extended Warranties Available**



**Discount-Equipment.com is your online resource for
commercial and industrial quality parts and equipment sales.**

561-964-4949

visit us on line @ www.discount-equipment.com

Select an option below to find your Equipment

Search by Manufacturer

Search by Product Type

Request a Quote

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment, Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep, Small Line, Wanco, Yanmar