

## ARX 16-2

### LIGHT TANDEM VIBRATORY ROLLER

EU STAGE V / U.S. EPA TIER 4 FINAL

#### APPLICATIONS

- Small and medium construction sites
- Road maintenance
- City street repairs
- Confined work spaces
- Pathways
- Playgrounds, golf courses



#### PRODUCTIVITY

##### Smooth rolling

No sudden starts and stops during machine operation.

##### Compaction performance

Varied machine sizes ensure proper fits for the application and jobsite.

#### ERGONOMICS

The **operator platform** is designed for comfort, ensuring a pleasant experience no matter the duration of the shift.

The **operator station** offers 360° all-around machine visibility from the seat to maximize safety on the jobsite.

#### SERVICEABILITY

##### Low downtime

Robust design that protects components.

##### Reduced maintenance

Easy-to-reach maintenance points.

#### SUSTAINABILITY

##### ECOdrop

Improved efficiency, reduced use of fluids.

##### Advanced technologies

Machine usage controlled to bring efficiency, productivity – and enable precise documentation.

#### OPTIONAL EQUIPMENT


- Two non-split drums, in-line
- Additional documentation printed
- Additional lights for hard canopy
- Additional Lights for ROPS
- Additional Lights for ROPS with Beacon
- Additional mirror
- AmmannCare Gold
- AmmannCare Silver
- Back-up alarm
- Back-up alarm adaptive
- CE conformity
- Certificate of origin
- Color scheme customer
- Drive lever additional left
- Edge cutter 45° (front left)
- Frame ROPS
- Hard canopy ROPS mounted
- Hard driving
- Hydraulic oil biodegradable
- Infrared thermometer
- Maintenance kit 1000h
- Maintenance kit 500h
- Maintenance kit 200h
- Maintenance kit 50h
- Overseas shipping preparation
- Registration plate holder
- Road lights
- Road lights incl. turn signals
- Scrapers double drum tiltable
- Seat activation warning switch
- Seat belt 3"
- Seat options armrests
- Seat options seat heating
- Telematics ServiceLink Light
- Telematics ServiceLink Plus
- Toolset
- Warning beacon green LED
- Warning beacon LED for hard canopy
- Warning beacon LED for ROPS
- Warning beacon LED green for hard canopy
- Warning beacon permanently activated
- Warning beacon with holder
- Water tank lock

#### STANDARD EQUIPMENT

- 1 amplitude / 2 frequencies
- Ammann color design and decals
- Articulation joint with oscillation
- AVC - Automatic Vibration Control
- Operator station with one drive lever (RH)
- Front and rear drive and vibration
- Open platform with safety handles
- Front and rear side free drum attachment
- Electronic drive lever
- Pressure water sprinkling with interval switch, 2 stage filtration
- Horizontally adjustable driver's seat
- Multi-functional display for machine overview
- Non-tiltable scrapers
- Standard hydraulic oil
- Telematics ready
- On-board diagnostics
- Ammann Traction Control (ATC)
- Battery disconnection switch
- Central lifting point

# ARX 16-2

StV/T4f



## WEIGHT & OPERATING CHARACTERISTICS

OPERATING WEIGHT CECE	1 510 kg (3,329 lb)
OPERATING WEIGHT MAX.	1 655 kg (3,649 lb)
STATIC LINEAR LOAD AVG.	8,45 kg/cm (47.3 lb/in)
MAX. WORKING SPEED	8 km/h (5 MPH)
GRADEABILITY WITHOUT VIBRATION	35%
GRADEABILITY WITH VIBRATION	30%
TURNING RADIUS (INNER)	2 130 mm (83.9 in)
DRUM OFFSET	48 mm (1.9 in)

## ENGINE

MANUFACTURER	Kubota
ENGINE TYPE	D1105
ENGINE SPEED	2400 / 2600 rpm
POWER OUTPUT ISO 14396	15,6 kW / 21,2 HP
EMISSION STAGE	EU Stage V / U.S. EPA Tier 4 Final

## COMPACTION FORCES

AMPLITUDE I	0,5 mm (0.020 in)
AMPLITUDE II	0,5 mm (0.020 in)
FREQUENCY I	60 Hz (3,600 vpm)
FREQUENCY II	70 Hz (4,200 vpm)
CENTRIFUGAL FORCE I	20 kN (4,496 lbf)
CENTRIFUGAL FORCE II	23 kN (5,171 lbf)

## MISCELLANEOUS

BRAKES OPERATING	Hydrostatic
BRAKES PARKING	Multiple-disc spring brake
BRAKES EMERGENCY	Multiple-disc spring brake
FUEL TANK CAPACITY	24 l (6.3 gal)
WATER TANK CAPACITY	110 l (29.1 gal)
TYPE OF WATERING	Pressure
HYDRAULIC TANK CAPACITY	28,5 l (7.5 gal)
STEERING ANGLE	±30°
OSCILLATION ANGLE	±6°
BATTERY VOLTAGE	12V
BATTERY CAPACITY	77 Ah

## MAXIMUM RECOMMENDED COMPACTED LIFT THICKNESS AT OPTIMAL WORKING CONDITIONS

ROCKFILL	N/A
SAND / GRAVEL	200 mm (7.9 in)
MIXED SOILS	150 mm (5.9 in)
SILT	N/A
CLAY	N/A
STABILISATION	100 mm (3.9 in)
ASPHALT	80 mm (3.1 in)



www.discount-equipment.com



Materials and specification data are subject to change without notice.  
MSS-2798-02-EN | © Ammann Group

**TO PURCHASE THIS PRODUCT PLEASE CONTACT US**



**Equipment Financing and  
Extended Warranties Available**



**Discount-Equipment.com is your online resource for  
commercial and industrial quality parts and equipment sales.**

**561-964-4949**

**visit us on line @ [www.discount-equipment.com](http://www.discount-equipment.com)**

Select an option below to find your Equipment

**Search by Manufacturer**

**Search by Product Type**

**Request a Quote**

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment, Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep, Small Line, Wanco, Yanmar