

The APF 20/50 provides the most power in the new APF lineup. It features a working width of 500 mm (19.7 in) and centrifugal force of 20 kN. The plate's technologically advanced exciter unit is completely maintenance free. The exciter system also provides significant forward-moving power to enhance productivity in challenging materials and on steep grades. The APF 20/50 petrol version can be equipped with either a Honda, Vanquard or Rato engine. The APF 20/50 Hatz combines all the benefits of other Ammann plates with a diesel engine that makes fueling at the jobsite more convenient. The diesel engine provides engine power of 3.2 kW (4.3 HP) and also excels in higher altitudes.

#### SIMPLE OPERATION

- · Operator safety with low HAV levels on the handle
- Machine frame that enables secure grip
- Great maneuverability boosts accuracy and makes work simple

#### POWERFUL COMPACTOR

- · Generously sized, powerful exciter unit
- Leading compaction power, speed, climbing ability and machine life
- Compact dimensions allow use on sites with limited space

#### READY FOR RENTAL

- · Low cost upkeep for owners
- · Good match for many applications
- · Easy for new users to operate

#### **SERVICEABILITY**

- · Maintenance-free exciter system
- · Full engine protection frame
- · Toolless daily maintenance

#### VERSATILE OPTIONS


- Toolless mountable water tank and sprinkler system
- · Toolless mountable rubber mats to change onto paving stones
- Permanently mounted transport wheels ensure easy relocation of the machine on site


#### **APPLICATIONS**

- Compaction in confined areas
- Asphalt and paving applications
- Light to medium patchwork
- Pipeline and trench construction
- Landscaping and gardening
- Earthwork



# TECHNICAL SPECIFICATIONS APF 20/50 FORWARD MOVING VIBRATORY PLATES





#### **DIMENSIONS & WEIGHTS**

		Honda / Vanguard / Rato	Hatz
MACHINE WEIGHT		88 kg (194 lb)	106 kg (234 lb)
MACHINE WEIGHT (INCL. OPTIONAL SPRINKLER & WHEELS)		97 kg (214 lb)	115 kg (254 lb)
Α	MACHINE LENGTH	700 mm (27.6 in)	700 mm (27.6 in)
В	MACHINE LENGTH WITH HANDLE	1020 mm (40.2 in)	1020 mm (40.2 in)
С	BASE PLATE LENGTH	559 mm (22 in)	559 mm (22 in)
D	GROUND CONTACT LENGTH	352 mm (13.9 in)	352 mm (13.9 in)
Ε	MACHINE HEIGHT	667 mm (26.3 in)	674 mm (26.5 in)
F	WITH HANDLE (WORK)	976 mm (38.4 in)	976 mm (38.4 in)
G	WITH HANDLE (TRANSPORT)	736/*960 mm (29/*37.8 in)	736 mm (29 in)
Н	MACHINE WIDTH	500 mm (19.7 in)	500 mm (19.7 in)

### **COMPACTION FORCES**

MAX. VIBRATION FREQUENCY	90 Hz (5400 vpm)	90 Hz (5400 vpm)
MAX. CENTRIFUGAL FORCE	20 kN (4496 lbf)	20 kN (4496 lbf)
WORKING SURFACE	930 m²/h (10 010 ft²/h)	990 m²/h (10 656 ft²/h)
SPEC. SURFACE PRESSURE	11.4 N/cm² (16.5 psi)	11.4 N/cm² (16.5 psi)

<sup>\*</sup>Vanguard & Rato

#### **ENGINE**

	Fuel	Engine Output at RPM
HONDA GX 160	Petrol	3.4 kW (4.6 HP) @3250
VANGUARD 160	Petrol	3.5 kW (4.7 HP) @3250
RATO R180	Petrol	3.8 kW (5.1 HP) @3250
HATZ 1B20	Diesel	3.2 kW (4.3 HP) @3250

#### **MISCELLANEOUS**

	Honda / Vanguard / Rato	Hatz
HAND-ARM VIBRATION ON HANDLE	3.1 m/s <sup>2</sup>	<2.5 m/s <sup>2</sup>
MAX. GRADEABILITY	0-31 m/min (0-101.7 ft/min)	0-33 m/min (0-108.3 ft/min)
MAX. GRADEABILITY	30 %	30 %
MAX. INCLINE	20°	20°

#### **OPTIONS**

RUBBER MAT	x	x
TRANSPORT WHEELS	x	x
WATER SPRINKLER SYSTEM	12 l (3.2 gal)	12 l (3.2 gal)
HOUR METER	Y	Y

#### HIGHLIGHTS

- Low-vibration handle for operator safety and comfort
- Maintenance-free exciter system
- Self cleaning and wear resistant base plate
- Engine frame for protection on the jobsite and during transport
- Transport wheels, which can be dropped with a foot release, for increased mobility on the jobsite





## TO PURCHASE THIS PRODUCT PLEASE CONTACT US



**Equipment Financing and Extended Warranties Available** 



Discount-Equipment.com is your online resource for commercial and industrial quality parts and equipment sales. 561-964-4949
visit us on line @ www.discount-equipment.com

Select an option below to find your Equipment

Search by Manufacturer

Search by Product Type

Request a Quote

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment, Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep, Small Line, Wanco, Yanmar