**MOBILE GENERATORS** 





**SDG220** 

**PRIME POWER** 



1 | DSEGenset® Digital Control Panel Model 7310 MKII



2 | Single-Phase Receptacles 120V - 20A x 2 | 240V - 50A x 3 Optional Dual Row Cam-Loks™ Shown



3 | Large Electrical Output Lugs 3Φ Output - 480V & 240V or 208V



10 | External Fuel Tank Connections with 3-Way Selection Valve

www.discount-equipment.com



### PERFORMANCE //

- 1 DSE® Digital Control Panel
- 2 Curbside Electrical Panel
- 3 Large Electrical Lugs
- 4 Emergency Stop Button
- 5 Prime Power Alternator
- 6 QuieTech™ Sound Attenuation
- 7 Fast Change Voltage Link Board

### MAINTENANCE //

- 8 Lift-off Door Hinges
- 9 110% Fluid Containment
- 10 Ext. Fuel Tank Connections
- 11 Built-in Service Ladder
- 12 Service Extensions
- 13 Front DEF Access Door

### CONSTRUCTION //

- 14 Powder-coated Steel Enclosure
- 15 Stainless Steel Hardware
- 16 Lockable Access Doors
- 17 Automotive Door Seals
- 18 285 Gallon Fuel Tank
- 19 Heavy-Duty Steel Trailer



# SDG220S-8E1



GENERATOR SPECIFICATIONS	SDG220S-8E1
ALTERNATOR TYPE	STAMFORD®
STANDBY OUTPUT	
THREE-PHASE AT 240V 30-4 WIRE	242 kVA / 194 kW
SINGLE-PHASE AT 240V 10-3 WIRE	129.9 kW
PRIME OUTPUT	
THREE-PHASE AT 240V 30-4 WIRE	220 kVA / 176 kW
SINGLE-PHASE AT 240V 10-3 WIRE	117.9 kW
FREQUENCY	60 Hz
VOLTAGE (THREE-PHASE), LINK BOARD	208/220/240/416/440/480
VOLTAGE (SINGLE-PHASE), LINK BOARD	120/127/139/240/254/277
ARMATURE CONNECTION	Star with Neutral / Zig Zag
EXCITATION	Brushless with AVR
NUMBER OF POLES	4
POWER FACTOR (THREE-PHASE)	0.8
POWER FACTOR (SINGLE-PHASE)	
INSULATION	Class F
VOLTAGE REGULATION	±0.5%
FREQUENCY REGULATION, STEADY STATE	±0.25% of Overall Mean Value
AMPERAGE	
SINGLE-PHASE (120V)	491 A x 2
SINGLE-PHASE (240V)	491 A
THREE-PHASE (208V)	608 A
THREE-PHASE (240V)	529 A
THREE-PHASE (480V)	264 A
ENGINE MAKE & MODEL	JOHN DEERE® 6068
ENGINE CONTROL PANEL	DSE® 7310 MK <b>II</b>
EPA TIER 4 / CARB Emission certified	Tier 4 Final, Model Year 2023 EPA & CARB Certification
TYPE OF AFTERTREATMENT	DEF, DOC, SCR, ASC
ENGINE TYPE	Electronic Direct Injection 4-Cycle Liquid Cooled Diesel
ASPIRATION	Turbocharged + Turbo After Cooler

	101111 000000 1010
ENGINE MAKE & MODEL (Continued)	JOHN DEERE® 6068
SAE GROSS HP / BHP@1800 RPM	323 BHP / 240.8 kW
HORSEPOWER RATING (@1800 RPM)	295 HP / 220 kW
NUMBER OF CYLINDERS	6
DISPLACEMENT	415 cu in
ENGINE SPEED	1800 RPM
GOVERNOR TYPE	Electronic
FUEL TYPE	Ultra-low sulfer diesel
DEF CAPACITY	11.7 gal
DEF CONSUMPTION (MAXIMUM)	5.7 gal Per Tank of Diesel
DEF RUNTIME @ FULL LOAD	46 hrs
FUEL TANK CAPACITY	285 gal
FUEL CONSUMPTION	
FULL LOAD	12.1 gal/hr
75% LOAD	9.5 gal/hr
50% LOAD	6.8 gal/hr
RUNTIME @ FULL LOAD	23.5 hrs
FUEL PUMP (w/SERVICEABLE STRAINER)	Self-priming Electric Fuel Pump
	Pre-filter/Sedimenter x 1
FUEL FILTER TYPE / QUANTITY	Fuel Filter x 1
LUBRICATING OIL CAPACITY	8.7 gal
BATTERY	
SYSTEM VOLTAGE	12V
BATTERY CHARGER ALTERNATOR	90 A
QUANTITY	12V x 1
COLD CRANKING AMPS	925 CCA
AMP HOURS	150 Ah
COOLING SYSTEM	
	Linuid/Air Fin and
COOLING SYSTEM TYPE	Liquid/Air Fin and Tube Radiator 50/50 Mix
COOLANT CAPACITY	▼ 7.1 gal
WATER PUMP TYPE	Impeller
FAN TYPE	Blower Fan, Viscous Clutch
NOISE LEVEL @ 23 FEET (NO/FULL LOAD)	63 dBA / 69 dBA

ENCLOSURE	
	Positively Charged Ion (E-coat) Electrodeposition Coating, Baking
PAINT TYPE	Finish Coating for Weatherproof, and Anti-corrosion and Salt Pollution
ENCLOSURE METAL / CONSTRUCTION	Steel
GAUGE STEEL	16 Gauge
DOOR HINGES	Stainless Steel
SERVICE ACCESS POINTS HARDWARE	Stainless Steel
SPILL CONTAINMENT	110%
WEIGHTS & DIMENSIONS	
LENGTH x WIDTH x HEIGHT	137.8" x 51.2" x 87.4"
DRY WEIGHT	7,452 lbs
OPERATING WEIGHT	9,656 lbs
TRAILER WEIGHT	1,365 lbs
OPERATING WEIGHT w/TRAILER (GVWR)	11,021 lbs
TRAILER WEIGHTS & DIMENSIONS	
LENGTH	219"
WIDTH	83.75"
HEIGHT W/GENERATOR INSTALLED	103.4"
WEIGHT	1,365 lbs
WHEEL SIZE-TIRE RATING	ST225/75R15 Load Limit E, 2830 lbs @ 80 psi
NUMBER OF AXLES / RATING	2 Axles / 6,000 lbs each
BRAKING TYPE	Surge or Electric
LIGHTING TYPE	LED
CERTIFICATIONS USA/DOT COMPLIANT	FMVSS
ADJUSTABLE HITCH HEIGHT	Yes
COMPLIANCE & CERTIFICATIONS	
FLUID CONTAINMENT	110%
USA DOT COMPLIANT	Yes
CSA LISTED	Yes
TRANSPORT CANADA COMPLIANT	Yes
DIESEL ENGINE EPA TIER LEVEL	Tier 4 Final

All specifications are subject to change without prior notice. Visit anacorp.com for the most current information.

## SM/NRTLOAD"

LOAD BANK SYSTEM

- U.S. PATENT PENDING -



**Parallelling Control Panel** 



**Battery Charger** 

### **ACCESSORIES & OPTIONS**

- SmartLoad™ System
- Paralleling Feature
- Battery Charger
  Dual Row Cam-Loks™ (See Front)
  Lockable Battery Disconnect
  Fuel Filter Heater
  Engine Coolant Heater
  Engine Block Heater
  Battery Blanket
  600V
- CSA Certification5-Yr./10,000-Hr. Ext. Warranty









www.discount-equipment.com





### TO PURCHASE THIS PRODUCT PLEASE CONTACT US



**Equipment Financing and Extended Warranties Available** 



Discount-Equipment.com is your online resource for commercial and industrial quality parts and equipment sales. 561-964-4949
visit us on line @ www.discount-equipment.com

Select an option below to find your Equipment

Search by Manufacturer

Search by Product Type

Request a Quote

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment, Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep, Small Line, Wanco, Yanmar