AIRMAN

MOBILE GENERATORS





SDG150

150 kVA

PRIME POWER



1 | DSEGenset® Digital Control Panel Model 7310 MKII



2 | Single-Phase Receptacles 120V - 20A x 2 | 240V - 50A x 3 Optional Dual Row Cam-Loks™ Shown



7 | Lockable Voltage Selector Switch 3Φ 277/480V & 139/240V-120/208V 1Φ 120/240V



10 | External Fuel Tank Connections with 3-Way Selection Valve

www.discount-equipment.com



PERFORMANCE //

- 1 DSE® Digital Control Panel
- 2 Curbside Electrical Panel
- **3** Large Electrical Lugs
- 4 Emergency Stop Button
- 5 Delta Demand Excitation™
- 6 QuieTech™ Sound Attenuation
- 7 Lockable Voltage Selector

MAINTENANCE //

- 8 Lift-off Door Hinges
- 9 110% Fluid Containment
- 10 Ext. Fuel Tank Connections
- 11 Built-in Service Ladder
- 12 Service Extensions
- 13 Front DEF Access Door

CONSTRUCTION //

- 14 Powder-coated Steel Enclosure
- 15 Stainless Steel Hardware
- 16 Lockable Access Doors
- 17 Automotive Door Seals
- 18 204 Gallon Fuel Tank
- 19 Heavy-Duty Steel Trailer



GENERATOR MODEL SDG150S-8E1



GENERATOR SPECIFICATIONS	SDG150S-8E1
ALTERNATOR TYPE	TAIYO WYE Winding
STANDBY OUTPUT	
THREE-PHASE AT 240V 3CD-4 WIRE	165 kVA / 132 kW
SINGLE-PHASE AT 240V 1CD-3 WIRE	95.7 kVA / 95.7 kW
PRIME OUTPUT	
THREE-PHASE AT 240V 3CD-4 WIRE	150 kVA / 120 kW
SINGLE-PHASE AT 240V 1CD-3 WIRE	87 kVA / 87 kW
FREQUENCY	60 Hz
VOLTAGE (THREE-PHASE), SWITCHABLE	208/220/240/416/440/480
VOLTAGE (SINGLE-PHASE), SWITCHABLE	120/127/139/240/254/277
ARMATURE CONNECTION	Star with Neutral / Zig Zag
EXCITATION	Brushless with AVR
NUMBER OF POLES	4
POWER FACTOR (THREE-PHASE)	0.8
POWER FACTOR (SINGLE-PHASE)	1.0
INSULATION	Class F
VOLTAGE REGULATION	±0.5%
FREQUENCY REGULATION, STEADY STATE	±0.25% of Overall Mean Value
AMPERAGE	
SINGLE-PHASE (120V) - ZIG ZAG	363A x 2
SINGLE-PHASE (240V) - ZIG ZAG	363A
THREE-PHASE (208V)	394A
THREE-PHASE (240V)	361A
THREE-PHASE (480V)	180A
ENGINE MAKE & MODEL	JOHN DEERE® 6068
ENGINE CONTROL PANEL	DSE® 7310 MK II
EPA TIER 4 / CARB Emission certified	Tier 4 Final, Model Year 2023 EPA & CARB Certification
TYPE OF AFTERTREATMENT	DEF, DOC, SCR, ASC
ENGINE TYPE	Electronic Direct Injection 4-Cycle Liquid Cooled Diesel
ASPIRATION	Turbocharged + Turbo After Cooler

ENGINE MAKE & MODEL (Continued)	JOHN DEERE® 6068
SAE GROSS HP / BHP@1800 RPM	257 BHP / 192 kW
HORSEPOWER RATING (@1800 RPM)	235 HP / 175 kW
NUMBER OF CYLINDERS	6
DISPLACEMENT	415 cu in
ENGINE SPEED	1800 RPM
GOVERNOR TYPE	Electronic
FUEL TYPE	Ultra-low sulfer diesel
DEF CAPACITY	11.7 gal
DEF CONSUMPTION (MAXIMUM)	4.1 gal Per Tank of Diesel
DEF RUNTIME @ FULL LOAD	67 hrs
FUEL TANK CAPACITY	204 gal
FUEL CONSUMPTION	
FULL LOAD	8.5 gal/hr
75% LOAD	6.9 gal/hr
50% LOAD	5.1 gal/hr
RUNTIME @ FULL LOAD	24 hrs
FUEL PUMP (w/SERVICEABLE STRAINER)	Self-priming Electric Fuel Pump
	Pre-filter/Sedimenter x 1
FUEL FILTER TYPE / QUANTITY	Fuel Filter x 1
LUBRICATING OIL CAPACITY	8.7 gal
BATTERY	
SYSTEM VOLTAGE	12V
BATTERY CHARGER ALTERNATOR	90 A
QUANTITY	1
COLD CRANKING AMPS	925 CCA
AMP HOURS	150 Ah
COOLING SYSTEM	
	Liquid/Air Fin and
COOLING SYSTEM TYPE	Tube Radiator 50/50 Mix
COOLANT CAPACITY	7.1 gal
WATER PUMP TYPE	Impeller
FAN TYPE	Blower Fan, Viscous Clutch
NOISE LEVEL @ 23 FEET (NO/FULL LOAD)	61 dBA / 66 dBA

ENCLOSURE	
	Positively Charged Ion (E-coat)
	Electrodeposition Coating, Baking Finish Coating for Weatherproof, and
PAINT TYPE	Anti-corrosion and Salt Pollution
ENCLOSURE METAL / CONSTRUCTION	Steel
GAUGE STEEL	16 Gauge
DOOR HINGES	Stainless Steel
SERVICE ACCESS POINTS HARDWARE	Stainless Steel
SPILL CONTAINMENT	110%
WEIGHTS & DIMENSIONS	
LENGTH x WIDTH x HEIGHT	129.9" x 51.2" x 84.6"
DRY WEIGHT	6,878 lbs
OPERATING WEIGHT	8,488 lbs
TRAILER WEIGHT	1,350 lbs
OPERATING WEIGHT w/TRAILER (GVWR)	9,838 lbs
TRAILER WEIGHTS & DIMENSIONS	
LENGTH	211"
WIDTH	83.75"
HEIGHT W/GENERATOR INSTALLED	100.6"
WEIGHT	1,350 lbs
	ST225/75R15
WHEEL SIZE-TIRE RATING	Load Limit E, 3520 lbs @ 80 psi
NUMBER OF AXLES / RATING	2 Axles / 6,000 lbs each
BRAKING TYPE	Surge or Electric
LIGHTING TYPE	LED
CERTIFICATIONS USA/DOT COMPLIANT	FMVSS
ADJUSTABLE HITCH HEIGHT	Yes
COMPLIANCE & CERTIFICATIONS	
FLUID CONTAINMENT	110%
USA DOT COMPLIANT	Yes
CSA LISTED	Yes
TRANSPORT CANADA COMPLIANT	Yes
DIESEL ENGINE EPA TIER LEVEL	Tier 4 Final

All specifications are subject to change without prior notice. Visit anacorp.com for the most current information.

SM/NRTLOAD"

LOAD BANK SYSTEM

- U.S. PATENT PENDING -



SmartLoad™ System



Parallelling Control Panel

ACCESSORIES & OPTIONS

- SmartLoad™ System
- Paralleling Feature
 Dual Row Cam-Loks™ (See Front)
 4-Position Selector Switch
 Lockable Battery Disconnect
 Fuel Filter Heater
 Engine Coolant Heater
 Engine Block Heater
 Battery Charger
 Battery Blanket
 600V
- CSA Certification5-Yr./10,000-Hr. Ext. Warranty









www.discount-equipment.com



TO PURCHASE THIS PRODUCT PLEASE CONTACT US



Equipment Financing and Extended Warranties Available



Discount-Equipment.com is your online resource for commercial and industrial quality parts and equipment sales. 561-964-4949
visit us on line @ www.discount-equipment.com

Select an option below to find your Equipment

Search by Manufacturer

Search by Product Type

Request a Quote

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment, Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep, Small Line, Wanco, Yanmar