

PDSF375DP

DUAL PRESSURE

375 cfm @ 100 psi 330 @ 150 psi



1 | Digital Touch Screen Control with Start Button & Pressure Selector Switch



3 | Air Connections 3/4" Ball Valve x 2 | 2" Ball Valve x 1



12 | Exterior Service Drains Quick drain valves for the Radiator, Oil Cooler and Engine Oil fluids



13 | Front-mounted SCR System Convenient access for easy servicing

www.discount-equipment.com



PERFORMANCE //

- 1 Digital Touch Screen Control
- 2 Emergency Shut-off Button
- 3 Quick Access Air Connections
- 4 Direct Coupled Engine to Air
- 5 QuieTech™ Sound Attenuation
- 6 E2 Airflow Technology

MAINTENANCE //

- 7 Large Gullwing Doors
- 8 Curbside Filter Servicing
- 9 Compressor Oil Access Door
- 10 After Cooler Access Door
- 11 Curbside Fuel Drain
- 12 Exterior Service Drains
- 13 Front SCR Access Panel

CONSTRUCTION //

- 14 Stainless Steel Hardware
- 15 Powder-coated Steel Enclosure
- 16 Lockable Access Doors
- 17 Automotive Door Seals
- 18 47 Gallon Fuel Tank
- 19 Heavy-Duty Steel Tow Trailer



AIR COMPRESSOR MODEL PDSF375DP/DPC-6E1 (AFTER COOLER)



AIR COMPRESSOR SPECIFICATIONS
COMPRESSOR TYPE
DUAL PRESSURE 375 CFM @ 100 PS
375 ACTUAL FREE AIR DELIVERY
WORKING PRESSURE
WORKING PRESSURE (MAXIMUM)
WORKING PRESSURE (MINIMUM)
DUAL PRESSURE 330 CFM @ 150 PS
330 ACTUAL FREE AIR DELIVERY
WORKING PRESSURE
WORKING PRESSURE (MAXIMUM)
WORKING PRESSURE (MINIMUM)
COMPRESSOR LUBRICATING OIL CAP.
COMPRESSOR LUBRICATING SYSTEM
DRIVING SYSTEM
RECEIVER TANK CAPACITY
AIR SERVICE VALVES
SEPERATION FILTERS
OIL COOLER TYPE
COMPRESSOR OIL FILTER
SOUND dBA RATING
ENGINE MAKE & MODEL
ENGINE TYPE
ASPIRATION
NUMBER OF CYLINDERS

PDSF375DP/DPC-6E1
Single-Stage Oil Cooled, Screw Type
375 cfm
100 psig
120 psig
58 psig
330 cfm
150 psig
180 psig
58 psig
10.5 gal
Forced Lubrication by Compressed Air
Direct Drive w/Rubber Dampener Coupling
20.3 g/min
3/4" Male Ball Valve x 2 2" Female Ball Valve x 1

Internal Oil Separator Air Pressurized Tube and Fin Spin-on Cartridge Type 76 dBA KUBOTA® V3800TIEF4B-COHE-1 4-cycle, Water-cooled, Direct injection, Diesel Turbocharged + Turbo After Cooler

ENGINE MAKE & MODEL (Continued)
ENGINE DISPLACEMENT
HORSEPOWER RATING (@2600 RPM)
SAE BRAKE HORSEPOWER (@2600 RPM)
OPERATING SPEED (LOW IDLE)
OPERATING SPEED (HIGH IDLE)
EPA TIER 4F
CARB EMISSION CERTIFIED
EMISSIONS TIER
EMISSIONS TYPE
FUEL TANK CAPACITY
FUEL FILTER QUANTITY/ TYPE
FUEL PUMP
DIESEL EXHAUST FLUID (DEF) CAPACITY
DEF CONSUMPTION
ENGINE OIL CAPACITY
COOLANT CAPACITY
ELECTRICAL SYSTEM - VOLTAGE
BATTERY RATING
BATTERY GROUP
AMBIENT TEMPERATURE (MIN./MAX.)
OPERATING ALTITUDE (MAXIMUM)
RUNTIME (FULL LOAD / 70% LOAD)
CONTAINMENT
FUEL CONSUMPTION
FULL LOAD
70% LOAD
NO LOAD

KUBOTA® V3800TIEF4B-COHE-1
230 cu in
104.5 HP / 77.9 kW
114.1 HP
1300 rpm
2600 rpm
Tier 4 Final, Model Year 2023 EPA & CARB Certification
EPA Tier 4 Final
DOC, PTOX-DPF, ASC, SCR, EEGF
47.0 gal
1 Pre-filter, 1 Sedimenter, 1 Fuel Filte
Fuel Air-bleeding Electric Pump w/Filte
5.3 gal
0.12 gal/hr
3.4 gal
4.12 gal
12V, 90A Alternator
695 CCA / 120 Ah
130F51, 12V
5°F to 104°F, Humidity < 80%
4,921 ft
9.1 hrs / 13.8 hrs
No Fluid Containment
5.12 gal/hr
3.40 gal/hr
1.58 gal/hr

WEIGHTS & DIMENSIONS
LENGTH x WIDTH x HEIGHT
DRY WEIGHT/ WITH AFTERCOOLER
OPERATING WT./ WITH AFTERCOOLER
LENGTH
WIDTH
HEIGHT
TOWING PACKAGE
LENGTH x WIDTH x HEIGHT
LENGTH
WIDTH
HEIGHT
OPERATING WEIGHT w/TOWING (GVWR)
TOWING SPEED (MAXIMUM)
TRACK WIDTH TOW PACKAGE
WHEEL SIZE - TIRE RATING
NUMBER OF AXLES / RATING
BRAKING TYPE
LIGHTING TYPE
ADJUSTABLE HITCH HEIGHT
COMPLIANCE & CERTIFICATIONS
FLUID CONTAINMENT
USA DOT COMPLIANT
CSA LISTED
TRANSPORT CANADA COMPLIANT
DIESEL ENGINE EPA TIER LEVEL

_	
	103.5" x 57.3" x 47.6"
	3,737 lbs / 3,803 lbs
	4,233 lbs / 4,299 lbs
_	103.5"
	57.3"
_	47.6"
٠,	174" x 77.75" x 69"
l	174"
	77.75"
_	69"
)	4,653 lbs / 4,719 w/After Coole
_	65 mph - Conditions Permitting
_	68"
_	ST235/80R16E / 3,520 lbs @ 80ps
_	1 Spring Axle / 5,300 lbs
_	Electric w/Breakaway Battery System
_	LED
-	3-Position
	No Fluid Containment
-	Meets FMVSS
-	Not CSA Listed
-	Transport Canada Compliant
-	Tier 4 Final & CARB Compliant

All specifications are subject to change without prior notice. Visit anacorp.com for the most current information.

OPTIONAL ACCESSORIES




Integrated After Cooler



Double Hose Reel Kit



Single Hose Reel Kit











Battery Charger



Engine Block Heater



Battery Blanket



www.discount-equipment.com



TO PURCHASE THIS PRODUCT PLEASE CONTACT US



Equipment Financing and Extended Warranties Available



Discount-Equipment.com is your online resource for commercial and industrial quality parts and equipment sales. 561-964-4949
visit us on line @ www.discount-equipment.com

Select an option below to find your Equipment

Search by Manufacturer

Search by Product Type

Request a Quote

We sell worldwide for the brands: Genie, Terex, JLG, MultiQuip, Mikasa, Essick, Whiteman, Mayco, Toro Stone, Diamond Products, Generac Magnum, Airman, Haulotte, Barreto, Power Blanket, Nifty Lift, Atlas Copco, Chicago Pneumatic, Allmand, Miller Curber, Skyjack, Lull, Skytrak, Tsurumi, Husquvarna Target, Stow, Wacker, Sakai, Mi-T-M, Sullair, Basic, Dynapac, MBW, Weber, Bartell, Bennar Newman, Haulotte, Ditch Runner, Menegotti, Morrison, Contec, Buddy, Crown, Edco, Wyco, Bomag, Laymor, EZ Trench, Bil-Jax, F.S. Curtis, Gehl Pavers, Heli, Honda, ICS/PowerGrit, IHI, Partner, Imer, Clipper, MMD, Koshin, Rice, CH&E, General Equipment, Amida, Coleman, NAC, Gradall, Square Shooter, Kent, Stanley, Tamco, Toku, Hatz, Kohler, Robin, Wisconsin, Northrock, Oztec, Toker TK, Rol-Air, APT, Wylie, Ingersoll Rand / Doosan, Innovatech, Con X, Ammann, Mecalac, Makinex, Smith Surface Prep, Small Line, Wanco, Yanmar