

WINCO®

Quality Generators Since 1927

W10PTOS



Generator End:

- 100% copper windings - longer life and improved motor starting
- Single phase, 2 pole
- Rotating field brushless type
- Maintenance free bearings
- Class H Insulation
- Capacitor regulated

Features:

- 60A NEMA 14-60P full power plug included
- Large 3" voltmeter
- Low harmonic content, appropriate for sensitive loads
- Cast iron gear case with 515 RPM 1 3/8" spline input shaft
- Compact design for easy storage
- Square D mainline circuit breaker
- Protective PTO shield
- Heavy duty steel mounting base
- Helical gears for smooth operation
- Rodent protection
- Ground lug

Accessories (optional):

- PTO drive shaft (tumbling bar)
- PTO trailer kit
- 3 point hitch kit with PTO shaft
- Manual transfer switches

CONTINUOUS STANDBY RATING	10,000 WATTS
AMPS (1)	42
VOLTS	120/240
PHASE	Single
VOLTAGE REGULATION	+/- 5%
TOTAL HARMONIC DISTORTION	< 5%
GENERATOR HEAT TEMP RISE	125°C
TYPE	2-POLE REVOLVING FIELD
GENERATOR SPEED	3600 RPM
VOLTAGE CONTROL	CAPACITOR
PTO INPUT SPEED	515
REQUIRED INPUT HP (2)	20
MOTOR STARTING (3)	4 HP
120 VOLT RECEPTACLES	2x NEMA 5-20R
120/240 VOLT RECEPTACLES	1x NEMA 14-60R
MAIN LINE CIRCUIT BREAKER	40 AMP
DIMENSIONS (LxWxH)	25.1" x 13.375" x 20.8"
NET WEIGHT	156
SHIP WEIGHT	166
WARRANTY	1 YR

NOTES: (1) Unity (1.0) power factor (2) Required HP at PTO of tractor for full rated output. Each 2 HP of tractor power equals approximately 1 kW of electric power. (3) Code G capacitor start motor. Please consult factory or authorized dealer for further information.



Presented by:

Toll Free: 1-800-733-2112
sales@wincogen.com

www.wincogen.com

225 South Cordova Avenue
Le Center MN, 56057