

3200 & 6000-Watt Gasoline

ChoreMaster® Series


With commitment to quality and performance, Mi-T-M ChoreMaster® generators offer great power in a compact package. They provide maximum output under any given situation and are durable and reliable featuring a Mi-T-M or Honda OHV engine.



GEN-3200-OMMO



GEN-6000-SMHO



GFCI 5-20R



NEMA L14-20R
125/250V



CSA
CERTIFIED

All Models Feature Engine

- Mi-T-M OHV or Honda OHV engine with low-oil shutdown
- Recoil starting system

Alternator

- 100% copper windings

Frame

- Low profile, compact design
- Heavy-duty wraparound frame with 1-inch powder coated steel tubing

Components

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low-tone mufflers
- Fuel shut-off valve
- Heavy-duty industrial air cleaners hold up under extreme conditions

Miscellaneous

- USDA/USFS-approved spark arrestors
- Circuit breaker protected

Warranties

1 YEAR LIMITED MI-T-M ENGINE WARRANTY	2 YEAR LIMITED ALTERNATOR WARRANTY	3 YEAR LIMITED HONDA ENGINE WARRANTY
--	---	---

GEN-3200-OMMO Model Additional Features

Alternator

- Brushless 120V alternator
- Total harmonic distortion (THD) less than 6%

GEN-6000-SMHO Model Additional Features

Alternator

- Brushless 120V/240V alternator
- Total harmonic distortion (THD) less than 5%

Components

- Fuel gauge
- Fuel tanks are powder coated outside, zinc-plated inside to prevent rusting

Model Number	GEN-3200-OMMO	GEN-6000-SMHO
Max. AC Output	3200 watts	6000 watts
Rated AC Output	2600 watts	5500 watts
Displacement/Engine	208cc Mi-T-M OHV	337cc Honda OHV
Frequency/Voltage	60Hz/120V	60Hz/120V/240V
Max. Amps (120V/240V)	26.7	50.0/25.0
Cont. Amps (120V/240V)	21.7	45.8/22.9
Receptacles	120V, 20A GFCI duplex	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock
Main Circuit Breakers	20A push-button	(2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole
Rated Speed	3600 RPM	3600 RPM
Fuel Capacity	2.7 gallons	7.3 gallons
Run Time (at full load)	5.9 hours	6.9 hours
Dimensions (LxWxH)	25in.x18in.x18in.	28in.x24.5in.x22.25in.
Ship Wt.	140 lbs.	228 lbs.
Net Wt.	117 lbs.	203 lbs.

Models are compliant in 49 states. Cannot be sold in California.

ACCESSORIES

Part Number	Description	Fits Models
AW-5090-0002	Lifting hook - For easier portability, folds down and out of the way when not in use	GEN-6000-SMHO
AW-5740-0013	Wheel kit - For easier portability, pneumatic tires with tubes, rubber gripped handles	GEN-6000-SMHO