



Chicago Pneumatic



People.
Passion.
Performance.

CPPG Portable Generators (60 Hz)

The CPPG Inverter

The day-to-day silent solution below 3kVA. When it comes to fuel efficiency, compactness and noise attenuation, CPPG Inverter are the future. The variable speed smart control, together with paralleling capability, delivers efficient power with the lowest fuel consumption, adapting engine speed to the load conditions.



| TECHNICAL DATA | | CPPG INVERTER | |
|---|-------|--------------------|-----------------------|
| | | CPPG2iW | CPPG3iW |
| Generator data | | | |
| Rated frequency | Hz | 60 | 60 |
| Rated voltage | V | 120 | 120 |
| Nominal power output | kVA | 1,6 | 3,0 |
| Peak power output | kVA | 1,8 | 3,3 |
| Power factor cos Phi | | 1 | 1 |
| Fuel tank capacity | l | 4 | 10 |
| Fuel autonomy at nominal power | h | 5 | 6 |
| Sockets configuration | | 2 x 3P20A | 2 x 3P20A + 1 x 3P30A |
| 3P20A: Nema 120 V 20 A 3P30A: Nema 120 V 30A Twist Lock | | | |
| Engine | | | |
| Model | | CP148F Gasoline | CP170FD Gasoline |
| Nominal speed | rpm | 5000 | 3600 |
| Power output | kWm | 2,4 | 4,4 |
| Displacement | cm3 | 79 | 212 |
| Starter type | | Recoil | Electric / Recoil |
| Exhaust gas compliant | | EPA Tier 2 | EPA Tier 2 |
| Alternator | | | |
| Power | kVA | 2 | 3 |
| Noise level | | | |
| Sound pressure level (LpA) at 7m | dB(A) | 65 | 63 |
| Sound power level (LwA) | dB(A) | 90 | 88 |
| Weight and dimensions | | | |
| Length | mm | 500 | 580 |
| Width | mm | 285 | 440 |
| Height | mm | 455 | 510 |
| Weight | kg | 21 | 45 |

The CPPG Standard

The CPPG Standard Line offers straight forward gasoline generators with all the features you need for your occasional use built right in. They are designed to deliver stable electrical output and safe, user-friendly operation over a long service life.



| TECHNICAL DATA | | CPPG STANDARD | | |
|--|-------|-----------------------|-----------------------|-----------------------|
| | | CPPP2.5W | CPPG5.5W | CPPG7W |
| Generator data | | | | |
| Rated frequency | Hz | 60 | 60 | 60 |
| Rated voltage | V | 240 / 120 | 240 / 120 | 240 / 120 |
| Nominal power output | kVA | 2,5 | 5 | 6,5 |
| Peak power output | kVA | 2,8 | 5,5 | 7,0 |
| Power factor cos Phi | | 1 | 1 | 1 |
| Fuel tank capacity | l | 15 | 25 | 25 |
| Fuel autonomy at nominal power | h | 11 | 10 | 8 |
| Sockets configuration | | 2 x 3P20A + 1 x TL240 | 4 x 3P20A + 1 x TL240 | 4 x 3P20A + 1 x TL240 |
| 3P20A: Nema 120 V 20A TL240: Nema 240/120 V Twist Lock | | | | |
| Engine | | | | |
| Model | | CP200FA Gasoline | CP390FD Gasoline | CP420FD Gasoline |
| Nominal speed | rpm | 3600 | 3600 | 3600 |
| Power output | kWm | 4,1 | 8,2 | 9 |
| Displacement | cm3 | 196 | 389 | 420 |
| Starter type | | Recoil | Electric / Recoil | Electric / Recoil |
| Exhaust gas compliant | | EPA Tier 2 | EPA Tier 2 | EPA Tier 2 |
| Alternator | | | | |
| Power | kVA | 2,5 | 5,5 | 6,5 |
| Noise level | | | | |
| Sound pressure level (LpA) at 7m | dB(A) | 70 | 72 | 76 |
| Sound power level (LwA) | dB(A) | 95 | 97 | 101 |
| Weight and dimensions | | | | |
| Length | mm | 590 | 675 | 680 |
| Width | mm | 430 | 540 | 550 |
| Height | mm | 480 | 540 | 550 |
| Weight | kg | 52 | 79 | 83 |



Over 100 Years of Experience

Since 1901 the Chicago Pneumatic name has represented high-performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools and air compressors are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.



For more information, please contact your CP partner:

Use only authorized parts. Any damage or malfunction caused by the use of unauthorized parts is not covered by Warranty or Product Liability.