



Welcome to North Slope

FROST



STANDARD CHILLER FEATURES

- Rated at ambient temperatures from 35° F to 100° F
- Hermetically sealed compressor
- Lite industrial 3.5 GPM centrifugal pump
- Non-ferrous piping system
- Submersed copper coil evaporator
- 1.5 Gallon corrosion resistant thermally insulated reservoir
- Environmentally acceptable r410a refrigerant
- Powder-coated steel cabinet
- Available voltage: 110v
- Standard 110V cord and plug for electrical connections
- Mounted on 4casters for easy mobility



REFRIGERATION

- This series of chillers is totally self-contained and requires only a power connection
- High side filter drier
- Full refrigerant charge
- Environmentally friendly r410a

Product Type	Model Number	Fluid Temperature Range (°F)	Refrigerant	Pump	Reservoir Capacity	Cooling Capacity	Capacity (BTU/hr) *	Dimensions	Weight (Approx)	Amps
FROST	NSC0250-FROST	45°F - 85°F	r410a	3.5 GPM MAX	1.5 GALLON	3,000	3,000	22"L x 11"W x 21.5"H	64 lbs	6.5
	NSC1000-FROST	45°F - 85°F	r410a	3.5 GPM MAX	4 GALLON	12,000	12,000	26"L x 18.5"W x 35"H	174 lbs	8

New Equipment - Used Equipment - Rental Equipment - Parts and Accessories



www.discount-equipment.com

561-964-4949

Parts: wbparts@Discount-Equipment.com

Sales: info@Discount-Equipment.com



NORTH SLOPE CHILLERS

FROST FEATURES

CATCH A COLD WITH FROST

This non-industrial portable chiller system is a fantastic entry-level unit if you are ready to test the waters with chilling. Ideal for single container/application chilling, Frost pumps 3.5 gallons per minute. Frost's fluid temperature range is 45°F - 85°F, and allowing for a 10°F differential, it will cool contents down to 55°F with ease.



CHILLER: Air-cooled, stand-alone chiller designed for indoor operation. Capacity is 3,000 BTU's/hr at rated conditions. Set up for ambient temperatures 35° F to 100° F (for higher or lower ambient conditions please consult North Slope).



PUMP: This chiller is equipped with a continuous duty, non-ferrous pump. Set up to deliver 3.5 GPM. The fluid types are to be water or water/glycol (for other fluids consult manufacturer).



EVAPORATOR: Submersed copper coil continuously formed is the most reliable design in the industry. It is less susceptible to freezing and fluid contaminations.



RESERVOIR: Corrosion resistant insulated tank; It will include: drain, sight glass and manual fill port. Sight glass is easily visible from the exterior of the chiller.



ELECTRICAL:

- Available as 115v/1/60Hz
- On/Off
- Current = 5.7A @ 110V

New Equipment - Used Equipment - Rental Equipment - Parts and Accessories



www.discount-equipment.com

561-964-4949

Parts: wpbparts@Discount-Equipment.com

Sales: info@Discount-Equipment.com