



STV-50X

Outstanding Features

- Silicon Carbide Mechanical Seals for Increased Abrasive Resistance, Longer Life, and Less Maintenance
- Impellers and Volutes are Constructed of Spheroidal Graphite Ductile Cast Iron for Increased Durability, and Long Operating Life
- Pump Housings are Made of Die Cast Aluminum for Strength, Weight Reduction, and Portability
- Strong Transport Protection Powder Coated Steel Roll Cages
- Reliable **KOSHIN** Engines with Low Oil Shut Off Two Year Limited Warranty, Engines and Pumps



STV-80X

PERFORMANCE CURVES



**Optional
Wheel Kit
Available**

	STV-50X	STV-80X
Suction, Discharge Size	2" NPT	3" NPT
Maximum Output (GPM)	163	246
Maximum Discharge Head (ft)	90	90
Maximum Suction Lift (ft)	26	26
Maximum Pressure (Psi)	39	39
Engine Model	K180	K180
Engine Displacement (cc)	179	179
Engine Horse Power	4.7	4.7
Fuel Tank Capacity (Gal)	0.95	0.95
Full Load Run Time (hrs)	2	2
Fuel Type	Automotive Gasoline	
Packaged Weight (Lbs)	66	78
Packaged Dimensions (LxWxH)	20"x17"x19"	21"x17"x19"