

### ENGINE

- Isuzu 4LE2TAGV-03- liquid cooled, diesel engine; Final Tier 4
  - Standby - 40.2 hp @ 1800 rpm
  - Prime – 36.2 hp @ 1800 rpm
  - 4 cylinder
  - 2.2 L displacement
- Polyethylene Fuel Tank:
  - Fuel Type: Diesel
  - Fuel Capacity: 51.4 gal. (194.5 L)
  - 3.5 in. (88.9 mm) fill port
- Fuel Consumption:
  - Full Load: 2.1 gph (7.8 Lph)\*
  - Lights Only: 1.05 gph (3.97 Lph)\*
  - Maximum Runtime (Lights Only): 48\*
- 60 Hz engine/generator
- Cooling system capable of operating at 120°F (49°C) ambient
- 250 hour service interval
- Full flow oil filter, spin on type
- Fuel filter with replaceable element
- Dry type cartridge air filter
- Wind Rating: 65 mph (105 kph)

*\*Results based on engine manufacturer and field test data after 100-hour engine break-in period and may vary based on factors including age and maintenance of equipment, environmental conditions and fuel density. Consult the Owner's Manual for fuel and maintenance recommendations.*

### GENERATOR

- Marathon Electric<sup>®</sup>
  - Brushless
- 20 kW standby output
- 120/240 VAC – 167/83A
- +/-1% electronic voltage regulation

### ENGINE CONTROLS

- Engraved, aluminum punched and anodized control panel
- Four position keyed switch – glow plugs (preheat, off, run, start)
- Hour meter
- Automatic low oil/high temperature shutdown system

### ELECTRICAL AND SYSTEM CONTROLS

- Individual floodlight circuits with 15A breakers
- Ballast indicator lights
- 100A start limit breaker (assures no load condition exists before starting)
- Standard individually breakered convenience outlets:
  - (2) 120 VAC 20 Amp GFCI duplex outlets (NEMA 5-20R type)
  - (2) 240 VAC 30 Amp Twistlock outlets (NEMA L6-30R type)
  - (2) 240 VAC 50 Amp Twistlock outlets (Non-NEMA 6369)
- 720CCA wet cell battery



**FLOODLIGHTS**

- Four (4) 1050 watt metal halide; 462,000 total lumens
- Oval aluminum reflector
- Tempered glass lens
- Silicone gaskets for moisture and dust protection
- Friction disc mounting for tool less positioning
- Individual floodlight On/Off switches

**MAST**

- Horizontal mast; 30 ft. (9.14 m) maximum extension, 3-section
- Urethane guides on all sides of mast tubes
- Industrial black powder coat finish
- Dual winch system located at ergonomic height allowing single person operation
- 359° ground-level rotation with locking system
- Coiled mast cord

**ENCLOSURE**

- Steel enclosure – 14-gauge
  - UV & fade resistant, high temperature cured, white polyester powder paint
  - 68 dB(A) at 23 ft. (7 m) – prime power
- Stainless steel hinges on doors
- Multi-lingual operating/safety decals
- License plate holder with light
- Manual holder with operating manual
- Equipped with single lifting eye and fork pockets

**TRAILER**

- Removable tongue – 48 in. (1219.20 mm) long
- (4) 2000 lb. (907.18 kg) adjustable leveling jacks – 4 point stance
- All jacks transport and lock in horizontal position for storage
- Side outriggers – 140 in. (3.56 m) span
- 7800 lb. (3538 kg) safety chains with spring loaded safety hooks
- 2 in. (50.8 mm) ball hitch
- Single wall polyethylene fenders
- DOT approved tail, side, brake, and directional lights
  - Recessed rear lights
- 3000 lb. (1361 kg) leaf spring axle
- P205/75R15 – 6 ply
- 58 in. (1473 mm) axle span

**WEIGHT & DIMENSIONS**

- Dry weight: 2315 lbs. (1050 kg)
- Operating weight: 2630 lbs. (1193 kg)
- Mast stowed: 115 x 68 x 70 in. (2.92 x 1.73 x 1.78 m)

**WARRANTY**

2 Years / 2000 Hours

**CERTIFICATIONS**

CSA Certified

**OPTIONS**

Contact sales representative or factory for a list of current available options

Discount-Equipment.com

