

NEW MLT6 LED LIGHT TOWERS

CHOOSE THE MODEL THAT IS RIGHT FOR YOU

Introducing the newest members of the award-winning MLT6 light tower family from Generac Mobile.

The new **MLT6SMDS** and **MLT6SKDS** offer many of the same benefits as our popular MLT6SMD LED light tower, but with simplified features and controls, and choice of Mitsubishi or Kubota engine.

The full featured **MLT6SMD** comes standard with our Power Zone controller for maximum programmability, including auto start and stop and dusk-to-dawn sensor, as well as a variable ECOSpeed engine for ultimate fuel efficiency. Automatic voltage regulation (AVR) ensures that on-board power is clean and consistent - safe for sensitive electronics and more.

All MLT6 LED light towers feature our robust and powerful LED fixtures, designed to last the life of the tower. Never change a bulb again!



| FEATURE | MLT6SMDS NEW! | MLT6SKDS NEW! | MLT6SMD |
|---------------------------------|--|--|-------------------------|
| Engine | Single Speed Mitsubishi® | Single Speed Kubota® | ECOSpeed Mitsubishi® |
| Max Mast Height | 23 ft (7 m) | 23 ft (7 m) | 23 ft (7 m) |
| Lights | (4) 296W LED | (4) 296W LED | (4) 296W LED |
| Total Lumens | 172,200 | 172,200 | 172,200 |
| Coverage @ Min. 0.5 ft-c | 19,526 ft² (1,814 m²) | 19,526 ft² (1,814 m²) | 19,526 ft² (1,814 m²) |
| Max Run Time (Lights Only)* | 117 hrs | 138 hrs | 203 hrs |
| Standard Controller | Analog, Digital Power Zone Optional | Analog, Digital Power Zone Optional | Digital Power Zone |
| Individual On/Off Light Control | No | No | Yes |
| Dusk-To-Dawn Sensor | Optional | Optional | Standard |
| Winch | Manual, Electric Option | Manual, Electric Option | Manual, Electric Option |
| Oil Service Interval* | 1000 hrs | 750 hrs | 1000 hrs |
| Onboard Export Power | Up to 6kW | Up to 6kW | Up to 6kW |
| AVR | No | No | Yes |

*Results based on engine manufacturer and field test data after 100 hour engine break-in period and may vary based on factors including age and maintenance of equipment, environmental conditions and fuel density. Consult the Owner's Manual for fuel and maintenance recommendations. 1000 hour service interval only applies to LED light towers with Mitsubishi engines.

www.discount-equipment.com



GENERAC® | **MOBILE**