

ENGINE

- Kubota® D1105-E3BG - liquid cooled, diesel engine; Final Tier 4
 - Standby - 15.4 hp @ 1800 rpm
 - Prime - 13.5 hp @ 1800 rpm
 - 3 cylinder
 - 1.12 L displacement
- Polyethylene Fuel Tank:
 - Fuel Type: Diesel
 - Fuel Capacity: 56.4 gal. (213.5 L)
 - 3.5 in. (88.9 mm) fill port
- Fuel Consumption:
 - Full Load: 0.70 gph (2.65 Lph)*
 - Lights Only: 0.35 gph (1.32 Lph)*
 - Maximum Runtime (Lights Only): 161 hours*
- 60 Hz engine/generator
- Cooling system capable of operating at 120°F (49°C) ambient
- 750 hour service interval
- Full flow oil filter, spin on type
- Fuel filter with replaceable element
- Dry type cartridge air filter
- Wind Rating: 65 mph (105 kph)



**Results based on engine manufacturer and field test data after 100-hour engine break-in period and may vary based on factors including age and maintenance of equipment, environmental conditions and fuel density. Consult the Owner's Manual for fuel and maintenance recommendations.*

GENERATOR

- Marathon Electric®
 - Brushless
- 8 kW standby output
- 120/240 VAC – 66/33A
- +/-6% capacitor voltage regulation

ENGINE CONTROLS

- Engraved, aluminum punched and anodized control panel
- Four position keyed switch – glow plugs (preheat, off, run, start)
- Hour meter
- Automatic low oil/high temperature shutdown system

ELECTRICAL AND SYSTEM CONTROLS

- Individual floodlight circuits with 15A breakers
- Ballast indicator lights
- 40A start limit breaker (assures no load condition exists before starting)
- Standard individually breakered convenience outlets:
 - (2) 120 VAC 20 Amp GFCI duplex outlets (NEMA 5-20R type)
 - (1) 240 VAC 30 Amp Twistlock outlets (NEMA L6-30R type)
- 440CCA wet cell battery

FLOODLIGHTS

- Four (4) 1050 watt metal halide; 462,000 total lumens
- Oval aluminum reflector
- Tempered glass lens
- Silicone gaskets for moisture and dust protection
- Friction disc mounting for tool less positioning
- Individual floodlight On/Off switches

MAST

- Horizontal mast; 30 ft. (9.14 m) maximum extension, 3-section
- Dual winch system located at ergonomic height allowing single person operation
- Urethane guides on all sides of mast tubes
- Industrial black powder coat finish
- 359° ground-level rotation with locking system
- Coiled mast cord

ENCLOSURE

- Steel enclosure – 14-gauge
 - UV & fade resistant, high temperature cured, white polyester powder paint
 - 68 dB(A) at 23 ft. (7 m) – prime power
- Stainless steel hinges on doors
- Multi-lingual operating/safety decals
- License plate holder with light
- Manual holder with operating manual
- Equipped with single lifting eye on mast and fork pockets

TRAILER

- Removable tongue – 48 in. (1219.20 mm) long
- (4) 2000 lb. (907.18 kg) adjustable leveling jacks – 4 point stance
- All jacks transport and lock in horizontal position for storage
- Side outriggers – 140 in. (3.56 m) span
- 7800 lb. (3538 kg) safety chains with spring loaded safety hooks
- 2 in. (50.8 mm) ball hitch
- Single wall polyethylene fenders
- DOT approved tail, side, brake, and directional lights
 - Recessed rear lights
- 2200 lb. (998 kg) leaf spring axle
- ST175/80D13 – 6 ply
- 56 in. (1422.4 mm) axle span

WEIGHT & DIMENSIONS

- Dry weight: 1712 lbs. (777 kg)
- Operating weight: 1925 lbs. (874 kg)
- Mast stowed: 170 x 68 x 70 in. (4.32 x 1.73 x 1.78 m)

WARRANTY

2 Years / 2000 Hours

CERTIFICATIONS

CSA Certified

Discount-Equipment.com

