

MOBILE TRASH PUMPS

GENERAC[®]
MOBILE

**Discount
Equipment**

www.discount-equipment.com



MOBILE TRASH PUMPS

With the lowest suction height in the industry and Final Tier 4 engines, Generac Mobile trash pumps are designed for ultimate performance - allowing for fast and efficient high volume dewatering projects. A choice of wet prime and dry prime options allow you to specify the perfect pump for your needs. Wet prime pumps offer excellent value, while dry prime options enhance efficiency and enable faster pump priming and set-up. Durable and reliable Cornell® pump components mean less downtime on the job. Final tier 4 engines maximize fuel efficiency and minimize jobsite emissions. For jobsites in sound-sensitive locations, an optional sound attenuated flip-hood cabinet provides quiet operation. All models handle water and solids up to 3 inches (76.2 mm) in diameter, and operate for extended run times to ensure that your worksite is clean and ready for the next phase. The LOFA controller with back-lit LCD display makes operation hassle-free.

APPLICATIONS

- General Construction
- Road Work
- Municipal Projects
- Mining Operations
- Excavation Projects
- Sewer Bypass



SPECIFICATIONS

Model	MTP4DZD	MTP4DZV	MTP4SZ	MTP6DZD	MTP6DZV	MTP6SZ
Engine USA (METRIC)						
Engine Make	Deutz D2.9			Deutz TD2.9		
EPA Tier	Final Tier 4					
Controller	LOFA CP750					
Performance						
Pump Output: gpm (Lpm)	1450 (5489)		900 (3407)	2750 (10409)		1680 (6359)
Total Dynamic Head: ft (m)	165 (50.29)			150 (45.7)		170 (52)
Max. Solid Diameter: in (mm)	3 (76.2)					
Max. Lift Suction: ft (m)	28 (8.5)					
Pump						
Pump Make	Cornell 4NNTL Pump		Cornell 4STX	Cornell 6NNT Pump		Cornell 6STX
Fitting Size	4 NPTF			6 NPTF		
Priming System	Diaphragm - Dry	Venturi - Dry	Self Prime - Wet	Diaphragm - Dry	Venturi - Dry	Self Prime - Wet
Trailer Mounted Suction Height: in (m)	29 (0.73)		39 (1.0)	30 (0.76)		41 (1.04)
Capacities						
Fuel Tank Capacity Total/ Usable gal (L)	113 (428) / 100 (379)					
Fuel Consumption @ Prime: gph (Lph)	2.93 (11.1)	2.93 (11.1)	2.30 (8.71)	3.60 (13.6)	3.60 (13.6)	3.27 (12.4)
Weight & Dimensions						
Trailer Mounted: l x w x h, in (m)	150.12 x 75 x 73.88 (3.81 x 1.91 x 1.88)					
Skid Mounted: l x w x h, in (m)	91.16 x 66.6 x 61.5 (2.32 x 1.69 x 1.56)					
Trailer Mounted, Dry Weight: lbs (kg)	3836 (1740)		3714 (1685)	4275 (1939)		3,914 (1775)
Trailer Mounted, Operating Weight: lbs (kg)	4650 (2109)		4528 (2054)	4970 (2254)		4728 (2144)
*Dry Trailer Mounted, Cabineted Weight: lbs (kg)	3,836 (1,740)		N/A	4,123 (1,870)		N/A

For complete specifications, visit GeneracMobileProducts.com.

*Cabinet option not available on wet prime models.



www.discount-equipment.com

Discount-Equipment.com



*Assembled in the USA using domestic and foreign parts



Part No. 0202550 REV. A 12/2018
©2018 Generac Power Systems, Inc. All Rights Reserved.
Specifications are subject to change without notice.