


P32N

GRINDER POLISHER

MAXIMUM PRODUCTIVITY FOR
GRINDING AND POLISHING



FEATURES

- Eliminates swirl marks left by conventional grinding methods
- Direct drive system
- Multiple variations to get the perfect model
- Robust Construction
- Dust extraction port
- Dust-free when used with suitable dust control vacuum
- Large diameter wheels for excellent mobility and stability
- Removable weight to vary grinding pressure
- Simple adjustment to level to the floor surface
- Fully adjustable handle
- Accurate grinding of concrete surfaces
- Removal of old floor coatings and contaminants
- Latex and adhesive removal
- Grinding and polishing of resin-based and tiled terrazzo
- Fully compatible with the iShine Floor System

TECHNICAL SPECS

Voltage	400VAC OR 460VAC
Power Output	15hp (11kW)
Phase	3 Phase
Cycles	50Hz/60Hz
Head Speed	0 - 1010rpm
Motor Speed	0 - 1765rpm
Grinding Plate	0 - 105rpm
Grinding Width	32" (814mm)
Grinding Heads	4
Head Diameter	10.5" (270mm)
Water Tank	6gal (22.7L)
Hose Size	3" (75mm)
Length	57" (1450mm)
Width	33" (830mm)
Height	52" (1320mm)
Weight	950lbs (431kg)



www.Discount-Equipment.com