



GRINDERS & POLISHERS



SHOTBLASTERS



FLOOR REMOVAL



SCARIFIERS



SCREED



TROWELS



BARTELL

morrison

SPE

Innovatech

CONTEC NORTH AMERICA


PRECISION METAL WORKS



SAWS



TOOLING & CONSUMABLES



DIAMOND BLADES



SPREADERS



COMPACTION



GENERATORS



MIXERS

SCARIFIERS

PRODUCT CATEGORY



BARTELLGLOBAL.COM

FEATURES AND BENEFITS

BEF 200N



FEATURES

- Rigid, compact design
- Quick Lift - Pulls Cutters In/Out of Cut
- 50mm (2") dust extraction port
- Dust free when operated with a suitable vacuum
- Large diameter wheels for excellent mobility and stability
- Welded construction is rigid and strong
- Fine Adjust- Screw type raise and lower control
- Firm engine mounting plate
- Front wheels protected from debris
- Height adjustment at the handle

BEF 275



FEATURES

- 50mm (2") dust extraction port
- Dust free when operated with recommended vacuum
- Six flail shafts, heavy duty TCT cutters
- Large wheels for excellent mobility & stability
- Forward mounted cutter drum for perfect balance
- Side plate access for easy drum removal
- Adjustable handle
- Strong and rigid design
- Accurate depth control

BEF 320



FEATURES

- 50mm (2") dust extraction port
- Dust free when operated with recommended vacuum
- Hydraulic drum raise and lower
- Variable speed
- Self-propelled, hydrostatic drive
- Forward and reverse controls
- Up-cutting drum for efficiency
- Heavy-duty build
- Accurate depth control

COMPLETE LINE

BEF 200N

TECHNICAL SPECS

Type	Electric (1 Phase)	Electric (1 Phase)	Electric (3 Phase)	Gas / Petrol
Part Number	BEF 200N-1	BEF 200N-2 (A)	BEF 200N-3	BEF 200N-4(A)
Power Output	3hp / 2.2kW	3hp / 2.2kW	3hp / 2.2kW	(Gross) 5.5hp/4kW
Voltage	110V	230V	-	-
Cutter Head Speed	1738 RPM	1738 (2090)	1738 RPM	1833 RPM
Length	990mm (39")	990mm (39")	990mm (39")	990mm (39")
Width (Body)	375mm (15")	375mm(15")	375mm (15")	360mm (14")
Width (INCL. Handle)	429mm (16")	429mm (16")	429mm (16")	429mm (16")
Height	942mm (37")	942mm (37")	942mm (37")	942mm (37")
Weight	62kg (137lbs)	62kg (137lbs)	62kg (137lbs)	58kg (127lbs)
Working Width	200mm (7.9")	200mm (7.9")	200mm (7.9")	200mm (7.9")
Working Distance from Wall	60mm (2.4")	60mm (2.4")	60mm (2.4")	50mm (1.9")
Engine RPM	-	-	-	3000 RPM
Motor RPM	2870 RPM	2870 (3450)	2870 RPM	-

BEF 275

BEF 320

TECHNICAL SPECS

Type	Petrol / Gas	Electric	Electric	Electric	Diesel
Part Number	BEF 275-1	BEF 275-2	BEF 275-7	BEF 320-1A	BEF 320-3A
Power Output	11hp / 8.2kW	10hp / 7.5kW	10hp / 7.5kW	15hp / 11.2kW	10hp / 7.5kW
Voltage	-	400v / 460v	230v 3 Phase	400/460v 3 Phase	-
Cycles	-	50 / 60Hz	50 / 60Hz	50 / 60 Hz	-
Cutter Head Speed	1640 RPM	1640 RPM	1640 RPM	933 RPM	1333 RPM
Starter	-	-	-	Star / Delta	Manual
Travel Speed	-	-	-	0-12 m/min (0-39 ft/min)	0-12 m/min (0-39 ft/min)
Length	1220mm (48")	1220mm (48")	1220mm (48")	1230mm (48.4")	1230mm (48.4")
Width	511mm (20.1")	511mm (20.1")	511mm (20.1")	590mm(23.2")	590mm(23.2")
Height	900mm (35.4")	900mm (35.4")	900mm (35.4")	1220mm (48")	1220mm (48")
Weight	145kg (319lbs)	150kg (331lbs)	150kg (331lbs)	339kg (749lbs)	319kg (702lbs)
Working Width	275mm (10.8")	275mm (10.8")	275mm (10.8")	320mm(12.6")	320mm(12.6")
Working Distance from Wall	65mm (2.6")	65mm (2.6")	65mm (2.6")	40mm(1.6")	40mm(1.6")
Engine RPM	3000 RPM	2800 RPM	2800 RPM	-	-