

BEF 200N

SCARIFIER



HIGH PRODUCTION & RIGID DESIGN

FEATURES

- Rigid, compact design
- Quick Lift - Pulls Cutters In/Out of Cut
- 50mm dust extraction port
- Dust free when operated with a suitable vacuum
- Large diameter wheels for excellent mobility and stability
- Welded construction is rigid, strong and lower control
- Fine Adjust- Screw type raise and lower control
- Firm engine mounting plate
- Front wheels protected from debris
- Height adjustment at the handle

APPLICATIONS

- Cleaning and texturing concrete and asphalt
- Removal of paint, rust, grease, ice deposits, line markings, and concrete laitance
- Concrete reduction and scabbling
- Removal of roof chippings
- Grooving applications
- Cleaning concrete formwork and shuttering
- Non-slip finishes
- Removal of concrete and plaster droppings

TECHNICAL SPECS

Type	Electric (1 Phase)	Electric (1 Phase)	Electric (3 Phase)	Gas / Petrol
Part Number	BEF 200N-1	BEF 200N-2 (A)	BEF 200N-3	BEF 200N-4(A)
Power Output	3hp / 2.2kW	3HP / 2.2kW	3hp / 2.2kW	(Gross) 5.5hp/4kW (Net) 4.8hp/3.6kW
Voltage	110V	230V	-	-
Cutter Head Speed	1738 RPM	1738 (2090)	1738 RPM	1833 RPM
Length	990mm (39")	990mm (39")	990mm (39")	990mm (39")
Width (Body)	375mm (15")	375mm(15")	375mm (15")	360mm (14")
Width (INCL. Handle)	429mm (16")	429mm (16")	429mm (16")	429mm (16")
Height	942mm (37")	942mm (37")	942mm (37")	942mm (37")
Weight	62kg (137lbs)	62kg (137lbs)	62kg (137lbs)	58kg (127lbs)
Working Width	200mm (7,9")	200mm (7,9")	200mm (7,9")	200mm (7,9")
Working Distance from Wall	60mm (2.4")	60mm (2.4")	60mm (2.4")	50mm (1.9")
Engine RPM	-	-	-	3000 RPM
Motor RPM	2870 RPM	2870 (3450)	2870 RPM	-



BEF 200N



BEF 275



BEF 320