

The MS 230 Multistripper has been developed to satisfy the requirements of removing floor coverings from smaller projects and confined areas

This compact, easy-to-operate machine offers the user a solution for commercial and domestic applications. Forward motion is achieved by manual effort made easier by the adjustable handle to suit different body heights. All components are manufactured from the highest grade materials ensuring strength and reliability.



Specifications								
Туре	MS 230 Electric 110v	MS 230 Electric 220v						
Part Number	MS 230-1	MS 230-2						
Power Output	2.0hp (1.5kw)	2.0hp (1.5kw)						
Voltage	110	220						
Cycles	50hz	50hz						
Machine Dimensions								
Length	685mm (27")	685mm (27")						
Width	380mm (15")	380mm (15")						
Height	787mm (31")	787mm (31")						
Weight	45kg (99lbs)	45kg (99lbs)						
Work Width	230mm (9")	230mm (9")						
Engine/Motor	1400rpm	1400rpm						

Accessories	Part No.	Description		
MS 230	C301		Std Blade	



Features

- Fully adjustable chassis to adjust blade angle
- · Large diameter wheels for excellent mobility and stability
- Simple clamp arrangement for quick and easy blade change
- Optimum weight distribution to ensure high work rate
- · Handle height adjustable for operator control

Applications

- The removal of sheet vinyl, linoleum, cork, bonded carpet
- Woodblock, tiles, debonded membranes, sports surfaces
- Failed latex
- . Build-up of excess materials in production areas
- Mortar/Plaster droppings from concrete floors in new build

Specifications								
Machine	Volts	Plug Size	Cable Size	Max Cable Length	Transformer	Generator		
MS 230-1	110	16A 3 Pin	2.5mm (0.1") 3 Core	30m (98')	3 kva	5 kva		
MS 230-2	220	16A 3 Pin	2.5mm (0.1") 3 Core	30m (98')	-	5 kva		











www.Discount-Equipment.com