



**The SPE 9G Autoblaster machine has been developed for the preparation of smaller and confined areas**

A user-friendly, compact machine suitable for flooring contractors and the rental industry. Manually driven the machine starts and stops on a single deadmans handle delivering a measured volume of abrasive to the surface. Recognized in the industry as the modern, fast, versatile environmental dust-free means of dry abrasive cleaning and texturing of horizontal or slightly inclined surfaces. This eliminates mess normally associated with hand blasting and leaves an ideal surface for coatings and overlays to be applied. Available in 110v, 220, 50hz/60hz.

**Features**

- Blast unit constructed of manganese steel
- Handle fully adjustable in height
- Deadman handle automatically starts/stops blast motor and open/closes shot valve
- Front and rear support wheels fully adjustable in height
- Grill fitted into lower separator hopper unit assembly to eliminate foreign objects being allowed into the blastwheel and causing damage

**Applications**

- Removal of old coatings
- Providing non-slip surfaces
- Laitance removal on new concrete floors
- Texturing power floated concrete
- Shopping precincts
- Workshops
- Factories
- Warehouses



Specifications		
Type	110v	220v
Part Number	SPE 9G-1	SPE 9G-2
Power Output (Blast Motor)	2.6hp	2.6hp
Voltage	110	220
Cycles	50/60	50/60
Cleaning Width	230mm (9.1")	230mm (9.1")
Machine Dimensions		
Length	340mm (13.4")	340mm (13.4")
Width	840mm (33.1")	840mm (33.1")
Height	830mm (32.7")	830mm (32.7")
Weight	62kg (137lbs)	62kg (137lbs)
Vacuum Specifications		
<small>See Vacuum section page</small>		
Model	Suggested Vacuum Model	
SPE 9G-1	VAC 316-1	
SPE 9G-2	VAC 316-2	

Electrical Requirements						
Machine	Volts	Plug Size	Cable Size	Max Cable Length	Transformer	Generator
SPE 9G-1	110	16A 3 Pin	2.5mm (0.1") 3 Core	30m (98')	3 kva	5 kva
SPE 9G-2	220	16A 3 Pin	2.5mm (0.1") 3 Core	30m (98')	3 kva	5 kva