

SPE 12ES

SHOT BLASTER



TECHNICAL SPECS | SPE 12ES

| | |
|--------------------|--|
| Voltage | 230V/400V/460V |
| Phase | 3 Phase |
| Blast Motor Output | 10hp (7.5kw) |
| Cycles | 50/60Hz |
| Cleaning Width | 12" (305mm) |
| L x W x H | 46.5" x 18.9" x 47.2" (1180mm x 480mm x 1200mm) |
| Weight | 704lbs (320kg) |

TECHNICAL SPECS | SPE 12DC

| | |
|-------------|--|
| Type | 3 Phase |
| Part Number | SPE 12DC |
| Voltage | 400/460V |
| Cycles | 50/60Hz |
| L x W x H | 68.1" x 31.5" x 63" (1730mm x 800mm x 1600mm) |
| Weight | 770lbs (350kg) |

FEATURES

- Blast unit constructed of manganese steel
- Dust collector fitted with integral compressor and reverse air jet pulsation system to allow continuous working
- Blasting width can be reduced for line removal and weld inspection
- Self propelled variable speed drive allows complete operator control
- Grill fitted into lower separator hopper unit assembly to eliminate foreign objects being allowed into the blastwheel causing damage
- Capable of using up to S550 abrasive
- Fully machined blastwheel support bearing assembly (eliminates bearing problems and automatically self-aligns blastwheel components)
- Blastwheel can be rotated in both directions (Optional extra)
- Can be dismantled to pass through a 600mm (23.6") access hole in storage tanks



SPE 9G

SPE 9ES

SPE 12ES

SPE 16ES

SPE 20ES

SPE 20ES

ELECTRIC DRIVE