

www.Discount-Equipment.com





SHOTBLASTERS



FLOOR REMOVAL









CONCRETE GRINDERS



FEATURES AND BENEFITS

DFG280	SINGLE-HEAD GRINDER	FEATURES NEW Floating head design Folding Handle, with multiple settings for height adjustment Built in Lifting Handles Edge grinding capabilities on BOTH sides Flexible 'moreflex' coupling 				DFG280	S	
DFG250		FEATURES					TEC	HNI
	SINGLE-HEAD,	 Ballast weight that allows for perfect grinding in all situations Simple foot pedal to raise or lower machine during use 						
	HEAVY-DUTY	 Removable weight to vary grinding pressure Simple adjustment to level to the floor surface 		Part No.	DFG 280-3	DFG 280-5	DFG 280-6	DFG 2
	GRINDER	Accurate grinding of concrete surfaces		Туре	Electric	Electric 110V	Electric	Electri
		 Meets requirements of rental and contracting companies Fits easily in trunk for transportation 		Voltage	230V		120V	230V/4
			-	Power Output		3hp (2.2kW)		7.4hp
				Cycles	50Hz	50Hz	60Hz	50Hz/6
		FEATURES		Head Speed	1400rpm	1400rpm	1725rpm	1400rp
DFG400			•	Motor Speed	1400rpm	1400rpm	1725rpm	2800rp
	DUAL-HEAD	 Heavy duty gearbox drive system Large diameter wheels for excellent mobility and stability 		Length	40" (1020mm)	40" (1020mm)	40" (1020mm)	44.1" (
	GRINDER	Removable weight to vary grinding pressureSimple adjustment to level to the floor surface		Width	11" (280mm)	11" (280mm)	11" (280mm)	26.4" (
		Fully adjustable handle		Height	37" (940mm)	37" (940mm)	37" (940mm)	41" (10
		 Accurate grinding of concrete surfaces Meets requirements of rental and contracting companies 		Weight	97lbs (44kg)	97lbs (44kg)	97lbs (44kg)	352lbs
•		• Meets requirements of rental and contracting companies		Removable Wt.	, -	-	-	1 x 44
DFG500	DUAL-HEAD HEAVY-DUTY GRINDER	FEATURES • Two ballast weights that can be removed • Push button hydraulic raise and lower • Screw type handwheel allows machine to be accurately set to the surface • Large diameter wheels for excellent mobility and stability • Removable weight to vary grinding pressure • Simple adjustment to level to the floor surface • Accurate grinding of concrete surfaces • Meets requirements of rental and contracting companies			DFG	500	TEC	
		FEATUDES		Davit Ma		00.1 -		DEC
₩ DFG460		• Eliminates swirl marks left by conventional grinding methods		Part No.	DFG 50		DFG 460-2	DFG ·
2.00	3-HEAD	Direct drive system	-	Туре	Electric		Electric 00V/460V	Elect 230V
	PLANETARY	 Large diameter wheels for excellent mobility and stability Removable weight to vary grinding pressure 		Voltage	400V/4	400V Va	ariable Optional	Variable
	GRINDER	 Simple adjustment to level to the floor surface 		Power Output			5hp (2.2kW)	3hp (
	ORINDER	 Grinding and polishing of resin-based and tiled terrazzo Meets requirements of rental and contracting companies 		Cycles	50/60H		0Hz/60Hz	50Hz
		Fits easily in truck for easy transportation		Head Speed	1400rp	0 mc) - 277rpm	0 - 27
		Fully compatible with the iShine Floor System		Motor Speed	2800rp	om 0) - 1740rpm	0 - 17
DFG700		FEATURES		Length	55.1" (1	1400mm) 4	1" (1040mm)	41"(1
	3-HEAD	FEATURES		Width	28.5" (2	725mm) 18	8.5" (470mm)	18.5"
The second se	HEAVY-DUTY,	 Heavy duty gearbox drive system Grinding heads supported by multi-directional flexible coupling 		Height	43.4" (1	1100mm) 42	2.5" (1080mm)	42.5"
	PLANETARY	 Variable grinding speed (DFG 700-1) 		Weight	660lbs	s (300kg) 2'	273lbs (124kg)	273lk
	GRINDER	 Quick release drive plate system Pivotal weights Re-profiling of old concrete floors 		Removable Wt	. 2 x 441	lbs (20kg)		

VISIT OUR WEBSITE FOR MORE PRODUCT INFO, EDUCATIONAL CONTENT AND MORE

COMPLETE LINE





CHNICAL SPECS

	PECS			
DFG 250-1	DFG 250-2	DFG 400-5	DFG 400-3	DFG 400-2
Electric	Gas/Petrol	Electric	Electric	Gas/Petrol
230V/400V/460V	-	110V	230V	-
7.4hp (5.5kW)	13hp (9.7kW)	3hp (2.2kW)	3hp (2.2kW)	5.5hp (4.1kW)
50Hz/60Hz	-	50Hz/60Hz	50Hz/60Hz	-
1400rpm	700rpm/ 1400rpm	335rpm	335rpm	400rpm
2800rpm	1400rpm/ 2800rpm	2800rpm	2800rpm	2800rpm
44.1" (1120mm)	44.1" (1120mm)	32.3" (820mm)	32.3" (820mm)	32.3" (820mm)
26.4" (670mm)	26.4" (670mm)	22" (560mm)	22" (560mm)	22" (560mm)
41" (1040mm)	41" (1040mm)	27.6" (700mm)	27.6" (700mm)	27.6" (700mm)
352lbs (160kg)	268lbs (122kg)	189lbs (86kg)	189lbs (86kg)	172lbs (78kg)
1 x 44lbs (20kg)	-	-	-	-

DFG400





DFG460

CHNICAL SPECS

DFG 460-4	DFG 460-5	DFG 700-1	DFG 700-2
Electric	Electric	Electric	Electric
230V Variable Optional	110V	400V/460V	400V/460V
3hp (2.2kW)	3hp (2.2kW)	14.7hp (11kW)	14.7hp (11kW)
50Hz/60Hz	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz
0 - 277rpm	231rpm	3 x 180rpm/400rpm	3 x 400rpm
0 - 1704rpm	1420rpm	2800rpm	2800rpm
41" (1040mm)	41" (1040mm)	61.8" (1570mm)	61.8" (1570mm)
18.5" (470mm)	18.5" (470mm)	26.8" (680mm)	26.8" (680mm)
42.5" (1080mm)	42.5" (1080mm)	43" (700mm)	43" (700mm)
273lbs (124kg)	273lbs (124kg)	642lbs (292kg)	631lbs (287kg)
		2 x 44lbs (20kg)	2 x 44lbs (20kg)