



Ideal for spraying all types of curing compounds after finish work is completed.

- The best pump in the industry.
- Sprays materials with a variable pressure between 40 and 120 psi while constantly agitating material.
- Easily handles form oils, pigmented curing compounds, bond breakers, soaps and detergents, pest control liquids, and most liquid type material.
- Handles white pigment curing compounds up to 40% solids. (S201)
- S151 can handle up to 20% solids
- · Designed to be used from a truck, dock, work platform, dolly or skid.

Exclusive wear adjustment feature increases pump life as much as

- 200% (S201)
- · Powered by dependable Honda engines.
- Comes with 25' (7.6m) of 3/8" (0.95cm) hose and adjustable spray nozzle that can be disassembled for easy cleaning. Barrel not included.

Options

- Hose Lengths: 50' (15.2m), 75' (22.7m) or 100' (30.5m)
- Fan Spray Nozzle
- · Shown with hand cart
- Tow Cart





	Specification S201 & S151
Pressure	Between 40 and 120 psi
Engine	GX120
Hose Length Options	25' (7.6m), 50' (15.2m), 75' (22.8m)
Flow Rate	8gal/minute (30L/min)
Shipping Weight	120lbss (55kg)
Max Solids	S151 20% S201 40%

Additional information on accessories and consumables for our Sprayers is available through our website, or contacting us directly.









