



WET CONCRETE CONCRETE VIBRATOR



- Power Options - Four different electric motors 0.8 kW to 2.4 kW, and Honda 1.9 kW GXH50 series gas powered back pack unit.
- Heads available from 3/4" to 2.5" as well as rubber coated.
- Shaft lengths from 6' to 18'.
- Made in the USA.
- Quick release vibrator shafts for ease in changes.
- Interchangeable with many competitive brands.



Morrison #	Motor (HP)
MVM114	1.21
MVM134	1.75
MVM225	2.28
MVM325	3.22
MVPBP212	2.55 (Gasoline / Petrol)

4 Powerful Models			Maximum Head Size	
Model	Amps	kW	Steel	Rubber
MVS6P	9	0.9	1.5"	None
MVS9P	15	1.3	1.75"	None
MVS11P	17	1.7	2"	1.875", 2.75" short
MVS10	19	2.4	2.5"	69.9

Morrison #	Shaft (ft)
MVS6P	6
MVS9P	9
MVS11P	11
MVS10	10
MVS12	12
MVS14	14
MVS16	16
MVS18	18

Morrison #	Head Diameter (in / mm)
MVH34P	0.75 / 19.1
MVH100	1 / 25.4
MVH125	1.25 / 31.8
MVH112	1.5 / 38.1
MVH134	1.75 / 44.5
MVH178R	1.875 / 47.6
MVH200	2 / 50.8
MVH212	2.5 / 63.5

Head Diameter (in)	Radius of Action (in)	X=1 1/2 Times Radius of Action (in)	Amplitude Centerline to Side (in)	Centrifugal Force (kN)	Compaction Rate (cu. m./hour)
STEEL HEADS					
0.75	2.9	5	0.03	0.7	0.7-2.3
1	4	5.9	0.04	1.0	1.5-3.1
1.25	5	7.9	0.04	2.3	1.5-3.8
1.5	5.9	9.01	0.05	4.1	3.8-6.1
1.875	9	14.02	0.08	5.3	6.1-12.2
2	11.4	17.01	0.07	6.7	9.2-15.3
2.5	12.9	20	0.08	8.2	17.6-22.9
RUBBER HEADS					
1.875	11.4	16	0.09	6.3	7.6-13.8
2.5	14	20	0.12	8.5	10.7-16.8
2.75	18	27	0.12	9.3	19.1-26.8
2.75 short	15	22	0.12	4.9	6.9-11.5



www.Discount-Equipment.com