



www.Discount-Equipment.com



GRINDERS & POLISHERS



SHOTBLASTERS



FLOOR REMOVAL



SCARIFIERS



SCREED



TROWELS



BARTELL morrison



Innovatech

CONTEC NORTH AMERICA


PRECISION METAL WORKS



SAWS



TOOLING & CONSUMABLES



DIAMOND BLADES



SPREADERS



COMPACTION



GENERATORS



MIXERS

SCREED

PRODUCT CATEGORY



morrison
BARTELL GLOBAL

FEATURES AND BENEFITS



UNI-SCREED

FEATURES

- Specially designed to permit a single operator to quickly and easily level an entire area.
- Adjustable handle to meet operator needs and more efficient handling.
- Handle vibration is minimized with our impact absorbing mounting system to optimize control and operator comfort.
- Superior control is achieved with our responsive handle mounted throttle and on/off switch.
- High frequency vibration disperses and levels concrete without build-up.
- Lightweight, easy to transport to and around job sites.
- Blade design permits cutting and smoothing in a single operation.
- Interchangeable blades with other leading wet screed units.



STANDARD SCREED

FEATURES

- High frequency vibrations are distributed evenly across entire aluminum screed length to produce smooth, uniform surfaces quickly and easily.
 - Standard truss is 13.5" tall and can span 40'
 - Can consolidate less than 2" slump. Up to 12" in depth
 - Morrison screed vibrates at over 14,000 vpm
 - Aluminum screed weighs only 9lbs / ft. compared to steel screed at up to 20lbs
 - Lightweight makes our screed suitable for use on any type or form. Morrison aluminum screed is lighter and easier to move around the job site, but consolidates better than steel due to the higher rate of vpm
 - Loose bearing system - Only Morrison screed has the patented loose bearing system
- Our screed will continue to operate even losing up to 20% of the shaft bearings, while competitor's screed will stop after one bearing fails. A bearing never fails while it's sitting dormant, only when it's on the job
- Available in hydraulic travel or hand winch



SUPER SCREED

FEATURES

- High frequency vibrations are distributed evenly across entire aluminum screed length to produce smooth, uniform surfaces quickly and easily.
 - Super truss is 19.5" tall and can span 80'
 - Can consolidate less than 2" slump. Up to 12" in depth
 - Morrison screed vibrates at over 14,000 vpm
 - Lightweight makes our screed suitable for use on any type or form. Morrison aluminum screed is lighter and easier to move around the job site, but consolidates better than steel due to the higher rate of vpm
 - Loose bearing system - Only Morrison screed has the patented loose bearing system
- Our screed will continue to operate even losing up to 20% of the shaft bearings, while competitor's screed will stop after one bearing fails. A bearing never fails while it's sitting dormant, only when it's on the job
- Available in hydraulic travel or hand winch

COMPLETE LINE



STANDARD SCREED



SUPER SCREED

TECHNICAL SPECS

Height	13.5" (34cm)	19.5" (50cm)
Width	12" (30cm)	15" (37cm)
Weight	10lbs/foot (4.5kg/30cm)	15lbs/foot (6kg/30cm)
10' (3m) Base Section	79lbs (36kg)	94lbs (43kg)
2.5' (0.75m) Section	23lbs (10kg)	38lbs (17kg)
5' (1.5m) Section	45lbs (20kg)	76lbs (34kg)
10'(3m) Section	79lbs (36kg)	79lbs (36kg)
Motor with Mount	53lbs (24kg)	70lbs (32kg)
Engine	Honda GX160	Honda GX270
Max Recommended Span	40' (12m)	80' (24m)
Average Peak Vibration	12,830 rpm	14,000 rpm
Max Compaction Depth	12" (30cm)	12" (30cm)

TECHNICAL SPECS

Handle	28lbs (12.7kg)
Blades	
4' (1.2m)	6.4lbs (2.9kg)
6' (1.8m)	9.6lbs (4.4kg)
8' (2.4m)	12.8lbs (5.8kg)
10' (3m)	16lbs (7.3kg)
12' (3.7m)	19.2lbs (8.7kg)
14' (4.5m)	22.4lbs (10.2kg)
16' (4.9m)	25.6lbs (11.6kg)
Engine	GX35
Fuel Capacity	0.17 Gal (0.65L)
Estimated Running Time	1.1hrs @ 7000rpm
Weight (dry)	27.9lbs + blade (12.7kg + blade)
Weight (operating)	29.6lbs + blade (13.5kg + blade)
Sound Power	50 Dba
Vibration	<9 m/s ²



UNI-SCREED