### SPECIFICATIONS: 912SM/912HM

| Dimensions: | U.S.    | Metric:   |
|-------------|---------|-----------|
| Weight      | 620 lbs | 281.23 kg |
| Height      | 43"     | 1.09 m    |
| Length      | 81"     | 2.06 m    |
| Width       | 28"     | 711.2 mm  |
| Wheel Base  | 30"     | 762 mm    |

#### **Engine Options\*:**

Subaru (HP: 9) EX27 **EX27** GX270 Honda (HP: 8.5) GX270 Fuel Gasoline Gasoline

#### Additional Specs:

| Hydraulic Reservoir  | 9.5 gallons | 35. |
|----------------------|-------------|-----|
| Ground Drive Forward | 132 ft/min  | 40  |
| Ground Drive Reverse | 58 ft/min   | 17. |
| Digging Chain Speed  | 227 ft/min  | 69. |
|                      |             |     |

\*EX27 specs per http://robinamerica.com/pfeatures.aspx?pid=10 GX270 specs per http://engines.honda.com/models/model-detail/gx270

.96 liters .23 m/min .68 m/min 19 m/min



www.discount-equipment.com

BARRETO

المكافر أواله المان في بدر مطالحة إردوا الله وأوال المراجع المراجع الله فالم الدوم

# 912SM/912HM MINI TRENCHER

# DESIGN

Sometimes the job demands a more compact approach without sacrificing production speed. To meet the needs of the residential contractor who may be working in tight spaces, this self-propelled trencher can easily handle sprinkler systems, electrical lines, and other shallow trench applications. The 912 saves on space while still providing the horsepower necessary to trench up to 24" deep. The boom pivot design keeps high wear components out of the dirt and is easily maintained. The front end pivots on a pin instead of a boom pivot bushing. This reduces maintenance issues often caused by dirt and debris.

# CONTROLS

The control panel is simple and understandable for even the novice operator. The safety clutch engages and disengages the wheel and chain drives. When the clutch is released, the engine continues to run and the controls remain in place, ready to resume trenching at any time. Variable speed drive allows the operator to adjust their wheel speed to the soil conditions. The reversible chain drive can be operated manually to dislodge obstructions or debris.

# ROI

Trenchers can become one of your leading revenue sources. With a unique design that provides limited need for maintenance and repair, the 912 won't be tying up your revenue or your mechanic. It will stay in the field and get the job done. Because Barreto trenchers are reliable in the most difficult conditions, customer satisfaction is high. When the customer is provided with a piece of equipment that makes their job this easy, they keep coming back.

## FEATURES



Reliable hydraulic design keeps efficiency high and maintenance low



Simple controls are easy to operate with no color codes to remember



Free wheeling hubs allow the operator to transport without the engine running



The innovative boom pivot design keeps the bushing out of the dirt




Reversible chain can be manually operated to dislodge debris

### CHAIN OPTIONS



Cup Chain



Double Cup Chain



ComboShark Chain



Welded Shark Chain



Bolted Shark Chain



12, 18 or 24" depth 4 or 6" width



www.discount-equipment.com

