

DYNA

Portable Generators by **WINCO**[®]



D3000H



NEW DL6000I

DYNA FEATURES

- ❑ PREMIUM CARB/EPA APPROVED HONDA OR BRIGGS & STRATTON ENGINES
- ❑ ALL COPPER WINDINGS AND CIRCUIT BREAKERS FOR OPERATOR SAFETY AND PROTECTION AGAINST DAMAGING OVERLOADS
- ❑ STURDY WRAP-AROUND WELDED TUBULAR CRADLES
- ❑ DURABLE, LONG LASTING POWDER PAINT FINISH
- ❑ LIGHT, COMPACT DESIGN FOR CONVENIENT STORAGE AND TRANSPORT
- ❑ LARGE FUEL TANKS FOR LONGER RUN TIMES (5kW AND LARGER)
- ❑ SIZES RANGING FROM 3kW TO 9kW

WINCO INC[®]

A Division of **DTI** Dyna Technology Inc

225 South Cordova Ave
Le Center MN 56057 USA

Telephone: (507) 357-6821
Fax: (507) 357-4857
East Coast: (800) 733-2112
West Coast & Canada: (800) 324-8174
E-Mail: wincosales@wincogen.com
Web Site: www.wincogen.com



D3000H



DL5000H



DL6000I



DL9000E


PERFORMANCE & TECHNICAL DATA

Model Number	D3000H	DL5000H	DL6000I/ DL6000IE	DL6000H/ DL6000HE	DL9000E
Electrical Specifications					
Maximum Power Rating	3000 watts	5000 watts	6000 watts	6000 watts	9000 watts
Continuous Power Rating**	2300 watts	4500 watts	5500 watts	5500 watts	8000 watts
A.C. Output Voltage	120 volts	120/240 volts	120/240 volts	120/240 volts	120/240 volts
Continuous Current Rating	19.1 amps	37.4/18.7 amps	45.8/22.9 amps	45.8/22.9 amps	66.7/33.3 amps
Motor Starting Ability (1)	.75 hp	1.5 hp	1.5 hp	2 hp	4 hp
Engine Data					
Make/Model	Honda GC160	Honda GX270	B&S/Intek	Honda GX340	B&S/Vanguard
Displacement/Type	160 cc/OHC	270 cc/OHV	342 cc/OHV	337 cc/OHV	480 cc/OHV
Rated Power (3600 RPM)	5 hp	9 hp	11 hp	11 hp	16 hp
Starting System (2)	Recoil	Recoil	(3)	(3)	Electric/Recoil
Fuel Tank Capacity	2 Qt.	4.5 Gallons	4.5 Gallons	4.5 Gallons	4.5 Gallons
Low Oil Protection	Standard	Standard	Standard	Standard	Standard
Running Time-Full Load	1.1 hours	6.6 hours	5.3 hours	4.5 hours	3.4 hours
Running Time-Half Load	1.5 hours	10.3 hours	8.5 hours	6.4 hours	5.6 hours
120 Volt Receptacles					
Straight Blade (NEMA 5-20R)	2-20 amp	2-20 amp	4-20 amp	4-20 amp	4-20 amp
120/240 Volt Receptacles					
Twist-Lock (NEMA L14-30R)	N/A	1-30 amp	1-30 amp	1-30 amp	1-30 amp
Size & Weight					
Dimensions (LxWxH)	20.75x15x16 in.	30x19x22 in.	26.25x17.5x21.4 in.	30x22x22 in.	32x22x22 in.
Shipping Weight	92 lbs.	150 lbs.	140/152 lbs.	202/210 lbs.	274 lbs.
Warranty Information - Consumer Application (4)					
Generator/Engine	2 yrs/1 yr	2 yrs/2 yrs	2 yrs/2 yrs	2 yrs/2 yrs	2 yrs/2 yrs
CSA Approved	Yes	Yes	Yes	No	Yes

NOTES: (1) Code G Capacitor Start Motor. (2) Electric start models include battery rack and cables. Battery not included.
 (3) Models DL6000I and DL6000H are recoil start only. Models DL6000IE and DL6000HE have both recoil and electric start.
 (4) Commercial or Prime Power (Off-Grid) Warranty - 90 Days; International Warranty - Contact WINCO for details.

** Power Output +/- 5%

DYNA 3/05



WINCO INC
 A Division of DTE Dyna Technology Inc
 225 South Cordova Ave, Le Center MN 56057
 TEL: (507) 357-6821 FAX: (507) 357-4857
 East Coast: (800) 733-2112
 West Coast & Canada: (800) 324-8174
 E-Mail: wincosales@wincogen.com
 Web Site: www.wincogen.com