

<b>Description</b>	W9500HE
<b>DB Rating @ 7 meters (23 ft.)</b>	71.00 dBA
<b>Electrical Specifications</b>	
<b>Maximum Power Rating (watts)</b>	9500 watts
<b>Continuous Power Rating (watts)</b>	8500 watts
<b>A.C. Output Voltage @ 60 Hz.</b>	120 / 240 volts
<b>Power Factor (pf)</b>	1.0 pf
<b>Continuous Current Rating (A.C. amps)</b>	35.4 amps @ 240 volts
<b>Motor Starting Ability (hp)</b>	5 hp (240 volt only)
<b>120 Volt Full Power</b>	45.8 amps
<b>Generator Type (R.F.B. / R.F.L. / R.A.B.)</b>	R.F.L.
<b>Mechanical Specifications</b>	
<b>Generator Speed (rpm)</b>	3600 rpm
<b>Brushless</b>	Yes
<b>Single Point Lifting Eye</b>	Optional
<b>Engine Specifications</b>	
<b>Make / Model</b>	Honda / GX610
<b>Displacement / Type</b>	610 cc / OHV
<b>Rated Power @3600 rpm</b>	18 hp
<b>Engine Speed</b>	3600 rpm
<b>Low Oil Protection</b>	Standard
<b>Starting System</b>	Electric
<b>Cooling System</b>	Air
<b>Recommended Battery Size (Group/CCA)</b>	U1 / 235 cca
<b>Gasoline Information</b>	
<b>Fuel Tank Capacity</b>	4.5 gallons
<b>Running Time (Full Load)</b>	3.2 hours
<b>Running Time (Half Load)</b>	5.3 hours
<b>120 Volt Receptacles</b>	
<b>Straight Blade (NEMA 5-15R)</b>	4 - 15 amp GFCI
<b>Straight Blade (NEMA 5-50R)</b>	1 - 50 amp
<b>Twist Lock (NEMA L5-20R)</b>	2 - 20 amp / GFCI Protected
<b>Straight Blade (NEMA 6-15R)</b>	1 - 50 amp
<b>Twist Lock (NEMA L6-20R)</b>	1 - 20 amp
<b>120 / 240 Volt Receptacles</b>	
<b>Twist Lock (NEMA L14-30R)</b>	1 - 30 amp
<b>Circuit Breakers</b>	
<b>Main Breaker</b>	Standard
<b>Other Circuit Breakers</b>	Standard
<b>Size &amp; Weight</b>	

<b>L x W x H( in.)†</b>	32 x 22 x 22 in.
<b>Warranty Information</b>	
<b>Generator</b>	2 yrs
<b>Engine</b>	2 yrs
<b>Accessories</b>	
<b>2 Wheel Dolly Kit</b>	16204-000
<b>4 Wheel Dolly Kit</b>	16199-001
<b>Cover</b>	64444-012
<b>Transfer Switches</b>	
<b>EMER-TRANS SYS/SW60/30</b>	Suggested